



## DECLARATION OF PERFORMANCE

No: KTA 01:28/01/2022

1. Unique identification code of the product – type: **ULTRAFLEX01**
2. Intended use/es: **Improved cementitious adhesive with reduced slip and extended open time for internal and external tiling**
3. Manufacturer: **Knauf Cyprus Ltd, Christou Zeipekki 1, 4504 Vasa Kellakiou  
Tel. +357-25821040, Fax +357-25821043, E-Mail: knauf@knauf.com.cy**
4. System/s **System 3**
5. Harmonized standard: **CYS EN 12004:2017**  
Notified body/ies **EBETAM NB.0437**
6. Declared performance/s:

Essential characteristics	Performance	Harmonized standard
Reaction to fire	Class A1	CYS EN 12004:2017
Realease of dangerous substances	see MSDS	
Bond strength as		
- initial tensile adhesion strength:	$\geq 1\text{N/mm}^2$	
Durability, for		
- tensile adhesion strength after heat agent	$\geq 1\text{N/mm}^2$	
- tensile adhesion strength after water immersion	$\geq 1\text{N/mm}^2$	
- tensile adhesion strength after freeze/thaw cycles	$\geq 1\text{N/mm}^2$	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No. 305/2011, with the sole responsibility of the manufacturer identified above.

Signed for and behalf of the manufacturer by:  
Marina Christodoulou  
(Plant manager)

Limasol / Cyprus, on 28.04.2022