

## **Visona Unity**

Demountable acoustic ceiling

Product datasheet

07/2025



### **Description**

Visona is a demountable acoustical ceiling for mounting in a T-grid. The rectangular tiles offer a directional look and design to the ceiling surface.



### **Features**

- T-grid ceiling
- Rectangular ceiling tiles
- Installation from below the T-grid

### **Recyclable product**

- Made of gypsum
- Danish Indoor Climate Labelling
- Improved indoor climate
- Repaintable without loss of acoustics
- Product is recyclable and can be reused in the production of new gypsum boards and gypsum tiles

## Product specifics

<b>Edge design</b>	 <p>Lay-in tile in recessed grid lengthwise      No cross tees between tiles crosswise</p>
<b>Perforation design</b> Also available without perforations (Regula)	
<b>Perforation measures</b>	Unity 3 Square 3,5 x 3,5mm c/c 8,33mm
<b>Perforation %</b>	17,2%
<b>NRC, @ 200mm, no mineral wool</b>	0,80
<b>NRC, @ 200mm, 50mm mineral wool</b>	0,90
<b>Alpha-W, @ 200mm, no mineral wool</b>	0,80
<b>Alpha-W, @ 200mm, 50mm mineral wool</b>	0,90
<b>Light reflection</b>	69,2%
<b>Tile weight</b>	8,3 kg/m <sup>2</sup>
<b>Sizes, mm</b>	400 x 1200 x 12,5mm
<b>Surface treatment</b>	Front: White acrylic paint, RAL 9003, gloss 5 Back: Acoustic felt backing Available in other colours on request
<b>System components</b>	1) Gypsum ceiling tile, 2) T24/38 main runner, 3) Primary profile, 4) Hangers
<b>Certificates</b>	1) Environmental product declaration, 2) FDES - life cycle analysis, 3) Danoish Indoor Climate Labelling, 4) ISO 1600-9 Emission of VOCs, 5) UL-listed in accordance to R26164
<b>Fire rating</b>	A2-s1, d0
<b>Air quality</b>	Indoor value: 10 days Particle emission: LOW
<b>Ambient conditions</b>	Can withstand: constant RH 70% and 25°C ambient temperatures of up to 50°C
<b>Load-bearing capacity</b>	Up to 1 kg. pr. tile (at max 2mm deflection)