

# ***KNAUF***

## ***HERADESIGN® Fine Plus***



©Peter Smith

HERADESIGN® Fine Plus is a two layer, magnesite bonded, wood wool acoustic ceiling and wall panel.

- Two-layer acoustic panel as a composite product with mineral wool absorber
- Provides trickle protection
- Excellent sound absorption values

## ***Build on us.***

Characteristics	Detailed information																																																																
System	<p>B2.1, B2.2</p>																																																																
Edge details	<p>AK-01 Plus</p> <p>SK-04 Plus</p>																																																																
Dimensions (mm)	<p>1200 x 600</p>																																																																
Thickness (mm)	<table border="1"> <tr> <td>40</td> <td>50</td> <td>65</td> </tr> <tr> <td>15/25</td> <td>25/25</td> <td>25/40</td> </tr> </table>		40	50	65	15/25	25/25	25/40																																																									
40	50	65																																																															
15/25	25/25	25/40																																																															
Weight (kg/m <sup>2</sup> )	<table border="1"> <tr> <td>10.5</td> <td>15.6</td> <td>16.9</td> </tr> </table>		10.5	15.6	16.9																																																												
10.5	15.6	16.9																																																															
Sound absorption	<table border="1"> <thead> <tr> <th rowspan="2">Thickness (mm)</th> <th rowspan="2">TCH (mm)</th> <th colspan="2">HERADESIGN® Acoustic lining</th> <th colspan="7">Frequencies (Hz), <math>\alpha_p</math></th> <th colspan="2">Entire range</th> <th rowspan="2">Class</th> </tr> <tr> <th>(mm)</th> <th>(kg/m<sup>3</sup>)</th> <th>125</th> <th>250</th> <th>500</th> <th>1000</th> <th>2000</th> <th>4000</th> <th>NRC</th> <th><math>\alpha_w</math></th> </tr> </thead> <tbody> <tr> <td>15</td> <td>225</td> <td>25</td> <td>90</td> <td>0.60</td> <td>0.90</td> <td>0.85</td> <td>0.75</td> <td>0.70</td> <td>0.85</td> <td>0.80</td> <td>0.75 (L)</td> <td>C</td> </tr> <tr> <td>25</td> <td>225</td> <td>25</td> <td>90</td> <td>0.60</td> <td>0.90</td> <td>0.90</td> <td>0.80</td> <td>0.80</td> <td>0.90</td> <td>0.85</td> <td>0.85 (L)</td> <td>B</td> </tr> <tr> <td>25</td> <td>225</td> <td>40</td> <td>90</td> <td>0.60</td> <td>0.85</td> <td>0.90</td> <td>0.80</td> <td>0.80</td> <td>0.85</td> <td>0.85</td> <td>0.85 (L)</td> <td>B</td> </tr> </tbody> </table> <p>*Other acoustic performances can be achieved.</p>		Thickness (mm)	TCH (mm)	HERADESIGN® Acoustic lining		Frequencies (Hz), $\alpha_p$							Entire range		Class	(mm)	(kg/m <sup>3</sup> )	125	250	500	1000	2000	4000	NRC	$\alpha_w$	15	225	25	90	0.60	0.90	0.85	0.75	0.70	0.85	0.80	0.75 (L)	C	25	225	25	90	0.60	0.90	0.90	0.80	0.80	0.90	0.85	0.85 (L)	B	25	225	40	90	0.60	0.85	0.90	0.80	0.80	0.85	0.85	0.85 (L)	B
Thickness (mm)	TCH (mm)	HERADESIGN® Acoustic lining			Frequencies (Hz), $\alpha_p$							Entire range		Class																																																			
		(mm)	(kg/m <sup>3</sup> )	125	250	500	1000	2000	4000	NRC	$\alpha_w$																																																						
15	225	25	90	0.60	0.90	0.85	0.75	0.70	0.85	0.80	0.75 (L)	C																																																					
25	225	25	90	0.60	0.90	0.90	0.80	0.80	0.90	0.85	0.85 (L)	B																																																					
25	225	40	90	0.60	0.85	0.90	0.80	0.80	0.85	0.85	0.85 (L)	B																																																					
Reaction to fire	<p>Euroclass B-s1,d0</p>																																																																
Thermal resistance	<table border="1"> <tr> <td>15/25 0.80 m<sup>2</sup>K/W</td> <td>25/25 0.90 m<sup>2</sup>K/W</td> <td>25/40 1.30 m<sup>2</sup>K/W</td> </tr> </table>		15/25 0.80 m <sup>2</sup> K/W	25/25 0.90 m <sup>2</sup> K/W	25/40 1.30 m <sup>2</sup> K/W																																																												
15/25 0.80 m <sup>2</sup> K/W	25/25 0.90 m <sup>2</sup> K/W	25/40 1.30 m <sup>2</sup> K/W																																																															
Humidity resistance	<p>Suitable for rooms with a constant humidity of up to 90%.</p>																																																																
Application areas	<p>A decorative and acoustically effective suspended ceiling and wall panel for use in interior spaces as well as roofed outdoor areas that are not directly exposed to environmental influences such as rain or pollutants.</p>																																																																
Installation	<p>The installation of HERADESIGN® acoustic panels should take place during the last phase of the job, and in temperature and humidity controlled conditions. All building activities which create dust must be completed before the start of installation. Store the panels flat and protect against moisture and dirt. The packaging does not protect the products against rain. HERADESIGN® products should be installed in strict accordance with Knauf Ceiling Solutions installation and storage guidelines.</p>																																																																
Designation code	<p>WW-EN 13168-L4W2-T2-S2-P2,TR5-CL3</p>																																																																
Special information	<ul style="list-style-type: none"> <li>Manufacturing tolerances in nominal dimensions: L4, W2, T2: ± 1mm, for lengths &gt; 1250mm L4: ± 2mm</li> <li>Maximum changes in dimension in standard climate 23° C/50 % relative humidity: ± 1 %</li> </ul>																																																																
Cleanability																																																																	
Colours	<p><b>Standard colours</b></p> <p><b>Vario Design Colours</b></p> <p>White* Nature** Black*** Granite Steel Green Marble Copper Oak Brass Sandstone Concrete</p> <p>*similar to RAL 9010  **similar to RAL 1015  ***similar to RAL 9005</p> <p>• Other colours from popular RAL and NCS colour systems are available.  • Deviations in colour and visual appearance may occur due to the rough fibre and panel surface.</p>																																																																
Sustainability																																																																	