




## Knauf Contur

Create a unique, monolithic looking, demountable surface with Knauf Contur concealed tiles, ideal for renovation projects due to its space saving installation and office projects due to its aesthetics.

*Product-Data-Sheet*



### Areas of Application

S24 T-grid

### Compliance Standards

EN14190:2014

### Key Benefits

- Concealed grid design
- Installation from below the T-grid
- Installation depth down to 63mm
- Demountable for access

**Build on us.**

Creation Date: 25/10/2023  
Revision Reference: 002  
Revision Date: 27/02/2025

## Performance Data

Reaction to Fire (R2F)	Stability of Ceiling elements	Flexural Strength
A2-s1, d0	Pass	Pass

## Ceiling Sound Absorption

Perforation Type	Alpha-W ( $\alpha_w$ ) and Sound Absorption Class (@200mm suspension depth, with no mineral wool)
Micro	0.65 - Class C
Globe	0.60 - Class C
Quadril	0.60 - Class C
Tangent	0.80 - Class B
Unity 3	0.80 - Class B
Unity 4	0.70 - Class C
Unity 8/15/20	0.60 - Class C

## Technical Information

Thickness (mm)	Width (mm)	Length (mm)	Edge Profile	Colour	Weight (kg/m <sup>2</sup> )	Perforation Type	Perforation shape & size (mm)	Perforation (%)	Material Number
12.5	600	600	D	White acrylic paint, RAL 9003, gloss 5	9.45-10.20	Plain	-	-	24929
12.5	600	600	D	White acrylic paint, RAL 9003, gloss 5	9.45-10.20	Micro	Square - 3x3 c/c 8.33	10.2	54460
12.5	600	600	D	White acrylic paint, RAL 9003, gloss 5	9.45-10.20	Globe	Circles - Ø6 c/c 15	10.2	24799
12.5	600	600	D	White acrylic paint, RAL 9003, gloss 5	9.45-10.20	Quadril	Square - 12x12 c/c 30	13.0	24804
12.5	600	600	D	White acrylic paint, RAL 9003, gloss 5	9.45-10.20	Tangent	Obround - 4x14 c/c 10x20	21.3	173220
12.5	600	600	D+	White acrylic paint, RAL 9003, gloss 5	9.45-10.20	Unity 3	Square - 3.5x3.5 c/c 8.3	17.2	471331
12.5	600	600	D+	White acrylic paint, RAL 9003, gloss 5	9.45-10.20	Unity 4	Circles Ø4 c/c 10	12.2	532683
12.5	600	600	D+	White acrylic paint, RAL 9003, gloss 5	9.45-10.20	Unity 8/15/20	Various circles Ø8/15/20	10.8	471325

## Sustainability

### Recycled Content

Pre-consumer recycled content: 12%

Post-consumer recycled content: 28%

Total recycled content: 40%

2024 average by weight for all acoustic products produced in Denmark, recycled gypsum & paper

### Recyclability

This product is fully recyclable when separated from other waste and disposed correctly.

### Substances of very high Concern (SVHC)

At the time of publication, under REACH UK and REACH EU regulations this product contains no SVHC. For more information please consult the Safety Data Sheet.

### Volatile Organic Compound Content (VOC)

<2 g/L.

## Storage and Handling

No special education is required for safe handling. To be stored and used at temperatures below 50°C. Store indoors, in a clean and dry area on a level base protected from direct moisture with humidities of less than 70% RH. Wear clean cotton gloves when handling ceiling tiles to avoid fingermarks.

## Packaging

Recycled cardboard wrapping, gypsum tile topper, FSC pallet, and recyclable PE shrink wrap around the pallet.

## Service Life

### 60 years service life. Can withstand:

- constant RH 70% and 25°C
- periodic RH 90% and 30°C
- ambient temperatures of up to 50°C

## Disposal/Repair

Dust should be removed using a dry duster or vacuum cleaner. Marks can be removed with a damp cloth. Disposal should be in accordance with local authority requirements. European waste catalogue code: 17 08 02 Gypsum based construction materials, keep apart from waste that comes under 17 08 01.

## Health & Safety

Please refer to our Safety Data Sheet for guidance on Personal Protection Equipment required for the handling and installation of this product.

## Application / Installation

For full installation instructions please see the installation guide on our website. Contur has a 'positive' and a 'negative' side; install the tiles by lifting the 'male' side up across the one main runner, then push the 'female' side into position on the opposing main runner, and lower the 'male' side onto the first main runner.

## Additional Documentation

[Declaration of Performance UKCA](#)

[Declaration of Performance CE](#)

[Safety Data Sheet](#)

## Certification

[Product Sustainability Credentials](#)

[Product Sustainability Credentials](#)

Product Accreditations:



Knauf UK GmbH Company Accreditations:



The information given in this publication is believed to be current and accurate as at the date of publication, but no warranty, express or implied is given. Updates will not be automatically issued © Copyright Knauf 2024

### Customer Service

UK Tel: 0800 521 050

Eire Tel: 01 4620739

Email: [cservice@knauf.com](mailto:cservice@knauf.com)

### Technical Service

Tel: 0800 521050 (option 2)

Email: [technical-uk@knauf.com](mailto:technical-uk@knauf.com)  
(excluding public holidays)

### UK Address

Knauf  
Kemsley Fields Business Park  
Sittingbourne  
Kent ME9 8SR

### Ireland Address

Knauf  
87 Broomhill Road  
Tallaght  
Dublin 24  
D24 WR85

Creation Date: 25/10/2023

Revision Reference: 002

Revision Date: 27/02/2025