

Note on English translation / Hinweise zur englischen Fassung

This is a translation of the product data sheet valid in Germany.

All stated details and properties are in compliance with the regulations of the German standards and building regulations. They are only applicable for the specified products, system components, application rules, and construction details in connection with the specifications of the respective certificates and approvals.

Knauf Gips KG denies any liability for applications outside of Germany as this requires changes acc. to the respective national standards and building regulations.

KNAUF

Plaster and Façade Systems

B1304_DSP.de

Product Data Sheet

2025-02



Fassadol

Silicone-reinforced façade paint for exteriors

Product description

Silicone-reinforced, highly colour shade fast and high coverage pure acrylic façade paint with a satin-matt appearance. It is vapour permeable, highly water-repellent and dries stress-free.

Composition

Pure acrylic, water-repellent agents, titanium dioxide, fillers, water, additives, colour pigments and preservatives.

Storage

The material can be stored for at least 24 months in the original container in a cool and frost-free environment. Close opened buckets airtight.

Quality

The product is subject to continuous factory production control and is compliant to EN 10621 as well as DIN 18363 section 2.4.1.

Properties and added value

- For exterior use
- Highly colour shade fast
- Very high coverage
- Diffusion permeable
- High filling capacity
- Colour shade white (approximately RAL 9003)
- Can be pigmented with the Knauf ColorConcept colour shade selector card

Silicone-reinforced façade paint for exteriors

Field of application

Fassadol paint is easy to apply. Fassadol is applied as the first coat or renovation coat after examination of the substrate and possible pretreatment of the substrate on:

- Mineral finishing renders (e.g. Noblo, SP 260 Pro)
- Organic renders (e.g. Conni, Addi)
- Silicate renders
- Old paint coats
- Lime sandstone
- Fibre cement boards
- Reinforced concrete (not on bridges)

Application

Substrate and pretreatment

Substrate	Pretreatment
Lime-based/cementitious mortar CS II/CS III acc. to EN 998-1	Pretreat coarse, porous, sanding, highly absorbent substrates with Grundol.
New mineral based renders (e.g. Noblo, SP 260 Pro)	Bright to pastel colour shades can be applied without a primer after sufficient drying time (at least 7 days). In case of intensive colour shades, a preliminary coat of Casiol Grund in approximately the same colour shade is recommended.
New organic top coats (e.g. Addi, Conni)	After sufficient drying time (generally 1 day per mm layer thickness, however at least 3 days), apply directly without pretreatment
Mineral based old renders	Knock out the cavities, clean the substrate thoroughly and apply render in accordance with the existing material and texture. Allow the newly rendered areas to dry sufficiently, and if necessary, apply fluosilicate treatment and wash off
Stable, but chalking or sanding surfaces	Pretreat with Grundol primer, the Tiefengrund primer must be fully absorbed beforehand.

Preparation

Check substrate for compliance with VOB part C, DIN 18350, DIN 18345 chapter 3.1 and/or according to VOB part B, DIN 1961 paragraph 4 no. 3. Clean the substrate of dust and remove loose parts, ensure that the surface is smooth. Preparation of the substrate in accordance with the substrate and pretreatment table. All substrates must be stable, dry, even and free of grease and dust as well as free of any residual substances that may reduce the adhesion. Please observe BFS - Code of Practice 9, section 5.2 (German only). Test existing coats (paint coats and old renders) for stability and compatibility before application of Fassadol. Cover easily-soiled building components before commencement in accordance with Code of Practice "Abklebe- und Abdeckarbeiten für Maler- und Stuckateurarbeiten - Masking and covering for painting and stucco work" (German only) issued by the German Bundesverband Ausbau und Fassade. Protect weather-exposed surfaces from precipitation and direct sunlight.

Application

Before work commences, check colour and batch numbers on all buckets as well as the colour shade by sampling (trial coat) to ensure it is correct. Never apply the content from different buckets together on a common wall. Mix the contents together in a clean bucket beforehand. Stir the contents of the bucket thoroughly. Fassadol paint is set ready to use by adding up to 5 % water. Dilution with up to 10 % water is possible as a primer coat. In case of over-dilution, the hiding power (opacity) and the guaranteed properties will be affected.

Apply Fassadol thin, evenly and edge-free *wet-in-wet* onto the stable and dry render surface, final coat or paint coat. Always complete surfaces that can be viewed together on the same day. Always complete a surface once started. Always work so that the transition areas between scaffolding are roll or brush applied *wet-in-wet*. Application is undertaken using a paint roller or paintbrush.

Application temperature / climate

Do not apply material at air and/or substrate temperatures below +5 °C and above +30 °C. Protect fresh coats from the effects of moisture, e.g. from precipitation and from the effects of rapid water loss, e.g. by exposure to direct sunshine or strong wind, by protecting with suitable measures such as protective nets. Do not apply Fassadol onto preheated substrates.

Drying time

Fassadol is touch dry at +20 °C and 65 % relative humidity after approx. 12 hours. The times are extended at lower temperatures and/or higher levels of air humidity. A minimum drying time of 24 hours and a maximum of 7 days is necessary between coats. Fully dry and ready-to-use after at least 3 days.

Note

Paint coats have to be applied according to DIN 18363 VOB part C section 3 as well as the generally recognized building engineering rules and valid guidelines. Work *fresh-in-fresh* in a single work step to avoid the formation of visible edging. Differences in the colour shade and surface shading may occur due to different weather-related and building site conditions.

When reordering, always state the consignment number of the previous delivery.

Note

Should dark coloured surfaces be exposed to high mechanical loading, the colour may change at affected locations (crazing). This does not affect the product quality and functionality.

Depending on the colour shade, there may be a reduced opacity with very bright, intensive colour shades. We recommend application to a trial surface, and if necessary, an additional final coat may be required.

Note

Fassadol is formulated ex-works with biocide film preservation. It protects the product against algae and mould growth. Permanent protection against algae and mould cannot be guaranteed, as the susceptibility depends on the local and environmental conditions.

Technical data

Description	Standard	Unit	Fassadol
Gloss	EN ISO 2813	Class	G ₃ matt
Dry film thickness	EN 1062-1	Category	E ₃ , > 100 ≤ 200 µm
Grain size	EN ISO 1524	Category	S ₁ fine
Water vapour transmission rate	EN ISO 7783-2	Category	V ₁ high*
Liquid water permeability	EN 1062-3	Category	W ₃ low
Colour shade durability	BFS code of practice no. 26	Category	B
Density	–	kg/l	1.55
VOC content	Directive 2004/42/EC, annex II, table A (Limit value product sub-category c: 40 g/l)	g/l	≤ 40

The stated technical data were evaluated acc. to the respective test standards. Deviations under site conditions are possible.

* The stated values apply only for the basis white paint. Pigments may deviate depending on the colour shade.

Material requirement and efficiency

Substrate	Application	Consumption approx. l/m ²	Yield approx. 5.0 l / 12.5 l m ² /bucket
Smooth	Single coat	0.20	25.0 / 62.5
	Double coat	0.30	17.0 / 42.0
Rough	Single coat	0.30	17.0 / 42.0
	Double coat	0.45	11.0 / 28.0

The exact consumption can only be determined with a test application on the individual object.

Product range

Description	Application	Paint	Packaging unit	Material number	EAN
Fassadol	12.5 l	White	32 buckets/pallet	00078636	4003950057731
		Pigmented		00080899	4003950060458
	5.0 l	White	68 buckets/pallet	00080752	4003950059636
		Pigmented		00080753	4003950059650

**Observe safety data sheet!**

For safety data sheets and CE marking see
pd.knauf.de



Videos for Knauf systems and products can be found under the
 following link:
youtube.com/knauf



All Knauf Gips documents are available in an up-to-date and
 clearly organised format in the [Download Center](#) at
www.knauf.com.

Knauf Direct

Technical Advisory Service:

▶ knauf-direkt@knauf.com

▶ www.knauf.com

Knauf Gips KG Am Bahnhof 7, 97346 Iphofen, Germany

All technical changes reserved. Only the current printed instructions are valid. The stated information represents current state-of-the-art Knauf technology. The entire state of approved engineering rules, appropriate standards, guidelines, and rules of craftsmanship are not included herewith. These and all application instructions have to be adhered to separately by the installer. Our warranty is expressly limited to our products in flawless condition. All application quantities and delivery amounts are based on empirical data that are not easily transferable to other deviating areas.

All rights reserved. All amendments, reprints and photocopies, including those of excerpts, require our expressed permission.