

## Aquapanel Joint Filler Grey

### Knauf UK & Ireland GmbH

Version No: 3.1

Safety Data Sheet (Conforms to Annex II of REACH (1907/2006) - Regulation 2020/878)

Issue Date: 01/02/2024

Print Date: 04/06/2024

L.REACH.IRL.EN.E

## SECTION 1 Identification of the substance / mixture and of the company / undertaking

### 1.1. Product Identifier

|                               |                             |
|-------------------------------|-----------------------------|
| Product name                  | Aquapanel Joint Filler Grey |
| Chemical Name                 | Not Applicable              |
| Synonyms                      | Not Available               |
| Chemical formula              | Not Applicable              |
| Other means of identification | Not Available               |

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

|                          |  |
|--------------------------|--|
| Relevant identified uses | The product is used as a joint filling agent.<br>Use according to manufacturer's directions. |
| Uses advised against     | No specific uses advised against are identified.   |

### 1.3. Details of the manufacturer or supplier of the safety data sheet

|                         |  |
|-------------------------|--|
| Registered company name | Knauf UK & Ireland GmbH                                    |
| Address                 | 87 Broomhill Road Tallaght D24 WR85 Ireland                |
| Telephone               | 01 4620739   |
| Fax                     | Not Available  |
| Website                 | <a href="http://www.knauf.com">www.knauf.com</a>           |
| Email                   | <a href="mailto:cservice@knauf.com">cservice@knauf.com</a> |

### 1.4. Emergency telephone number

|                                   |                         |
|-----------------------------------|-------------------------|
| Association / Organisation        | Knauf UK & Ireland GmbH |
| Emergency telephone numbers       | 01 4620739 - 9am - 5pm  |
| Other emergency telephone numbers | 112 - HSE               |

## SECTION 2 Hazards identification

### 2.1. Classification of the substance or mixture

|  |   |
|--|---|
| Classification according to regulation (EC) No 1272/2008 [CLP] and amendments <sup>[1]</sup> | H315 - Skin Corrosion/Irritation Category 2, H318 - Serious Eye Damage/Eye Irritation Category 1, H335 - Specific Target Organ Toxicity - Single Exposure (Respiratory Tract Irritation) Category 3 |
| Legend:  | 1. Classification by vendor; 2. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI   |

### 2.2. Label elements

## Aquapanel Joint Filler Grey

|                     |   |
|---------------------|---|
| Hazard pictogram(s) |  |
|---------------------|---|

|             |               |
|-------------|---------------|
| Signal word | <b>Danger</b> |
|-------------|---------------|

## Hazard statement(s)

|      |                                   |
|------|-----------------------------------|
| H315 | Causes skin irritation.           |
| H318 | Causes serious eye damage.        |
| H335 | May cause respiratory irritation. |

## Supplementary statement(s)

Not Applicable

## Precautionary statement(s) General

|      |                                |
|------|--------------------------------|
| P102 | Keep out of reach of children. |
|------|--------------------------------|

## Precautionary statement(s) Prevention

|      |   |
|------|---|
| P261 | Avoid breathing dust/fumes.   |
| P271 | Use only outdoors or in a well-ventilated area.   |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. |

## Precautionary statement(s) Response

|                     |   |
|---------------------|---|
| P305+P351+P338+P310 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. |
| P302+P352           | IF ON SKIN: Wash with plenty of water and soap.   |
| P332+P313           | If skin irritation occurs: Get medical advice/ attention.   |
| P362+P364           | Take off contaminated clothing and wash it before reuse.  |
| P304+P340+P312      | IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.  |

## Precautionary statement(s) Storage

Not Applicable

## Precautionary statement(s) Disposal

|      |  |
|------|--|
| P501 | Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation. |
|------|--|

Material contains silica crystalline - quartz, portland cement, calcium hydroxide, portland cement, flue dust.

## 2.3. Other hazards

Inhalation and/or ingestion may produce health damage\*.

Cumulative effects may result following exposure\*.

Possible respiratory sensitizer\*.

REACH - Art.57-59: The mixture does not contain Substances of Very High Concern (SVHC) at the SDS print date.

## SECTION 3 Composition / information on ingredients

## 3.1.Substances

See 'Composition on ingredients' in Section 3.2

## 3.2.Mixtures

Continued...

## Aquapanel Joint Filler Grey

| 1. CAS No<br>2. EC No<br>3. Index No<br>4. REACH No                   | %<br>[weight] | Name   | Classification according to regulation (EC) No 1272/2008 [CLP] and amendments  | SCL / M-Factor  | Nanoform Particle Characteristics |
|---|---------------|--|--|---|-----------------------------------|
| 1. 14808-60-7<br>2. 238-878-4<br>3. Not Available<br>4. Not Available | 30-<40        | <u>silica</u><br><u>crystalline -</u><br><u>quartz</u> | Specific Target Organ Toxicity - Repeated Exposure Category 2; H373 <sup>[1]</sup>   | Not Available<br>Acute M factor: Not Available<br>Chronic M factor: Not Available | Not Available                     |
| 1. 65997-15-1<br>2. 266-043-4<br>3. Not Available<br>4. Not Available | 25-35         | <u>portland</u><br><u>cement</u>                       | Skin Corrosion/Irritation Category 2, Sensitisation (Skin) Category 1, Serious Eye Damage/Eye Irritation Category 1, Specific Target Organ Toxicity - Single Exposure (Respiratory Tract Irritation) Category 3, Germ Cell Mutagenicity Category 2, Specific Target Organ Toxicity - Repeated Exposure Category 2; H315, H317, H318, H335, H341, H373 <sup>[1]</sup> | Not Available<br>Acute M factor: Not Available<br>Chronic M factor: Not Available | Not Available                     |
| 1. 1305-62-0<br>2. 215-137-3<br>3. Not Available<br>4. Not Available  | 5-<10         | <u>calcium</u><br><u>hydroxide</u> *                   | Corrosive to Metals Category 1, Skin Corrosion/Irritation Category 1B, Serious Eye Damage/Eye Irritation Category 1; H290, H314, H318 <sup>[1]</sup>   | Not Available<br>Acute M factor: Not Available<br>Chronic M factor: Not Available | Not Available                     |
| 1. 68475-76-3<br>2. 270-659-9<br>3. Not Available<br>4. Not Available | 0.02-<1.5     | <u>portland</u><br><u>cement</u> ,<br><u>flue dust</u> | Skin Corrosion/Irritation Category 1A, Sensitisation (Skin) Category 1, Serious Eye Damage/Eye Irritation Category 1, Specific Target Organ Toxicity - Single Exposure (Respiratory Tract Irritation) Category 3, Carcinogenicity Category 1B, Hazardous to the Aquatic Environment Long-Term Hazard Category 1; H314, H317, H318, H335, H350i, H410 <sup>[1]</sup>  | Not Available<br>Acute M factor: Not Available<br>Chronic M factor: Not Available | Not Available                     |

**Legend:**

1. Classification by vendor; 2. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 3. Classification drawn from C&L; \* EU IOELVs available; [e] Substance identified as having endocrine disrupting properties

**SECTION 4 First aid measures****4.1. Description of first aid measures**

|                     |  |
|---------------------|--|
| <b>Eye Contact</b>  | <p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> <li>▶ Immediately hold eyelids apart and flush the eye continuously with running water.</li> <li>▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>▶ Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.</li> <li>▶ Transport to hospital or doctor without delay.</li> <li>▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul> |
| <b>Skin Contact</b> | <p>If skin or hair contact occurs:</p> <ul style="list-style-type: none"> <li>▶ Immediately flush body and clothes with large amounts of water, using safety shower if available.</li> <li>▶ Quickly remove all contaminated clothing, including footwear.</li> <li>▶ Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre.</li> <li>▶ Transport to hospital, or doctor.</li> </ul>   |
| <b>Inhalation</b>   | <ul style="list-style-type: none"> <li>▶ If fumes or combustion products are inhaled remove from contaminated area.</li> <li>▶ Lay patient down. Keep warm and rested.</li> <li>▶ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.</li> <li>▶ Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.</li> <li>▶ Transport to hospital, or doctor, without delay.</li> </ul>   |

Continued...

## Aquapanel Joint Filler Grey

|                  |  |
|------------------|--|
| <b>Ingestion</b> | <ul style="list-style-type: none"> <li>▶ <b>If swallowed do NOT induce vomiting.</b></li> <li>▶ If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.</li> <li>▶ Observe the patient carefully.</li> <li>▶ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.</li> <li>▶ Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.</li> <li>▶ Seek medical advice.</li> </ul> |
|------------------|--|

### 4.2 Most important symptoms and effects, both acute and delayed

See Section 11

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

For acute or short term repeated exposures to iron and its derivatives:

- ▶ Always treat symptoms rather than history.
- ▶ In general, however, toxic doses exceed 20 mg/kg of ingested material (as elemental iron) with lethal doses exceeding 180 mg/kg.
- ▶ Control of iron stores depend on variation in absorption rather than excretion. Absorption occurs through aspiration, ingestion and burned skin.
- ▶ Hepatic damage may progress to failure with hypoprothrombinaemia and hypoglycaemia. Hepatorenal syndrome may occur.
- ▶ Iron intoxication may also result in decreased cardiac output and increased cardiac pooling which subsequently produces hypotension.
- ▶ Serum iron should be analysed in symptomatic patients. Serum iron levels (2-4 hrs post-ingestion) greater than 100 ug/dL indicate poisoning with levels, in excess of 350 ug/dL, being potentially serious. Emesis or lavage (for obtunded patients with no gag reflex) are the usual means of decontamination.
- ▶ Activated charcoal does not effectively bind iron.
- ▶ Catharsis (using sodium sulfate or magnesium sulfate) may only be used if the patient already has diarrhoea.
- ▶ Deferoxamine is a specific chelator of ferric (3+) iron and is currently the antidote of choice. It should be administered parenterally. [Ellenhorn and Barceloux: Medical Toxicology]
- ▶ Manifestation of aluminium toxicity include hypercalcaemia, anaemia, Vitamin D refractory osteodystrophy and a progressive encephalopathy (mixed dysarthria-apraxia of speech, asterixis, tremulousness, myoclonus, dementia, focal seizures). Bone pain, pathological fractures and proximal myopathy can occur.
- ▶ Symptoms usually develop insidiously over months to years (in chronic renal failure patients) unless dietary aluminium loads are excessive.
- ▶ Serum aluminium levels above 60 ug/ml indicate increased absorption. Potential toxicity occurs above 100 ug/ml and clinical symptoms are present when levels exceed 200 ug/ml.
- ▶ Deferoxamine has been used to treat dialysis encephalopathy and osteomalacia. CaNa<sub>2</sub>EDTA is less effective in chelating aluminium.

[Ellenhorn and Barceloux: Medical Toxicology]

For acute or short-term repeated exposures to highly alkaline materials:

- ▶ Respiratory stress is uncommon but present occasionally because of soft tissue edema.
- ▶ Unless endotracheal intubation can be accomplished under direct vision, cricothyroidotomy or tracheotomy may be necessary.
- ▶ Oxygen is given as indicated.
- ▶ The presence of shock suggests perforation and mandates an intravenous line and fluid administration.
- ▶ Damage due to alkaline corrosives occurs by liquefaction necrosis whereby the saponification of fats and solubilisation of proteins allow deep penetration into the tissue.

Alkalis continue to cause damage after exposure.

INGESTION:

- ▶ Milk and water are the preferred diluents

No more than 2 glasses of water should be given to an adult.

▶ Neutralising agents should never be given since exothermic heat reaction may compound injury.

\* Catharsis and emesis are absolutely contra-indicated.

\* Activated charcoal does not absorb alkali.

\* Gastric lavage should not be used.

Supportive care involves the following:

- ▶ Withhold oral feedings initially.
- ▶ If endoscopy confirms transmucosal injury start steroids only within the first 48 hours.
- ▶ Carefully evaluate the amount of tissue necrosis before assessing the need for surgical intervention.
- ▶ Patients should be instructed to seek medical attention whenever they develop difficulty in swallowing (dysphagia).

SKIN AND EYE:

- ▶ Injury should be irrigated for 20-30 minutes.

Eye injuries require saline. [Ellenhorn & Barceloux: Medical Toxicology]

## SECTION 5 Firefighting measures

### 5.1. Extinguishing media

- ▶ There is no restriction on the type of extinguisher which may be used.
- ▶ Use extinguishing media suitable for surrounding area.

### 5.2. Special hazards arising from the substrate or mixture

Continued...

## Aquapanel Joint Filler Grey

|                             |             |
|-----------------------------|-------------|
| <b>Fire Incompatibility</b> | None known. |
|-----------------------------|-------------|

### 5.3. Advice for firefighters

|                              |   |
|------------------------------|---|
| <b>Fire Fighting</b>         | <ul style="list-style-type: none"> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ Wear breathing apparatus plus protective gloves in the event of a fire.</li> <li>▶ Prevent, by any means available, spillage from entering drains or water courses.</li> <li>▶ Use fire fighting procedures suitable for surrounding area.</li> <li>▶ <b>DO NOT</b> approach containers suspected to be hot.</li> <li>▶ Cool fire exposed containers with water spray from a protected location.</li> <li>▶ If safe to do so, remove containers from path of fire.</li> <li>▶ Equipment should be thoroughly decontaminated after use.</li> </ul>   |
| <b>Fire/Explosion Hazard</b> | <p>Under certain conditions the material may become combustible because of the ease of ignition which occurs after the material reaches a high specific area ratio (thin sections, fine particles, or molten states). However, the same material in massive solid form is comparatively difficult to ignite. Nearly all metals will burn in air under certain conditions. Some are oxidised rapidly in the presence of air or moisture, generating sufficient heat to reach their ignition temperatures.</p> <p>Others oxidise so slowly that heat generated during oxidation is dissipated before the metal becomes hot enough to ignite. Particle size, shape, quantity, and alloy are important factors to be considered when evaluating metal combustibility. Combustibility of metallic alloys may differ and vary widely from the combustibility characteristics of the alloys' constituent elements.</p> <p>Decomposition may produce toxic fumes of:<br/>silicon dioxide (SiO<sub>2</sub>)<br/>metal oxides</p> <p>When aluminium oxide dust is dispersed in air, firefighters should wear protection against inhalation of dust particles, which can also contain hazardous substances from the fire absorbed on the alumina particles.</p> <p>May emit poisonous fumes.<br/>May emit corrosive fumes.</p> |

## SECTION 6 Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

See section 8

### 6.2. Environmental precautions

See section 12

### 6.3. Methods and material for containment and cleaning up

|                     |   |
|---------------------|---|
| <b>Minor Spills</b> | <ul style="list-style-type: none"> <li>▶ Remove all ignition sources.</li> <li>▶ Clean up all spills immediately.</li> <li>▶ Avoid contact with skin and eyes.</li> <li>▶ Control personal contact with the substance, by using protective equipment.</li> <li>▶ Use dry clean up procedures and avoid generating dust.</li> <li>▶ Place in a suitable, labelled container for waste disposal.</li> </ul>   |
| <b>Major Spills</b> | <ul style="list-style-type: none"> <li>▶ Clear area of personnel and move upwind.</li> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ Wear full body protective clothing with breathing apparatus.</li> <li>▶ Prevent, by all means available, spillage from entering drains or water courses.</li> <li>▶ Consider evacuation (or protect in place).</li> <li>▶ No smoking, naked lights or ignition sources.</li> <li>▶ Increase ventilation.</li> <li>▶ Stop leak if safe to do so.</li> <li>▶ Water spray or fog may be used to disperse / absorb vapour.</li> <li>▶ Contain or absorb spill with sand, earth or vermiculite.</li> <li>▶ Collect recoverable product into labelled containers for recycling.</li> <li>▶ Collect solid residues and seal in labelled drums for disposal.</li> <li>▶ Wash area and prevent runoff into drains.</li> <li>▶ After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using.</li> <li>▶ If contamination of drains or waterways occurs, advise emergency services.</li> </ul> |

### 6.4. Reference to other sections

Personal Protective Equipment advice is contained in Section 8 of the SDS.

## SECTION 7 Handling and storage

### 7.1. Precautions for safe handling

Continued...

## Aquapanel Joint Filler Grey

|                                      |  |
|--------------------------------------|--|
| <b>Safe handling</b>                 | <ul style="list-style-type: none"> <li>▶ Avoid all personal contact, including inhalation.</li> <li>▶ Wear protective clothing when risk of exposure occurs.</li> <li>▶ Use in a well-ventilated area.</li> <li>▶ Prevent concentration in hollows and sumps.</li> <li>▶ <b>DO NOT enter confined spaces until atmosphere has been checked.</b></li> <li>▶ <b>DO NOT allow material to contact humans, exposed food or food utensils.</b></li> <li>▶ Avoid contact with incompatible materials.</li> <li>▶ <b>When handling, DO NOT eat, drink or smoke.</b></li> <li>▶ Keep containers securely sealed when not in use.</li> <li>▶ Avoid physical damage to containers.</li> <li>▶ Always wash hands with soap and water after handling.</li> <li>▶ Work clothes should be laundered separately. Launder contaminated clothing before re-use.</li> <li>▶ Use good occupational work practice.</li> <li>▶ Observe manufacturer's storage and handling recommendations contained within this SDS.</li> <li>▶ Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.</li> </ul> |
| <b>Fire and explosion protection</b> | See section 5  |
| <b>Other information</b>             | <ul style="list-style-type: none"> <li>▶ Store in original containers.</li> <li>▶ Keep containers securely sealed.</li> <li>▶ Store in a cool, dry area protected from environmental extremes.</li> <li>▶ Store away from incompatible materials and foodstuff containers.</li> <li>▶ Protect containers against physical damage and check regularly for leaks.</li> <li>▶ Observe manufacturer's storage and handling recommendations contained within this SDS.</li> </ul> <p>For major quantities:</p> <ul style="list-style-type: none"> <li>▶ Consider storage in bunded areas - ensure storage areas are isolated from sources of community water (including stormwater, ground water, lakes and streams).</li> <li>▶ Ensure that accidental discharge to air or water is the subject of a contingency disaster management plan; this may require consultation with local authorities.</li> </ul>  |

**7.2. Conditions for safe storage, including any incompatibilities**

|  |   |
|--|---|
| <b>Suitable container</b>  | <ul style="list-style-type: none"> <li>▶ Polyethylene or polypropylene container.</li> <li>▶ Check all containers are clearly labelled and free from leaks.</li> </ul>  |
| <b>Storage incompatibility</b>   | <ul style="list-style-type: none"> <li>▶ Avoid strong acids, acid chlorides, acid anhydrides and chloroformates.</li> <li>▶ Avoid contact with copper, aluminium and their alloys.</li> <li>▶ Segregate from alcohol, water.</li> </ul> |
| <b>Hazard categories in accordance with Regulation (EC) No 2012/18/EU (Seveso III)</b>                             | Not Available   |
| <b>Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of</b> | Not Available   |

**7.3. Specific end use(s)**

See section 1.2

**SECTION 8 Exposure controls / personal protection****8.1. Control parameters**

| Ingredient                 | DNELs<br>Exposure Pattern Worker   | PNECs<br>Compartment   |
|----------------------------|--|--|
| calcium hydroxide          | Dermal 14 mg/kg bw/day (Systemic, Chronic)<br>Inhalation 9.9 mg/m <sup>3</sup> (Systemic, Chronic)<br>Inhalation 1 mg/m <sup>3</sup> (Local, Chronic)<br>Inhalation 3 mg/m <sup>3</sup> (Local, Acute)<br><i>Dermal 5 mg/kg bw/day (Systemic, Chronic) *</i><br><i>Inhalation 1.7 mg/m<sup>3</sup> (Systemic, Chronic) *</i><br><i>Oral 0.5 mg/kg bw/day (Systemic, Chronic) *</i><br><i>Inhalation 0.3 mg/m<sup>3</sup> (Local, Chronic) *</i><br><i>Inhalation 4 mg/m<sup>3</sup> (Local, Acute) *</i> | 0.49 mg/L (Water (Fresh))<br>0.49 mg/L (Water - Intermittent release)<br>0.32 mg/L (Water (Marine))<br>1080 mg/kg soil dw (Soil)<br>3 mg/L (STP) |
| portland cement, flue dust | Inhalation 0.84 mg/m <sup>3</sup> (Local, Chronic)<br>Inhalation 4 mg/m <sup>3</sup> (Local, Acute)  | 282 µg/L (Water (Fresh))<br>282 µg/L (Water - Intermittent release)  |

Continued...

## Aquapanel Joint Filler Grey

| Ingredient | DNELs<br>Exposure Pattern Worker                     | PNECs<br>Compartment   |
|------------|--|--|
|            | Inhalation 0.84 mg/m <sup>3</sup> (Local, Chronic) * | 28 µg/L (Water (Marine))<br>875 µg/kg sediment dw (Sediment (Fresh Water))<br>88 µg/kg sediment dw (Sediment (Marine))<br>5 mg/kg soil dw (Soil)<br>6 mg/L (STP) |

\* Values for General Population

## Occupational Exposure Limits (OEL)

## INGREDIENT DATA

| Source   | Ingredient                  | Material name  | TWA                   | STEL                | Peak          | Notes             |
|--|-----------------------------|--|-----------------------|---------------------|---------------|-------------------|
| European Union Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens or mutagens at work | silica crystalline - quartz | Respirable crystalline silica dust-Respirable fraction                           | 0,1 mg/m <sup>3</sup> | Not Available       | Not Available | Not Available     |
| Ireland Occupational Exposure Limits   | silica crystalline - quartz | Silica, crystalline, respirable dust, (Cristobalite, Quartz, Tridymite, Tripoli) | 0.1 mg/m <sup>3</sup> | Not Available       | Not Available | Schedule 3, BOELV |
| EU Consolidated List of Indicative Occupational Exposure Limit Values (IOELVs)   | calcium hydroxide           | Calcium dihydroxide  | 1 mg/m <sup>3</sup>   | 4 mg/m <sup>3</sup> | Not Available | Not Available     |
| Ireland Occupational Exposure Limits   | calcium hydroxide           | Calcium dihydroxide - Respirable Fraction  | 1 mg/m <sup>3</sup>   | 4 mg/m <sup>3</sup> | Not Available | IOELV             |

## Emergency Limits

| Ingredient                  | TEEL-1                  | TEEL-2                | TEEL-3                  |
|-----------------------------|-------------------------|-----------------------|-------------------------|
| silica crystalline - quartz | 0.075 mg/m <sup>3</sup> | 33 mg/m <sup>3</sup>  | 200 mg/m <sup>3</sup>   |
| calcium hydroxide           | 15 mg/m <sup>3</sup>    | 240 mg/m <sup>3</sup> | 1,500 mg/m <sup>3</sup> |

| Ingredient                  | Original IDLH                               | Revised IDLH  |
|-----------------------------|---|---------------|
| silica crystalline - quartz | 25 mg/m <sup>3</sup> / 50 mg/m <sup>3</sup> | Not Available |
| portland cement             | 5,000 mg/m <sup>3</sup>                     | Not Available |
| calcium hydroxide           | Not Available                               | Not Available |
| portland cement, flue dust  | Not Available                               | Not Available |

## Occupational Exposure Banding

| Ingredient                 | Occupational Exposure Band Rating   | Occupational Exposure Band Limit |
|----------------------------|---|----------------------------------|
| portland cement            | E   | ≤ 0.01 mg/m <sup>3</sup>         |
| portland cement, flue dust | E   | ≤ 0.01 mg/m <sup>3</sup>         |
| <b>Notes:</b>              | <i>Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.</i> |                                  |

## MATERIAL DATA

## 8.2. Exposure controls

## 8.2.1. Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.

Employers may need to use multiple types of controls to prevent employee overexposure.

Continued...

## Aquapanel Joint Filler Grey

Local exhaust ventilation usually required. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection.

An approved self contained breathing apparatus (SCBA) may be required in some situations.

Provide adequate ventilation in warehouse or closed storage area. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

| Type of Contaminant:  | Air Speed:                   |
|---|------------------------------|
| solvent, vapours, degreasing etc., evaporating from tank (in still air).  | 0.25-0.5 m/s (50-100 f/min.) |
| aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation) | 0.5-1 m/s (100-200 f/min.)   |
| direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)  | 1-2.5 m/s (200-500 f/min.)   |
| grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).  | 2.5-10 m/s (500-2000 f/min.) |

Within each range the appropriate value depends on:

| Lower end of the range                                     | Upper end of the range           |
|--|----------------------------------|
| 1: Room air currents minimal or favourable to capture      | 1: Disturbing room air currents  |
| 2: Contaminants of low toxicity or of nuisance value only. | 2: Contaminants of high toxicity |
| 3: Intermittent, low production.                           | 3: High production, heavy use    |
| 4: Large hood or large air mass in motion                  | 4: Small hood-local control only |

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

### 8.2.2. Individual protection measures, such as personal protective equipment



### Eye and face protection

- ▶ Safety glasses with unperforated side shields may be used where continuous eye protection is desirable, as in laboratories; spectacles are not sufficient where complete eye protection is needed such as when handling bulk-quantities, where there is a danger of splashing, or if the material may be under pressure.
- ▶ Chemical goggles. Whenever there is a danger of the material coming in contact with the eyes; goggles must be properly fitted. [AS/NZS 1337.1, EN166 or national equivalent]
- ▶ Full face shield (20 cm, 8 in minimum) may be required for supplementary but never for primary protection of eyes; these afford face protection.
- ▶ Alternatively a gas mask may replace splash goggles and face shields.
- ▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

### Skin protection

See Hand protection below

### Hands/feet protection

- ▶ Elbow length PVC gloves

#### NOTE:

- ▶ The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.
- ▶ Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.

Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:

- frequency and duration of contact,
- chemical resistance of glove material,

## Aquapanel Joint Filler Grey

|                         |   |
|-------------------------|---|
|                         | <ul style="list-style-type: none"> <li>· glove thickness and</li> <li>· dexterity</li> </ul> <p>Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).</p> <ul style="list-style-type: none"> <li>· When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.</li> <li>· When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.</li> <li>· Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use.</li> <li>· Contaminated gloves should be replaced.</li> </ul> <p>As defined in ASTM F-739-96 in any application, gloves are rated as:</p> <ul style="list-style-type: none"> <li>· Excellent when breakthrough time &gt; 480 min</li> <li>· Good when breakthrough time &gt; 20 min</li> <li>· Fair when breakthrough time &lt; 20 min</li> <li>· Poor when glove material degrades</li> </ul> <p>For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended.</p> <p>It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.</p> <p>Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers technical data should always be taken into account to ensure selection of the most appropriate glove for the task.</p> <p>Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:</p> <ul style="list-style-type: none"> <li>· Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.</li> <li>· Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential</li> </ul> <p>Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.</p> <ul style="list-style-type: none"> <li>▶ Neoprene rubber gloves</li> </ul> <p>Experience indicates that the following polymers are suitable as glove materials for protection against undissolved, dry solids, where abrasive particles are not present.</p> <ul style="list-style-type: none"> <li>▶ polychloroprene.</li> <li>▶ nitrile rubber.</li> <li>▶ butyl rubber.</li> <li>▶ fluorocautchouc.</li> <li>▶ polyvinyl chloride.</li> </ul> <p>Gloves should be examined for wear and/ or degradation constantly.</p> |
| <b>Body protection</b>  | See Other protection below  |
| <b>Other protection</b> | <ul style="list-style-type: none"> <li>▶ Overalls.</li> <li>▶ P.V.C apron.</li> <li>▶ Barrier cream.</li> <li>▶ Skin cleansing cream.</li> <li>▶ Eye wash unit.</li> </ul>  |

## Ansell Glove Selection

| Glove — In order of recommendation |
|------------------------------------|
| AlphaTec® 15-554                   |
| AlphaTec® Solvex® 37-185           |
| AlphaTec® 38-612                   |
| AlphaTec® 58-008                   |
| AlphaTec® 58-530B                  |
| AlphaTec® 58-530W                  |
| AlphaTec® 58-735                   |
| AlphaTec® 79-700                   |
| AlphaTec® Solvex® 37-675           |
| DermaShield™ 73-711                |

The suggested gloves for use should be confirmed with the glove supplier.

## Respiratory protection

Type -P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

| Required Minimum Protection Factor | Half-Face Respirator | Full-Face Respirator | Powered Air Respirator |
|------------------------------------|----------------------|----------------------|------------------------|
| up to 10 x ES                      | P1<br>Air-line*      | -<br>-               | PAPR-P1<br>-           |
| up to 50 x ES                      | Air-line**           | P2                   | PAPR-P2                |
| up to 100 x ES                     | -                    | P3                   | -                      |
|                                    |                      | Air-line*            | -                      |
| 100+ x ES                          | -                    | Air-line**           | PAPR-P3                |

\* - Negative pressure demand \*\* - Continuous flow

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO<sub>2</sub>), G = Agricultural chemicals, K = Ammonia(NH<sub>3</sub>), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

If inhalation risk above the TLV exists, wear approved dust respirator.

Use respirators with protection factors appropriate for the exposure level.

- ▶ Up to 5 X TLV, use valveless mask type; up to 10 X TLV, use 1/2 mask dust respirator

Continued...

## Aquapanel Joint Filler Grey

- ▶ Up to 50 X TLV, use full face dust respirator or demand type C air supplied respirator
- ▶ Up to 500 X TLV, use powered air-purifying dust respirator or a Type C pressure demand supplied-air respirator
- ▶ Over 500 X TLV wear full-face self-contained breathing apparatus with positive pressure mode or a combination respirator with a Type C positive pressure supplied-air full-face respirator and an auxiliary self-contained breathing apparatus operated in pressure demand or other positive pressure mode
- Respirators may be necessary when engineering and administrative controls do not adequately prevent exposures.
- The decision to use respiratory protection should be based on professional judgment that takes into account toxicity information, exposure measurement data, and frequency and likelihood of the worker's exposure - ensure users are not subject to high thermal loads which may result in heat stress or distress due to personal protective equipment (powered, positive flow, full face apparatus may be an option).
- Published occupational exposure limits, where they exist, will assist in determining the adequacy of the selected respiratory protection. These may be government mandated or vendor recommended.
- Certified respirators will be useful for protecting workers from inhalation of particulates when properly selected and fit tested as part of a complete respiratory protection program.
- Where protection from nuisance levels of dusts are desired, use type N95 (US) or type P1 (EN143) dust masks. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU)
- Use approved positive flow mask if significant quantities of dust becomes airborne.
- Try to avoid creating dust conditions.

Where significant concentrations of the material are likely to enter the breathing zone, a Class P3 respirator may be required.

Class P3 particulate filters are used for protection against highly toxic or highly irritant particulates.

Filtration rate: Filters at least 99.95% of airborne particles

Suitable for:

- Relatively small particles generated by mechanical processes eg. grinding, cutting, sanding, drilling, sawing.
- Sub-micron thermally generated particles e.g. welding fumes, fertilizer and bushfire smoke.
- Biologically active airborne particles under specified infection control applications e.g. viruses, bacteria, COVID-19, SARS
- Highly toxic particles e.g. Organophosphate Insecticides, Radionuclides, Asbestos

Note: P3 Rating can only be achieved when used with a Full Face Respirator or Powered Air-Purifying Respirator (PAPR). If used with any other respirator, it will only provide filtration protection up to a P2 rating.

### 8.2.3. Environmental exposure controls

See section 12

## SECTION 9 Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

|                         |  |  |                           |
|-------------------------|--|--|---------------------------|
| <b>Appearance</b>       | Grey powder with slight characteristic odour; reacts with water and releases alkali. |  |                           |
| <b>Physical state</b>   | Divided Solid  | <b>Relative density (Water = 1)</b>            | Not Available             |
| <b>Odour</b>            | Slight   | <b>Partition coefficient n-octanol / water</b> | Not Available             |
| <b>Odour threshold</b>  | Not Available  | <b>Auto-ignition temperature (°C)</b>          | Not Applicable            |
| <b>pH (as supplied)</b> | Not Applicable   | <b>Decomposition temperature (°C)</b>          | *580 (calcium hydroxide)) |

Continued...

## Aquapanel Joint Filler Grey

|   |                |  |                |
|---|----------------|--|----------------|
| <b>Melting point / freezing point (°C)</b>          | Not Available  | <b>Viscosity (cSt)</b>                   | Not Applicable |
| <b>Initial boiling point and boiling range (°C)</b> | Not Available  | <b>Molecular weight (g/mol)</b>          | Not Applicable |
| <b>Flash point (°C)</b>                             | Not Applicable | <b>Taste</b>                             | Not Available  |
| <b>Evaporation rate</b>                             | Not Available  | <b>Explosive properties</b>              | Not Available  |
| <b>Flammability</b>                                 | Not Applicable | <b>Oxidising properties</b>              | Not Available  |
| <b>Upper Explosive Limit (%)</b>                    | Not Applicable | <b>Surface Tension (dyn/cm or mN/m)</b>  | Not Applicable |
| <b>Lower Explosive Limit (%)</b>                    | Not Applicable | <b>Volatile Component (%vol)</b>         | Not Available  |
| <b>Vapour pressure (kPa)</b>                        | Not Applicable | <b>Gas group</b>                         | Not Available  |
| <b>Solubility in water</b>                          | Reacts         | <b>pH as a solution (1%)</b>             | 11-13          |
| <b>Vapour density (Air = 1)</b>                     | Not Available  | <b>VOC g/L</b>                           | Not Available  |
| <b>Nanoform Solubility</b>                          | Not Available  | <b>Nanoform Particle Characteristics</b> | Not Available  |
| <b>Particle Size</b>                                | Not Available  |  |                |

**9.2. Other information**

Not Available

**SECTION 10 Stability and reactivity**

|   |  |
|---|--|
| <b>10.1. Reactivity</b>                         | See section 7.2  |
| <b>10.2. Chemical stability</b>                 | <ul style="list-style-type: none"> <li>▶ Unstable in the presence of incompatible materials.</li> <li>▶ Product is considered stable.</li> <li>▶ Hazardous polymerisation will not occur.</li> </ul> |
| <b>10.3. Possibility of hazardous reactions</b> | See section 7.2  |
| <b>10.4. Conditions to avoid</b>                | See section 7.2  |
| <b>10.5. Incompatible materials</b>             | See section 7.2  |
| <b>10.6. Hazardous decomposition products</b>   | See section 5.3  |

**SECTION 11 Toxicological information****11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

|                     |  |
|---------------------|--|
| <b>Inhaled</b>      | <p>Evidence shows, or practical experience predicts, that the material produces irritation of the respiratory system, in a substantial number of individuals, following inhalation. In contrast to most organs, the lung is able to respond to a chemical insult by first removing or neutralising the irritant and then repairing the damage. The repair process, which initially evolved to protect mammalian lungs from foreign matter and antigens, may however, produce further lung damage resulting in the impairment of gas exchange, the primary function of the lungs. Respiratory tract irritation often results in an inflammatory response involving the recruitment and activation of many cell types, mainly derived from the vascular system.</p> <p>Inhalation of dusts, generated by the material during the course of normal handling, may be damaging to the health of the individual.</p> <p>Inhalation may result in chrome ulcers or sores of nasal mucosa and lung damage.</p> <p>Minor exposures / slow dissolution of calcium hydroxide, in body fluids in the upper respiratory tract and lungs may produce delayed severe irritation or burning sensation. Severe acute dust inhalation may produce laryngitis and pulmonary oedema. Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled.</p> <p>If prior damage to the circulatory or nervous systems has occurred or if kidney damage has been sustained, proper screenings should be conducted on individuals who may be exposed to further risk if handling and use of the material result in excessive exposures.</p> <p>Effects on lungs are significantly enhanced in the presence of respirable particles. Overexposure to respirable dust may produce wheezing, coughing and breathing difficulties leading to or symptomatic of impaired respiratory function.</p> |
| <b>Ingestion</b>    | <p>Accidental ingestion of the material may be damaging to the health of the individual.</p> <p>Not normally a hazard due to the physical form of product. The material is a physical irritant to the gastro-intestinal tract</p>  |
| <b>Skin Contact</b> | <p>Evidence exists, or practical experience predicts, that the material either produces inflammation of the skin in a substantial number of individuals following direct contact, and/or produces significant inflammation when applied to the healthy intact skin of</p>  |

Continued...

## Aquapanel Joint Filler Grey

|   |  |
|---|--|
|   | <p>animals, for up to four hours, such inflammation being present twenty-four hours or more after the end of the exposure period. Skin irritation may also be present after prolonged or repeated exposure; this may result in a form of contact dermatitis (nonallergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to blistering (vesiculation), scaling and thickening of the epidermis. At the microscopic level there may be intercellular oedema of the spongy layer of the skin (spongiosis) and intracellular oedema of the epidermis.</p> <p>The material may accentuate any pre-existing dermatitis condition</p> <p>Contact with aluminas (aluminium oxides) may produce a form of irritant dermatitis accompanied by pruritus.</p> <p>Though considered non-harmful, slight irritation may result from contact because of the abrasive nature of the aluminium oxide particles.</p> <p>Four students received severe hand burns whilst making moulds of their hands with dental plaster substituted for Plaster of Paris. The dental plaster known as "Stone" was a special form of calcium sulfate hemihydrate containing alpha-hemihydrate crystals that provide high compression strength to the moulds. Beta-hemihydrate (normal Plaster of Paris) does not cause skin burns in similar circumstances.</p> <p>Skin contact may result in severe irritation particularly to broken skin. Ulceration known as "chrome ulcers" may develop. Chrome ulcers and skin cancer are significantly related.</p> <p>Handling wet cement can cause dermatitis. Cement when wet is quite alkaline and this alkali action on the skin contributes strongly to cement contact dermatitis since it may cause drying and defatting of the skin which is followed by hardening, cracking, lesions developing, possible infections of lesions and penetration by soluble salts.</p> <p>In the presence of moisture calcium hydroxide (slaked lime) is a caustic irritant and can be damaging to human tissue. Skin contact may result in severe burns and blistering, depending on duration of contact.</p> <p>Open cuts, abraded or irritated skin should not be exposed to this material</p> <p>Entry into the blood-stream through, for example, cuts, abrasions, puncture wounds or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.</p>   |
| <p style="text-align: center;"><b>Eye</b></p>     | <p>When applied to the eye(s) of animals, the material produces severe ocular lesions which are present twenty-four hours or more after instillation.</p> <p>Eye contact with calcium hydroxide may result in severe irritation and pain. The material may induce ulcerations of the corneal epithelium</p>  |
| <p style="text-align: center;"><b>Chronic</b></p> | <p>Long-term exposure to respiratory irritants may result in disease of the airways involving difficult breathing and related systemic problems.</p> <p>Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems.</p> <p>Chronic exposure to aluminas (aluminium oxides) of particle size 1.2 microns did not produce significant systemic or respiratory system effects in workers. Epidemiologic surveys have indicated an excess of nonmalignant respiratory disease in workers exposed to aluminum oxide during abrasives production.</p> <p>Very fine Al<sub>2</sub>O<sub>3</sub> powder was not fibrogenic in rats, guinea pigs, or hamsters when inhaled for 6 to 12 months and sacrificed at periods up to 12 months following the last exposure.</p> <p>When hydrated aluminas were injected intratracheally, they produced dense and numerous nodules of advanced fibrosis in rats, a reticulin network with occasional collagen fibres in mice and guinea pigs, and only a slight reticulin network in rabbits. Shaver's disease, a rapidly progressive and often fatal interstitial fibrosis of the lungs, is associated with a process involving the fusion of bauxite (aluminium oxide) with iron, coke and silica at 2000 deg. C.</p> <p>The weight of evidence suggests that catalytically active alumina and the large surface area aluminas can induce lung fibrosis(aluminosis) in experimental animals, but only when given by the intra-tracheal route. The pertinence of such experiments in relation to workplace exposure is doubtful especially since it has been demonstrated that the most reactive of the aluminas (i.e. the chi and gamma forms), when given by inhalation, are non-fibrogenic in experimental animals. However rats exposed by inhalation to refractory aluminium fibre showed mild fibrosis and possibly carcinogenic effects indicating that fibrous aluminas might exhibit different toxicology to non-fibrous forms. Aluminium oxide fibres administered by the intrapleural route produce clear evidence of carcinogenicity.</p> <p>Saffil fibre an artificially produced form alumina fibre used as refractories, consists of over 95% alumina, 3-4 % silica. Animal tests for fibrogenic, carcinogenic potential and oral toxicity have included in-vitro, intraperitoneal injection, intrapleural injection, inhalation, and feeding. The fibre has generally been inactive in animal studies. Also studies of Saffil dust clouds show very low respirable fraction.</p> <p>There is general agreement that particle size determines that the degree of pathogenicity (the ability of a micro-organism to produce infectious disease) of elementary aluminium, or its oxides or hydroxides when they occur as dusts, fumes or vapours. Only those particles small enough to enter the alveoli (sub 5 um) are able to produce pathogenic effects in the lungs.</p> <p>Red blood cells and rabbit alveolar macrophages exposed to calcium silicate insulation materials in vitro showed haemolysis in one study but not in another. Both studies showed the substance to be more cytotoxic than titanium dioxide but less toxic than asbestos.</p> <p>In a small cohort mortality study of workers in a wollastonite quarry, the observed number of deaths from all cancers combined and lung cancer were lower than expected. Wollastonite is a calcium inosilicate mineral (CaSiO<sub>3</sub>). In some cases, small amounts of iron (Fe), and manganese (Mn), and lesser amounts of magnesium (Mg) substitute for calcium (Ca) in the mineral formulae (e.g., rhodonite)</p> <p>In an inhalation study in rats no increase in tumour incidence was observed but the number of fibres with lengths exceeding 5 um and a diameter of less than 3 um was relatively low. Four grades of wollastonite of different fibre size were tested for carcinogenicity in one experiment in rats by intrapleural implantation. There was no information on the purity of the four samples used. A slight increase in the incidence of pleural sarcomas was observed with three grades, all of which contained fibres greater than 4 um in length and less than 0.5 um in diameter.</p> <p>In two studies by intraperitoneal injection in rats using wollastonite with median fibre lengths of 8.1 um and 5.6 um respectively, no intra-abdominal tumours were found.</p> <p>Evidence from wollastonite miners suggests that occupational exposure can cause impaired respiratory function and pneumoconiosis. However animal studies have demonstrated that wollastonite fibres have low biopersistence and induce a</p> |

Continued...

## Aquapanel Joint Filler Grey

transient inflammatory response compared to various forms of asbestos. A two-year inhalation study in rats at one dose showed no significant inflammation or fibrosis

Cement contact dermatitis (CCD) may occur when contact shows an allergic response, which may progress to sensitisation. Sensitisation is due to soluble chromates (chromate compounds) present in trace amounts in some cements and cement products. Soluble chromates readily penetrate intact skin. Cement dermatitis can be characterised by fissures, eczematous rash, dystrophic nails, and dry skin; acute contact with highly alkaline mixtures may cause localised necrosis.

Cement eczema may be due to chromium in feed stocks or contamination from materials of construction used in processing the cement. Sensitisation to chromium may be the leading cause of nickel and cobalt sensitivity and the high alkalinity of cement is an important factor in cement dermatoses [ILO].

Repeated, prolonged severe inhalation exposure may cause pulmonary oedema and rarely, pulmonary fibrosis. Workers may also suffer from dust-induced bronchitis with chronic bronchitis reported in 17% of a group occupationally exposed to high dust levels.

Respiratory symptoms and ventilatory function were studied in a group of 591 male Portland cement workers employed in four Taiwanese cement plants, with at least 5 years of exposure (1). This group had a significantly lowered mean forced vital capacity (FCV), forced expiratory volume at 1 s (FEV1) and forced expiratory flows after exhalation of 50% and 75% of the vital capacity (FEF50, FEF75). The data suggests that occupational exposure to Portland cement dust may lead to a higher incidence of chronic respiratory symptoms and a reduction of ventilatory capacity.

Chun-Yuh et al; Journal of Toxicology and Environmental Health 49: 581-588, 1996

Chronic symptoms produced by crystalline silicas included decreased vital lung capacity and chest infections. Lengthy exposure may cause silicosis a disabling form of pneumoconiosis which may lead to fibrosis, a scarring of the lining of the air sacs in the lung.

The form and severity in which silicosis manifests itself depends in part on the type and extent of exposure to silica dusts: chronic, accelerated and acute forms are all recognized. In later stages the critical condition may become disabling and potentially fatal. Restrictive and/or obstructive lung function changes may result from chronic exposure. A risk associated with silicosis is development of pulmonary tuberculosis (silico-tuberculosis). Respiratory insufficiencies due to massive fibrosis and reduced pulmonary function, possibly with accompanying heart failure, are other potential causes of death due to silicosis. Not all individuals with silicosis will exhibit symptoms (signs) of the disease. However, silicosis can be progressive, and symptoms may potentially appear years after exposures have ceased. Symptoms of silicosis may include (but are not limited to): Shortness of breath; difficulty breathing with or without exertion; coughing; diminished work capacity; diminished chest expansion; reduction of lung volume; heart enlargement and/or failure.

Respirable dust containing newly broken particles has been shown to be more hazardous to animals in laboratory tests than respirable dust containing older silica particles of similar size. Respirable silica particles which had aged for sixty days or more showed less lung injury in animals than equal exposures of respirable dust containing newly broken pieces of silica. There are reports in the literature indicating that crystalline silica exposure may be associated with adverse health effects involving the kidney, scleroderma (thickening of the skin caused by swelling and thickening of fibrous tissue) and other autoimmune and immunity-related disorders. Several studies of persons with silicosis or silica exposure also indicate or suggest increased risk of developing lung cancer, a risk that may increase with the duration of exposure. Many of these studies of silicosis do not account for lung cancer confounders, especially smoking.

Symptoms may appear 8 to 18 months after initial exposure. Smoking increases this risk. Classic silicosis is a chronic disease characterised by the formation of scattered, rounded or stellate silica-containing nodules of scar tissue in the lungs ranging from microscopic to 1.0 cm or more. The nodules isolate the inhaled silica particles and protect the surrounding normal and functioning tissue from continuing injury. Simple silicosis (in which the nodules are less than 1.0 cm in diameter) is generally asymptomatic but may be slowly progressive even in the absence of continuing exposure. Simple silicosis can develop in complicated silicoses (in which nodules are greater than 1.0 cm in diameter) and can produce disabilities including an associated tuberculous infection (which 50 years ago accounted for 75% of the deaths among silicotic workers). Crystalline silica deposited in the lungs causes epithelial and macrophage injury and activation. Crystalline silica translocates to the interstitium and the regional lymph nodes and cause the recruitment of inflammatory cells in a dose dependent manner. In humans, a large fraction of crystalline silica persists in the lungs. The question of potential carcinogenicity associated with chronic inhalation of crystalline silica remains equivocal with some studies supporting the proposition and others finding no significant association. The results of recent epidemiological studies suggest that lung cancer risk is elevated only in those patients with overt silicosis. A relatively large number of epidemiological studies have been undertaken and in some, increased risk gradients have been observed in relation to dose surrogates - cumulative exposure, duration of exposure, the presence of radiographically defined silicosis, and peak intensity exposure. Chronic inhalation in rats by single or repeated intratracheal instillation produced a significant increase in the incidences of adenocarcinomas and squamous cell carcinomas of the lung. Lifetime inhalation of crystalline silica (87% alpha-quartz) at 1 mg/m<sup>3</sup> (74% respirable) by rats, produced an increase in animals with keratinising cystic squamous cell tumours, adenomas, adenocarcinomas, adenosquamous cell carcinomas, squamous cell carcinoma and nodular bronchiolar alveolar hyperplasia accompanied by extensive subpleural and peribronchiolar fibrosis, increased pulmonary collagen content, focal lipoproteinosis and macrophage infiltration. Thoracic and abdominal malignant lymphomas developed in rats after single intrapleural and intraperitoneal injection of suspensions of several types of quartz.

Some studies show excess numbers of cases of scleroderma, connective tissue disorders, lupus, rheumatoid arthritis chronic kidney diseases, and end-stage kidney disease in workers

**NOTE:** Some jurisdictions require health surveillance be conducted on workers occupationally exposed to silica, crystalline. Such surveillance should emphasise

- demography, occupational and medical history and health advice
- standardised respiratory function tests such as FEV1, FVC and FEV1/FVC
- standardised respiratory function tests such as FV1, FVC and FEV1/FVC
- chest X-ray, full size PA view
- records of personal exposure

Chronic exposure to calcium hydroxide may result in narrowing of the esophagus, with difficulty in swallowing. This may happen after weeks, months or years of exposure.

Overexposure to the breathable dust may cause coughing, wheezing, difficulty in breathing and impaired lung function. Chronic symptoms may include decreased vital lung capacity and chest infections. Repeated exposures in the workplace to high levels of

## Aquapanel Joint Filler Grey

fine-divided dusts may produce a condition known as pneumoconiosis, which is the lodgement of any inhaled dusts in the lung, irrespective of the effect. This is particularly true when a significant number of particles less than 0.5 microns (1/50000 inch) are present. Lung shadows are seen in the X-ray. Symptoms of pneumoconiosis may include a progressive dry cough, shortness of breath on exertion, increased chest expansion, weakness and weight loss. As the disease progresses, the cough produces stringy phlegm, vital capacity decreases further, and shortness of breath becomes more severe. Other signs or symptoms include changed breath sounds, reduced oxygen uptake during exercise, emphysema and rarely, pneumothorax (air in the lung cavity).

Removing workers from the possibility of further exposure to dust generally stops the progress of lung abnormalities. When there is high potential for worker exposure, examinations at regular period with emphasis on lung function should be performed. Inhaling dust over an extended number of years may cause pneumoconiosis, which is the accumulation of dusts in the lungs and the subsequent tissue reaction. This may or may not be reversible.

Chronic excessive iron exposure has been associated with haemosiderosis and consequent possible damage to the liver and pancreas. Haemosiderin is a golden-brown insoluble protein produced by phagocytic digestion of haematin (an iron-based pigment). Haemosiderin is found in most tissues, especially in the liver, in the form of granules. Other sites of haemosiderin deposition include the pancreas and skin. A related condition, haemochromatosis, which involves a disorder of metabolism of these deposits, may produce cirrhosis of the liver, diabetes, and bronze pigmentation of the skin - heart failure may eventually occur.

Such exposure may also produce conjunctivitis, choroiditis, retinitis (both inflammatory conditions involving the eye) and siderosis of tissues if iron remains in these tissues. Siderosis is a form of pneumoconiosis produced by iron dusts. Siderosis also includes discoloration of organs, excess circulating iron and degeneration of the retina, lens and uvea as a result of the deposition of intraocular iron. Siderosis might also involve the lungs - involvement rarely develops before ten years of regular exposure. Often there is an accompanying inflammatory reaction of the bronchi. Permanent scarring of the lungs does not normally occur.

High levels of iron may raise the risk of cancer. This concern stems from the theory that iron causes oxidative damage to tissues and organs by generating highly reactive chemicals, called free radicals, which subsequently react with DNA. Cells may be disrupted and may become cancerous. People whose genetic disposition prevents them from keeping tight control over iron (e.g. those with the inherited disorder, haemochromatosis) may be at increased risk.

Iron overload in men may lead to diabetes, arthritis, liver cancer, heart irregularities and problems with other organs as iron builds up.

[K. Schmidt, New Scientist, No. 1919 pp.11-12, 2nd April, 1994]

Prolonged or repeated skin contact may cause drying with cracking, irritation and possible dermatitis following.

|                             |  |   |
|-----------------------------|--|---|
| Aquapanel Joint Filler Grey | <b>TOXICITY</b>                                    | <b>IRRITATION</b>   |
|                             | Not Available                                      | Not Available   |
| silica crystalline - quartz | <b>TOXICITY</b>                                    | <b>IRRITATION</b>   |
|                             | Oral (Rat) LD50: 500 mg/kg <sup>[2]</sup>          | Not Available   |
| portland cement             | <b>TOXICITY</b>                                    | <b>IRRITATION</b>   |
|                             | Not Available                                      | Not Available   |
| calcium hydroxide           | <b>TOXICITY</b>                                    | <b>IRRITATION</b>   |
|                             | dermal (rat) LD50: >2000 mg/kg <sup>[1]</sup>      | Eye (rabbit): 10 mg - SEVERE                              |
|                             | Inhalation (Rat) LC50: >3 mg/l4h <sup>[1]</sup>    | Eye: adverse effect observed (irritating) <sup>[1]</sup>  |
| portland cement, flue dust  | <b>TOXICITY</b>                                    | <b>IRRITATION</b>   |
|                             | dermal (rat) LD50: >=2000 mg/kg <sup>[1]</sup>     | Eye: adverse effect observed (irritating) <sup>[1]</sup>  |
|                             | Inhalation (Rat) LC50: >6.04 mg/l4h <sup>[1]</sup> | Skin: adverse effect observed (irritating) <sup>[1]</sup> |
| portland cement, flue dust  | <b>TOXICITY</b>                                    | <b>IRRITATION</b>   |
|                             | Oral (Rat) LD50: >1848 mg/kg <sup>[1]</sup>        |   |

**Legend:**

1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

**SILICA CRYSTALLINE - QUARTZ**

**WARNING:** For inhalation exposure ONLY: This substance has been classified by the IARC as Group 1: **CARCINOGENIC TO HUMANS**

The International Agency for Research on Cancer (IARC) has classified occupational exposures to **respirable** (<5 um) crystalline silica as being carcinogenic to humans. This classification is based on what IARC considered sufficient evidence from epidemiological studies of humans for the carcinogenicity of inhaled silica in the forms of quartz and cristobalite. Crystalline silica is also known to cause silicosis, a non-cancerous lung disease.

Intermittent exposure produces; focal fibrosis, (pneumoconiosis), cough, dyspnoea, liver tumours.

## Aquapanel Joint Filler Grey

|   |   |
|---|---|
|   | * Millions of particles per cubic foot (based on impinger samples counted by light field techniques).<br>NOTE : the physical nature of quartz in the product determines whether it is likely to present a chronic health problem. To be a hazard the material must enter the breathing zone as respirable particles.  |
| <b>CALCIUM HYDROXIDE</b>  | The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.  |
| <b>PORTLAND CEMENT &amp; PORTLAND CEMENT, FLUE DUST</b>                         | The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested.<br>No significant acute toxicological data identified in literature search.  |
| <b>PORTLAND CEMENT &amp; CALCIUM HYDROXIDE &amp; PORTLAND CEMENT, FLUE DUST</b> | Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. On the other hand, industrial bronchitis is a disorder that occurs as a result of exposure due to high concentrations of irritating substance (often particles) and is completely reversible after exposure ceases. The disorder is characterized by difficulty breathing, cough and mucus production. |

|  |   |                                 |   |
|--|---|---------------------------------|---|
| <b>Acute Toxicity</b>                    | ✗ | <b>Carcinogenicity</b>          | ✗ |
| <b>Skin Irritation/Corrosion</b>         | ✓ | <b>Reproductivity</b>           | ✗ |
| <b>Serious Eye Damage/Irritation</b>     | ✓ | <b>STOT - Single Exposure</b>   | ✓ |
| <b>Respiratory or Skin sensitisation</b> | ✗ | <b>STOT - Repeated Exposure</b> | ✗ |
| <b>Mutagenicity</b>                      | ✗ | <b>Aspiration Hazard</b>        | ✗ |

**Legend:** ✗ – Data either not available or does not fill the criteria for classification  
✓ – Data available to make classification

## 11.2 Information on other hazards

### 11.2.1. Endocrine disrupting properties

No evidence of endocrine disrupting properties were found in the current literature.

### 11.2.2. Other information

See Section 11.1

## SECTION 12 Ecological information

### 12.1. Toxicity

| Aquapanel Joint Filler Grey | Endpoint      | Test Duration (hr) | Species       | Value         | Source        |
|-----------------------------|---------------|--------------------|---------------|---------------|---------------|
|                             | Not Available | Not Available      | Not Available | Not Available | Not Available |
| silica crystalline - quartz | Endpoint      | Test Duration (hr) | Species       | Value         | Source        |
|                             | Not Available | Not Available      | Not Available | Not Available | Not Available |
| portland cement             | Endpoint      | Test Duration (hr) | Species       | Value         | Source        |
|                             | Not Available | Not Available      | Not Available | Not Available | Not Available |
| calcium hydroxide           | Endpoint      | Test Duration (hr) | Species       | Value         | Source        |
|                             | LC50          | 96h                | Fish          | 33.884mg/L    | 4             |

Continued...

## Aquapanel Joint Filler Grey

|                            |  |                           |                               |              |               |
|----------------------------|--|---------------------------|-------------------------------|--------------|---------------|
|                            | EC50   | 72h                       | Algae or other aquatic plants | >14mg/l      | 2             |
|                            | EC50   | 48h                       | Crustacea                     | 49.1mg/l     | 2             |
|                            | NOEC(ECx)  | 72h                       | Algae or other aquatic plants | 14mg/l       | 2             |
| portland cement, flue dust | <b>Endpoint</b>  | <b>Test Duration (hr)</b> | <b>Species</b>                | <b>Value</b> | <b>Source</b> |
|                            | NOEC(ECx)  | 96h                       | Fish                          | 11.1mg/l     | 2             |
|                            | EC50   | 72h                       | Algae or other aquatic plants | 22.4mg/l     | 2             |
| <b>Legend:</b>             | Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data |                           |                               |              |               |

**DO NOT** discharge into sewer or waterways.

## 12.2. Persistence and degradability

| Ingredient | Persistence: Water/Soil               | Persistence: Air                      |
|------------|---------------------------------------|---------------------------------------|
|            | No Data available for all ingredients | No Data available for all ingredients |

## 12.3. Bioaccumulative potential

| Ingredient | Bioaccumulation                       |
|------------|---------------------------------------|
|            | No Data available for all ingredients |

## 12.4. Mobility in soil

| Ingredient | Mobility                              |
|------------|---------------------------------------|
|            | No Data available for all ingredients |

## 12.5. Results of PBT and vPvB assessment

|                         | P             | B             | T             |
|-------------------------|---------------|---------------|---------------|
| Relevant available data | Not Available | Not Available | Not Available |
| PBT                     | ✘             | ✘             | ✘             |
| vPvB                    | ✘             | ✘             | ✘             |
| PBT Criteria fulfilled? | No            |               |               |
| vPvB                    | No            |               |               |

## 12.6. Endocrine disrupting properties

No evidence of endocrine disrupting properties were found in the current literature.

## 12.7. Other adverse effects

No evidence of ozone depleting properties were found in the current literature.

## SECTION 13 Disposal considerations

### 13.1. Waste treatment methods

|                                     |  |
|-------------------------------------|--|
| <b>Product / Packaging disposal</b> | <ul style="list-style-type: none"> <li>▶ <b>DO NOT</b> allow wash water from cleaning or process equipment to enter drains.</li> <li>▶ It may be necessary to collect all wash water for treatment before disposal.</li> <li>▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.</li> <li>▶ Where in doubt contact the responsible authority.</li> <li>▶ Recycle wherever possible or consult manufacturer for recycling options.</li> <li>▶ Consult State Land Waste Management Authority for disposal.</li> <li>▶ Bury residue in an authorised landfill.</li> <li>▶ Recycle containers if possible, or dispose of in an authorised landfill.</li> </ul> |
| <b>Waste treatment options</b>      | Not Available  |
| <b>Sewage disposal options</b>      | Not Available  |

## SECTION 14 Transport information

## Aquapanel Joint Filler Grey

## Labels Required

|                  |    |
|------------------|----|
| Marine Pollutant | NO |
|------------------|----|

## Land transport (ADR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

|                                    |                                |                |
|------------------------------------|--------------------------------|----------------|
| 14.1. UN number or ID number       | Not Applicable                 |                |
| 14.2. UN proper shipping name      | Not Applicable                 |                |
| 14.3. Transport hazard class(es)   | Class                          | Not Applicable |
|                                    | Subsidiary Hazard              | Not Applicable |
| 14.4. Packing group                | Not Applicable                 |                |
| 14.5. Environmental hazard         | Not Applicable                 |                |
| 14.6. Special precautions for user | Hazard identification (Kemler) | Not Applicable |
|                                    | Classification code            | Not Applicable |
|                                    | Hazard Label                   | Not Applicable |
|                                    | Special provisions             | Not Applicable |
|                                    | Limited quantity               | Not Applicable |
|                                    | Tunnel Restriction Code        | Not Applicable |

## Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

|                                    |   |                |
|------------------------------------|---|----------------|
| 14.1. UN number                    | Not Applicable  |                |
| 14.2. UN proper shipping name      | Not Applicable  |                |
| 14.3. Transport hazard class(es)   | ICAO/IATA Class   | Not Applicable |
|                                    | ICAO / IATA Subsidiary Hazard                             | Not Applicable |
|                                    | ERG Code  | Not Applicable |
| 14.4. Packing group                | Not Applicable  |                |
| 14.5. Environmental hazard         | Not Applicable  |                |
| 14.6. Special precautions for user | Special provisions  | Not Applicable |
|                                    | Cargo Only Packing Instructions                           | Not Applicable |
|                                    | Cargo Only Maximum Qty / Pack                             | Not Applicable |
|                                    | Passenger and Cargo Packing Instructions                  | Not Applicable |
|                                    | Passenger and Cargo Maximum Qty / Pack                    | Not Applicable |
|                                    | Passenger and Cargo Limited Quantity Packing Instructions | Not Applicable |
|                                    | Passenger and Cargo Limited Maximum Qty / Pack            | Not Applicable |

## Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

|                                    |                        |                |
|------------------------------------|------------------------|----------------|
| 14.1. UN number                    | Not Applicable         |                |
| 14.2. UN proper shipping name      | Not Applicable         |                |
| 14.3. Transport hazard class(es)   | IMDG Class             | Not Applicable |
|                                    | IMDG Subsidiary Hazard | Not Applicable |
| 14.4. Packing group                | Not Applicable         |                |
| 14.5. Environmental hazard         | Not Applicable         |                |
| 14.6. Special precautions for user | EMS Number             | Not Applicable |

## Aquapanel Joint Filler Grey

|                    |                |
|--------------------|----------------|
| Special provisions | Not Applicable |
| Limited Quantities | Not Applicable |

**Inland waterways transport (ADN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS**

|                                    |                     |                |
|------------------------------------|---------------------|----------------|
| 14.1. UN number                    | Not Applicable      |                |
| 14.2. UN proper shipping name      | Not Applicable      |                |
| 14.3. Transport hazard class(es)   | Not Applicable      | Not Applicable |
| 14.4. Packing group                | Not Applicable      |                |
| 14.5. Environmental hazard         | Not Applicable      |                |
| 14.6. Special precautions for user | Classification code | Not Applicable |
|                                    | Special provisions  | Not Applicable |
|                                    | Limited quantity    | Not Applicable |
|                                    | Equipment required  | Not Applicable |
|                                    | Fire cones number   | Not Applicable |

**14.7. Maritime transport in bulk according to IMO instruments****14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code**

Not Applicable

**14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code**

| Product name                | Group         |
|-----------------------------|---------------|
| silica crystalline - quartz | Not Available |
| portland cement             | Not Available |
| calcium hydroxide           | Not Available |
| portland cement, flue dust  | Not Available |

**14.7.3. Transport in bulk in accordance with the IGC Code**

| Product name                | Ship Type     |
|-----------------------------|---------------|
| silica crystalline - quartz | Not Available |
| portland cement             | Not Available |
| calcium hydroxide           | Not Available |
| portland cement, flue dust  | Not Available |

**SECTION 15 Regulatory information****15.1. Safety, health and environmental regulations / legislation specific for the substance or mixture****silica crystalline - quartz is found on the following regulatory lists**

Chemical Footprint Project - Chemicals of High Concern List

Europe EC Inventory

European Union - European Inventory of Existing Commercial Chemical Substances (EINECS)

European Union Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens or mutagens at work

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 1: Carcinogenic to humans

Ireland Occupational Exposure Limits

**portland cement is found on the following regulatory lists**

Europe EC Inventory

European Union - European Inventory of Existing Commercial Chemical Substances (EINECS)

Continued...

## Aquapanel Joint Filler Grey

**calcium hydroxide is found on the following regulatory lists**

EU Consolidated List of Indicative Occupational Exposure Limit Values (IOELVs)

Europe EC Inventory

European Union - European Inventory of Existing Commercial Chemical Substances (EINECS)

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

Ireland Occupational Exposure Limits

**portland cement, flue dust is found on the following regulatory lists**

Europe EC Inventory

European Union - European Inventory of Existing Commercial Chemical Substances (EINECS)

**Additional Regulatory Information**

Not Applicable

This safety data sheet is in compliance with the following EU legislation and its adaptations - as far as applicable - : Directives 98/24/EC, - 92/85/EEC, - 94/33/EC, - 2008/98/EC, - 2010/75/EU; Commission Regulation (EU) 2020/878; Regulation (EC) No 1272/2008 as updated through ATPs.

**Information according to 2012/18/EU (Seveso III):**

| Seveso Category | Not Available |
|-----------------|---------------|
|                 |               |

**15.2. Chemical safety assessment**

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

**National Inventory Status**

| National Inventory                               | Status  |
|--|---|
| Australia - AIIIC / Australia Non-Industrial Use | No (portland cement, flue dust)   |
| Canada - DSL                                     | Yes   |
| Canada - NDSL                                    | No (silica crystalline - quartz; portland cement; calcium hydroxide; portland cement, flue dust)  |
| China - IECSC                                    | No (portland cement, flue dust)   |
| Europe - EINEC / ELINCS / NLP                    | Yes   |
| Japan - ENCS                                     | No (portland cement; portland cement, flue dust)  |
| Korea - KECI                                     | Yes   |
| New Zealand - NZIoC                              | Yes   |
| Philippines - PICCS                              | No (portland cement; portland cement, flue dust)  |
| USA - TSCA                                       | Yes   |
| Taiwan - TCSI                                    | No (portland cement, flue dust)   |
| Mexico - INSQ                                    | No (portland cement, flue dust)   |
| Vietnam - NCI                                    | Yes   |
| Russia - FBEPH                                   | No (portland cement, flue dust)   |
| <b>Legend:</b>                                   | Yes = All CAS declared ingredients are on the inventory<br>No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration. |

**SECTION 16 Other information**

|               |            |
|---------------|------------|
| Revision Date | 01/02/2024 |
| Initial Date  | 29/11/2023 |

**Full text Risk and Hazard codes**

|       |  |
|-------|--|
| H290  | May be corrosive to metals.              |
| H314  | Causes severe skin burns and eye damage. |
| H317  | May cause an allergic skin reaction.     |
| H341  | Suspected of causing genetic defects.    |
| H350i | May cause cancer by inhalation.          |

Continued...

## Aquapanel Joint Filler Grey

|             |  |
|-------------|--|
| <b>H373</b> | May cause damage to organs through prolonged or repeated exposure. |
| <b>H410</b> | Very toxic to aquatic life with long lasting effects.              |

### SDS Version Summary

| Version | Date of Update | Sections Updated  |
|---------|----------------|---|
| 3.1     | 01/02/2024     | Toxicological information - Acute Health (swallowed), First Aid measures - Advice to Doctor, Physical and chemical properties - Appearance, Toxicological information - Chronic Health, Hazards identification - Classification, Composition / information on ingredients - Ingredients, Handling and storage - Storage (storage incompatibility) |

### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

For detailed advice on Personal Protective Equipment, refer to the following EU CEN Standards:

EN 166 Personal eye-protection

EN 340 Protective clothing

EN 374 Protective gloves against chemicals and micro-organisms

EN 13832 Footwear protecting against chemicals

EN 133 Respiratory protective devices

### Definitions and abbreviations

- PC - TWA: Permissible Concentration-Time Weighted Average
- PC - STEL: Permissible Concentration-Short Term Exposure Limit
- IARC: International Agency for Research on Cancer
- ACGIH: American Conference of Governmental Industrial Hygienists
- STEL: Short Term Exposure Limit
- TEEL: Temporary Emergency Exposure Limit,
- IDLH: Immediately Dangerous to Life or Health Concentrations
- ES: Exposure Standard
- OSF: Odour Safety Factor
- NOAEL: No Observed Adverse Effect Level
- LOAEL: Lowest Observed Adverse Effect Level
- TLV: Threshold Limit Value
- LOD: Limit Of Detection
- OTV: Odour Threshold Value
- BCF: BioConcentration Factors
- BEI: Biological Exposure Index
- DNEL: Derived No-Effect Level
- PNEC: Predicted no-effect concentration
  
- AIIC: Australian Inventory of Industrial Chemicals
- DSL: Domestic Substances List
- NDSL: Non-Domestic Substances List
- IECSC: Inventory of Existing Chemical Substance in China
- EINECS: European INventory of Existing Commercial chemical Substances
- ELINCS: European List of Notified Chemical Substances
- NLP: No-Longer Polymers
- ENCS: Existing and New Chemical Substances Inventory
- KECI: Korea Existing Chemicals Inventory
- NZIoC: New Zealand Inventory of Chemicals
- PICCS: Philippine Inventory of Chemicals and Chemical Substances
- TSCA: Toxic Substances Control Act
- TCSI: Taiwan Chemical Substance Inventory
- INSQ: Inventario Nacional de Sustancias Químicas
- NCI: National Chemical Inventory
- FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

### Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]

## Aquapanel Joint Filler Grey

| Classification according to regulation (EC) No 1272/2008 [CLP] and amendments                              | Classification Procedure |
|--|--------------------------|
| Skin Corrosion/Irritation<br>Category 2, H315  | Calculation method       |
| Serious Eye Damage/Eye<br>Irritation Category 1, H318  | Calculation method       |
| Specific Target Organ<br>Toxicity - Single Exposure<br>(Respiratory Tract Irritation)<br>Category 3 , H335 | Calculation method       |