



KNAUF SHEETROCK® PREMIUM PREMIX

Knauf Sheetrock® Premium Premix is a ready-mixed, lightweight compound suitable for all three coat applications or as a finishing coat for all plasterboard joints, angles, and fastener heads. Complies with ASTM C475 (where applicable).



1st Coat



2nd Coat



Finishing
Coat



Sandable



Patching



Skimming



Product Features

- Minimal shrinkage
- Easy sanding
- Exceptional crack resistance
- Excellent bond
- Smooth finish

Recommended

- Knauf Sheetrock® Premium Premix is suitable for use as all three coats in the Knauf 3 coat jointing system.
- Knauf Sheetrock® Premium Premix is suitable for the final coating of plasterboard joints, angles, and fastener heads when used in conjunction with Knauf setting type joint compounds for first and second coats.

Applications

- Surface must be clean and free from dust.
- Knauf Sheetrock® Premium Premix may have high viscosity in the pail. It may be diluted to a workable viscosity by adding water followed by mechanical mixing.
- Can be applied by hand or mechanical tools.
- When using Knauf Sheetrock® Premium Premix for all three coats, the first coat must be used to bed a high-quality paper tape such as Knauf Paper Joint Tape.

Directions - Jointing and Finishing

First Coat 150mm/300mm Wide

(Tapered Edge Joint/Square Edge Joint)

1. Cover joint with a thin layer of compound and embed paper tape, leaving at least 1mm of compound under feathered edge and allow to dry.

Second Coat 200mm/400mm Wide

(Tapered Edge Joint/Square Edge Joint)

2. Apply second coat, feathering approximately 50mm (tapered edge joint) or 100mm (square edge joint) beyond first coat. Allow to dry.

Third Coat 250mm/500mm Wide

(Tapered Edge Joint/Square Edge Joint)

3. Apply third coat, feathering 50mm (tapered edge joint) or 100mm (square edge joint) beyond second coat. Allow to dry and sand lightly. Finish fastener heads, corner beads, and inside corners as required with at least three coats of joint compound, feathered onto panel faces and finished to a smooth surface.
4. Knauf Sheetrock® Premium Premix Joint Compound must be allowed to dry thoroughly (up to 24 hours depending on temperature and humidity) before re-coating or sanding.
5. Only apply over setting type compounds that have been allowed to dry thoroughly.
6. Sand with care using 180 to 220 grit sandpaper.
7. Thoroughly clean all tools and equipment after use.

NOTE: All surfaces including applied joint compound require light sanding before painting.

Mixing

- Always use clean tools.
- Do not mix with residues of previously used compounds.
- The inclusion of such materials will impair the performance of this product and will void the product warranty.
- Knauf Sheetrock® Premium Premix Joint Compound may appear thick in pail. Before adding water, lightly mix and test its application. If required, add water to achieve desired consistency.
- **Caution:** Avoid overthinning when adding water as this may cause cracking and excessive shrinkage.
- If liquid has separated from the compound, stir carefully to restore consistency.
- **Caution:** Do not overmix; overmixing can introduce air bubbles, which can create surface imperfections.

Storage

- Knauf Sheetrock® Premium Premix should be stored under a cover in a dry environment and protected from temperature extremes. Storage in an unsuitable environment can shorten the lifespan of the product.
- Knauf Sheetrock® Premium Premix has a shelf life of 9 months from the date of manufacture.

Product Information

Colour	White
Drying Time	12 - 24 hours (depending on local conditions)
Packaging	Net 5.4kg and 28kg re-sealable pail
VOC	Meet ISO 11890-2 (<25g/L)
Jointing Coverage	47.6m ² (1kg covers 1.7m ²)
Skimming Coverage	Approximately 33m ² /28kg pail at 1mm thickness and skimming viscosity

Limitations

- The application of Knauf Sheetrock® Premium Premix at interior temperatures less than 10°C is not recommended. Under cold or wet weather conditions, allow more than 24 hours for thorough drying.
- When diluting Knauf Sheetrock® Premium Premix, do not vigorously overmix as this will introduce entrapped air which can result in surface imperfections.
- Do not apply Knauf Sheetrock® Premium Premix over joints that are not thoroughly dry; pinholes may result.
- Do not use sandpaper lower than 150 grit. Take care to avoid scratching when sanding.
- The inclusion of other materials to a mix will impair the performance (e.g. reduced strength and poor adhesion) and void the product warranty.
- Consume an opened bucket within 48 hours.

Precautionary Statement

- Dust from this product may contain silica. Prolonged inhalation may be harmful to health.
- Ensure adequate ventilation. Wear eye protection and an approved disposable respirator.
- If dust or paste causes irritation, use impervious PVC, nitrile or rubber gloves. Wash exposed skin after handling. If product gets into the eyes, wash thoroughly with clean water.
- Do not ingest contents of package. If ingested, seek medical advice immediately.
- Keep contents out of reach of children.
- Be conscious of the environment. Dispose of empty packaging in a responsible manner.
- Follow safe lifting instructions on the product label.



Knauf Singapore Pte. Ltd.

79 Anson Road #07-01 Singapore 079906

T: (65) 6272 9272 E: contact-us.sg@knauf.com W: www.knauf.com

© 2024 KNAUF. All rights reserved. KNAUF and PREMIUM PREMIX are trademarks of Knauf Singapore Pte. Ltd. or one or more of its affiliates. SHEETROCK is a trademark owned by United States Gypsum Company and used under license. Information provided is for reference purpose only. Due care has been taken to ensure accuracy at time of publication. Products, specifications, and requirements may vary according to geographical locations and applications. As each project is unique, please contact your nearest Knauf representative for further assessment.

Scan to visit
our website



SG_IF02_WL_SS_0524_V2 P_SG_IF02_0524_01