

Knauf Regular Gypsum Board



Knauf Regular Gypsum Board is designed for general applications for wall lining, ceiling and drywall.



Properties

- Lightweight constructions
- Easy, fast and dry application
- Flat and smooth paper surface to receive direct decoration or gypsum plaster
- A material that breathes and balances room climate and humidity levels
- Environment friendly
- Limitless design options

Where to use

- Light weighted partition wall
- Suspended Ceiling
- Wall lining

Application

Knauf regular plasterboard is designed for general use.

- For high humidity area, please choose Knauf Moistureshield.
- For fire protection, please choose Knauf Fireshield.
- For impact resistance, please choose Knauf Denseshield.
- For greater sound protection, please choose Knauf Soundshield.

Product specification

Board Dimensions

Thickness : 9.5/12/12.5/15mm

Width : 1220mm

Length : 2440mm

*Special sizes are available upon request.


Board Weights (average values):

9.5mm	approx. 6.8kg/m ²
12mm	approx. 8.7kg/m ²
12.5mm	approx. 9.2kg/m ²
15mm	approx. 11.6kg/m ²

Density \approx 725kg/m³

Thermal Conductivity \approx 0.16w/mk

Edge Detail

Taper Edge(AK) 

Asbestos content:

None

Appearance

Grey Paper Liner

Standard...

EN520 - Type A

BS1230 - Type 1

BS476 part 4, 6, 7

BSEN13501 - 1

ASTM C1396

ISO 9001

LEED Credit Category

Material and Resources	Points
C1.2 Building Reuse	1
C2 Construction Waste Management	1-2
C3 Material Reuse	1-2
C4 Recycled Content	1-2
C5 Regional Material	1-2
Innovation Design	
C1.1-C1.4 Exemplary	1-2

Knauf Hong Kong Ltd.

Suite 702A,7/F 625 King's Rd, North Point, Hong Kong

Tel: +852 2964 9311 Fax: +852 2964 9313

www.knauf.com

enquiry.hk@knauf.com

KNAUF