

Note on English translation / Hinweise zur englischen Fassung

This is a translation of the product data sheet valid in Germany.

All stated details and properties are in compliance with the regulations of the German standards and building regulations. They are only applicable for the specified products, system components, application rules, and construction details in connection with the specifications of the respective certificates and approvals.

Knauf Gips KG denies any liability for applications outside of Germany as this requires changes acc. to the respective national standards and building regulations.




Drywall Systems

K442c.de

Product Data Sheet

2020-11



Cleaneo Tape

Self-adhesive tape for masking perforations in acoustic board ceilings

Product description

Cleaneo Tape is a self-adhesive thin PE fleece fabric.

Storage

Store frost-free and not above 30 °C.

Do not expose to direct sunlight.

Properties and added value

- Very thin to ensure visually inconspicuous transitions to the perforated board
- Self-adhesive for quick application
- Can be painted over immediately
- Does not expand with moisture ensuring perfect surfaces without impairments
- Paint permeability ensures seamless sanding of the edges without visible structural differences

Field of application

Cleaneo Tape is used to create smooth closed surfaces on board ceilings, e.g. on the edge areas (edge frieze) or surrounding access panels.

Application

Notes	Do not use for random perforation designs and for perforations > 12 mm. Areas on acoustic board ceilings that are masked off with the tape are no longer acoustically effective.
--------------	---

Pretreatment

Note	Apply Knauf Tiefengrund primer before application of the Cleaneo Tape to the gypsum board surface.
-------------	--

Application

Notes	Use a dispersion paint with good filling properties. Ensure that the Cleaneo Tape is not pushed into the perforations, for example, by your fingers or when pressure is applied during painting or coating. Cleaneo Tape may not overlap. Overlap the fleece at the corners and subsequently remove it with a double cut.
--------------	---

Two persons are required for the application of Cleaneo Tape. One person holds the roll of Cleaneo Tape at a flat angle, approx. 40 cm from the area where it is applied. Cleaneo Tape should always be unrolled straight to avoid the formation of creases and to avoid overlaps. The second person pulls off the paper backing and presses the Cleaneo Tape crease-free onto the perforated board using a wallpaper pressure roller.

For not completely straight connections to walls, cut off Cleaneo Tape at the edge and do not follow the course of the wall. Changes in direction can cause creases.

With edging or corner details, adapt the Cleaneo Tape with a double cut so that it is adhesively fully bonded onto the surface of the perforated board.

Subsequently, a commercially available paint with good filling and covering properties (e.g. Intol E.L.F.) is used for a paint coat. Apply an initial thin coat without pressure using a foam roller to seal the fleece fabric. Ensure that the paint is not forced through the fleece fabric.

When using paints that have poorer filling properties, repeat this step after drying. The most suitable tool is a paint roller that applies the paint with an overlap right up to the perforated board.

After the paint has fully dried, the remaining visible edge of the Cleaneo Tape in the area should be finely sanded for about 1 to 2 cm until a level transition between Cleaneo Tape and the perforation board is achieved. For sanding we recommend, for example, the Abranet® P180 or finer.

Ensure that the board liner of the perforated board is not damaged. Sanding with slight pressure and a few long sanding strokes by hand, without the use of a machine or a sanding block have proven to be useful.

Coating

After sanding, paint the ceiling in the usual way with dispersion paint.

Product range

Description	Width mm	Length m	Packaging unit	Material number	EAN
Cleaneo Tape	49	50	2 rolls / carton 320 rolls / pallet	00607366	4003982423412
	98		2 rolls / carton 160 rolls / pallet	00607372	4003982423467
	160		2 rolls / carton 120 rolls / pallet	00607391	4003982423498



Videos for Knauf systems and products can be found under the following link:

www.youtube.com/knauf



The iPad App Knauf Infothek now provides all the current information and documents from Knauf Gips KG at any time and in every location in a clear and comfortable way.

[Knauf Infothek](#)

Knauf Direct

Technical Advisory Service:

▶ knauf-direkt@knauf.de

▶ www.knauf.de

Knauf Gips KG Am Bahnhof 7, 97346 Iphofen, Germany

All technical changes reserved. Only the current printed instructions are valid. The stated information represents current state-of-the-art Knauf technology. The entire state of approved engineering rules, appropriate standards, guidelines, and rules of craftsmanship are not included herewith. These and all application instructions have to be adhered to separately by the installer. Our warranty is expressly limited to our products in flawless condition. All application quantities and delivery amounts are based on empirical data that are not easily transferable to other deviating areas.

All rights reserved. All amendments, reprints and photocopies, including those of excerpts, require our expressed permission.