

# KNAUF

## Knauf Airless Finish

Knauf Airless Finish is an alternative to traditional gypsum skimming for finishing walls and ceilings. Designed for spray application and ready-mixed, Airless finish is ideal for smooth finishes over Knauf plasterboard with a two-coat application onto a prepared Taped and Jointed drylined system. Applied 1-2mm thick with a drying time of 12-24 hours prior to decorating, applied using an airless high pressure piston pump machine.

*Product-Data-Sheet*



### Areas of Application

Smooth backgrounds such as taped and jointed plasterboard, pre-cast panels, aircrete panels, refurbishment over previously re-decorated surfaces.

### Compliance Standards

EN15824:2017

### Key Benefits

- Ready-mixed, no direct water supply needed on site
- Waste is typically 1%
- Very low VOC's and trace silica
- Provides a smooth, white flat finish to walls and ceilings

**Build on us.**

Creation Date: 24/11/2023  
Revision Reference: 004  
Revision Date: 28/03/2025

**Performance Data**

Reaction to Fire (R2F)	Thermal Conductivity ( $\lambda$ )	Dangerous Substances (DS)	Adhesion (MPa)
A2-s1,d0	NPD	NPD	>0.3

**Technical Information**

Weight (kg)	Colour	Approximate Consumption	Material Number
25	White	0.8-1.5kg/m <sup>2</sup> depending on thickness of application and substrate	470362

## Sustainability

### Substances of very high Concern (SVHC)

At the time of publication, under REACH UK and REACH EU regulations this product contains no SVHC. For more information please consult the Safety Data Sheet.

### Volatile Organic Compound Content (VOC)

Total VOC 28 days <1mg/m<sup>3</sup>

## Storage and Handling

Store in a dry, cool location at a temperature between 10°C to 30°C. Use within 12 months of manufacture. Keep away from frost and direct sunlight.

## Packaging

LDPE plastic sack, in a cardboard opening box, on a wooden pallet.

## Service Life

12 months from the date of production, which is printed on the bag.

## Disposal/Repair

For repairs throughout the projects lifetime, fibre-glass tape and jointing compound can be used for patch repairs. Any unused product can be kept sealed in the hopper to be sprayed in upcoming days. For product which will not be used, dispose in accordance with licensed collectors sorting instructions. European waste code: 17 09 04 - mixed construction and demolition wastes other than those mentioned in 17 09 01, 17 09 02 and 17 09 03.

## Health & Safety

Impermeable protective gloves, safety glasses with side shields due to splashing, and a dust mask when sanding are recommended. For full information, please refer to the safety data sheet.

## Application / Installation

Best applied with an Airless piston pump machine, tip size 531-535. Product is ready-mixed and does not need dilution. Applied in two coats 1-2mm thick, drying time is dependant on application thickness, temperature, ventilation, air humidity and type of substrate. Typical drying time is approximately 24 hours. Sand away any high spots with 180 grit sandpaper, or if using a sander with a vacuum which is recommended, use 220 grit sandpaper. Should not be used below 5°C or above 30°C. The drying time will be longer if used in temperatures between 5-10°C. Do not apply if relative humidity (R.H.) is above 65%.

If the surface is to be wallpapered after applying Airless Finish, prior to wallpapering prime the surface using Knauf Wallboard Primer.

## Additional Documentation

[Declaration of Performance UKCA](#)

[Declaration of Performance CE](#)

[Safety Data Sheet](#)

## Certification

[Environmental Product Declaration](#)

Datasheet for indoor air quality available on request.

Product Accreditations:



Knauf UK GmbH Company Accreditations:



The information given in this publication is believed to be current and accurate as at the date of publication, but no warranty, express or implied is given. Updates will not be automatically issued © Copyright Knauf 2024

### Customer Service

UK Tel: 0800 521 050  
Eire Tel: 01 4620739  
Email: [cservice@knauf.com](mailto:cservice@knauf.com)

### Technical Service

Tel: 0800 521050 (option 2)  
Email: [technical-uk@knauf.com](mailto:technical-uk@knauf.com)  
(excluding public holidays)

### UK Address

Knauf  
Kemsley Fields Business Park  
Sittingbourne  
Kent ME9 8SR

### Ireland Address

Knauf  
87 Broomhill Road  
Tallaght  
Dublin 24  
D24 WR85

Creation Date: 24/11/2023  
Revision Reference: 004  
Revision Date: 28/03/2025