

Aquapanel® Tape

Technical Data Sheet 12/2023



Aquapanel® Tape

Joint Tape

Product Description

Aquapanel® Tape (10cm) is a glass fibre tape with an alkali-resistant coating. It is used to reinforce joints on walls and ceilings in interior areas and on walls and ceilings in exterior areas.

Standards referred to

Fields of Application

- Aquapanel® Partition Wall Systems
- Aquapanel® Interior and Exterior Suspended Ceiling Systems
- Aquapanel® Drywall Lining Systems
- Aquapanel® Façade Systems

General Data

Description	Width (mm)	Length (m)	Packaging (pcs/box)	Material Number
Aquapanel® Joint Tape	100	50	12	429471

Technical Data

Description	
Weight / unit area (g / m ²)	160
Initial tear strength (N / 5 cm)	2200
Thickness approx. (mm)	0,5
Colour	Blue
Mesh size	4x4

Material Consumption

Product	Unit	m/m ²
Aquapanel® Joint Tape	m	approx. 2,1

System Performance Values

Performance values as sound insulation, fire resistance etc. may differ acc. to the drywall system to be applied. Please check the performance values of the drywall systems;

[Knauf Technical Website](#)

[Document Center](#)

Application

Application should be done acc. to the applicable standards (TS 1475) and acc. to the Knauf Technical Brochures of the respective drywall system.

▶ 444 YAPI - 9274

▶ www.knauf.com.tr / www.teknik.knauf.com.tr

▶ teknik@knauf.com

Center: Knauf Moment Beştepe Office, Beştepe Mah. 32.Cadde No:1/212-218 06560 Beştepe-Yenimahalle / ANKARA Tel: 0312 297 0100 Faks: 0312 266 4506