


KNAUF

AMF THERMATEX® Thermofon Colour




© Knauf Ceiling Solutions

AMF THERMATEX® Thermofon Colour odlikuje se glatkom, laminiranom završnom obradom i modernim vizualnim izgledom. Osigurava visoku apsorpciju zvuka za veću akustičku udobnost.

- Visoka apsorpcija zvuka, $\alpha_w = 0.80$ (H)
- Idealno za fitness centre, kina, multimedijske dvorane, ugostiteljske objekte, izložbene prostore, auto salone, benzinske postaje, gaming prostore i prostore sličnih namjena.

Build on us.

Karakteristike		Detaljne informacije							
Detalji rubova		Board 							
Dodatni detalji rubova na zahtjev									
Debljina (mm)		15							
Dimenzije (mm)		600 x 600 625 x 625 1200 x 600 1250 x 625							
Sustav		Vidljiva konstrukcija, demontažni - sustav C							
Težina		2.9 kg / m²							
Boja		 Crna							
Apsorpcija zvuka		EN ISO 354		$\alpha_w = 0.80$ (H) prema EN ISO 11654 - Razred B					
		Frekvencija f (Hz)		125	250	500	1000	2000	4000
		α_p		0.55	0.75	0.75	0.80	0.95	1.00
		NRC = 0.85 prema ASTM C 423							
Uzdužna zvučna izolacija		EN ISO 10848-2 $D_{n,f,w} = 28$ dB prema EN ISO 717-1		CAC = 29 dB prema ASTM E 413-10					
Zvučna izolacija		EN ISO 10140-2 $R_w = 13$ dB prema EN ISO 717-1							
Reakcija na požar		Euroclass A2-s1, d0 prema EN 13501-1 Razred A prema ASTM E 84							
Toplinska provodljivost		$\lambda = 0.040$ W/mk prema EN 12667							
Otpornost na vlagu		95% RH							
Kvaliteta zraka		 A+	 E1	 IACG					
Čišćenje	 								
Održivost	 47.8-48% (2023)	 EN 15804	 EC 1272/2008 Annex Q	 M1	 CRADLE TO CRADLE	 www.blauer-engel.de/uz132			