



KNAUF



Gypsum Board Datasheet

12 .2021

Knauf Regular Gypsum Board KS

Knauf Regular Gypsum Boards are gypsum wallboards which are essential for standard lightweight drywall constructions..



support.technique@knauf.dz
www.knauf.dz

Headquarters

CW N°64, 31063 Benfréha, Gdyl, Oran, Algérie
Boite Postale N°02, 31240 Boufatis, Oran, Algérie
Tél.: +213 (0) 41 76 34 70 / 71
Fax: +213 (0) 41 76 34 75 / 78

Algiers Office

Zone d'activités, Lot 23 El Achour.
16043, Alger, Algérie

Sétif office

Lot 36 N°21 Ras El ma, 19120
Ouled Saber, Sétif, Algérie

Technical Properties

- Appearance : Ivory / Paper Liner
- Thickness :
 - 6.5 mm / 12.5 mm / 15 mm / 18 mm
- Width : 1200 mm
- Length : 2400 or 3000 mm*
- Nominal Weight :
 - 8,4 kg/m² (12,5mm)
 - 12 kg/m² (15mm)
 - 16 kg/m² (18mm)
- Density: 600 - 820 kg/m³
- Application systems :
 - Knauf Joint filler Product
 - Knauf Joint Tape

Knauf plasterboards are made based on high-quality plaster, the level of purity of which is greater than or equal to 95%. The manufacturing process is subject to strict quality control procedures.

Important information:

The information provided in this leaflet is only intended to guide users in the selection and use of Knauf products. In this regard, we make every effort to ensure its accuracy. However, neither Knauf Plâtres sarl, nor any of its employees or subsidiaries, can assume any legal responsibility for the completeness or usefulness of this leaflet, in the event of a fault in the installation or construction of any structure whatsoever, or which may arise as a result of the use of this leaflet. It is therefore advisable to check this information before applying it. Readers of this leaflet are in particular advised to obtain an independent opinion on the use of our products in specific structures, installations or constructions, in order to guarantee compliance with the regulations in force, in particular those relating to hygiene and to safety.

Knauf Regular Gypsum Board KS

PROPERTIES

- Lightweight constructions
- Easy, fast and dry application
- Good sound insulation performance
- A material that breathes and balances room climate and humidity levels
- Environmentally friendly
- Limitless design options

APPLICATION FIELDS


Knauf Regular Gypsum Boards are the essential for standard lightweight drywall construction and are used as the cladding component for:

- New & renovation : in drywall partitions & suspended ceilings
- Locals : Education, Offices, Commerce, Health, Industrial, hotels

NORMS & CERTIFICATIONS

- Produced under the norm : **NA 17036 : 2011 / EN 520+A1 : 2009**
- TEDJ** Certification
- Fire reaction : **A2-s1,d0**
- Board type **A**

EDGE CONFIGURATION



Square Edge (SE)



Taper Edge (TE)



Dust in general, are irritating to the respiratory system, and may cause coughing and other disorders. | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if worn. Continue rinsing. | Get immediate medical advice/attention. | Dispose of contents and container in accordance with local/regional/national/international regulations.