



## AMF THERMATEX® Thermofon

- AMF THERMATEX® Thermofon odlikuje se glatkom, belom laminiranom završnom obradom i modernim vizuelnim dizajnom. Pruža visoku apsorpciju zvuka za poboljšanu zvučnu udobnost.
- Visoka apsorpcija zvuka (0.80(H)  $\alpha_w$ )
- Odlična vrednost refleksije svetlosti (88 %)
- ISO 4
- Idealno rešenje za kancelarije, učionice i prostorije za učenje.



<b>Detalji ivica</b> Ostale dimenzije i ivice na upit		Board 	Tegular 24/90 	Tegular 15/90 														
<b>Debljina (mm)</b>		15	15	15														
<b>Dimenzije (mm)</b> Ostali formati na upit		600 x 600 625 x 625 1200 x 600 1250 x 625	600 x 600 625 x 625 1200 x 600	600 x 600 625 x 625 1200 x 600														
<b>Sistem</b>		Vidljiva konstrukcija, demontažne ploče - sistem C																
<b>Težina</b>		2.9 kg / m <sup>2</sup>																
<b>Boja</b>		Bela																
<b>Apsorpcija zvuka</b>		EN ISO 354 $\alpha_w = 0.80$ (H) prema EN ISO 11654 - <b>Klasa B</b> <table border="1"> <thead> <tr> <th>Frekvencija f (Hz)</th> <th>125</th> <th>250</th> <th>500</th> <th>1000</th> <th>2000</th> <th>4000</th> </tr> </thead> <tbody> <tr> <td><math>\alpha_p</math></td> <td>0.55</td> <td>0.75</td> <td>0.75</td> <td>0.80</td> <td>0.95</td> <td>1.00</td> </tr> </tbody> </table> NRC = <b>0.85</b> prema ASTM C 423			Frekvencija f (Hz)	125	250	500	1000	2000	4000	$\alpha_p$	0.55	0.75	0.75	0.80	0.95	1.00
Frekvencija f (Hz)	125	250	500	1000	2000	4000												
$\alpha_p$	0.55	0.75	0.75	0.80	0.95	1.00												
<b>Uzdužna zvučna izolacija</b>		EN ISO 10848-2 $D_{n,f,w} = 28$ dB prema EN ISO 717-1																
<b>Zvučna izolacija</b>		EN ISO 10140-2 $R_w = 13$ dB prema EN ISO 717-1																
<b>Reakcija na požar</b>		Euroclass <b>A2-s1, d0</b> prema EN 13501-1	RUS <b>KM1 (G1, V1, D1, T1)</b> prema 123-FZ															
<b>Refleksija svetlosti</b>		<b>88%</b>																
<b>Toplotna provodljivost</b>		$\lambda = 0.040$ W/mk prema EN 12667																
<b>Otpornost na vlagu</b>		<b>95% RH</b>																
<b>Klasa čistoće prostora</b>		<b>ISO 4</b> prema EN ISO 14644-1																
<b>Kvalitet vazduha</b>		 A+	 E1	 IACG														
<b>Čišćenje</b>																		
<b>Održavanje</b>																		
		42%																
			<a href="http://www.blauer-engel.de/uz132">www.blauer-engel.de/uz132</a>															

Proizvodi se mogu razlikovati između prodajnih područja. Molimo kontaktirajte svog lokalnog predstavnika. Za dodatne i pravne informacije posetite našu web stranicu.