



Knauf SFS U Track

Knauf SFS (Steel Framing Systems) U Track are galvanised solid steel 'U' sections which can be used either as a base track or head track for Knauf SFS C studs.

Product-Data-Sheet



Areas of Application

Light gauge steel sections to provide structural support for various cladding systems and accommodate various loading types.

Sections are for use in supporting lateral loads only as part of an external enveloping system

Compliance Standards

BS EN 1090-1:2009 + A1:2011

Key Benefits

- Full design service available including BIM modelling
- Cut to length to reduce on site wastage
- Part of a full BBA certified Throughwall system

Build on us.

Creation Date: 08/06/2023
Revision Reference: 002
Revision Date: 03/02/2025

Product Information

Performance Data

Reaction to Fire (R2F)	Flexural Strength	Load Bearing Capacity	Durability	Yield Strength
Class A1 Steel only	BS EN 10162:2003 - cross sectional tolerances & BS EN 1090-2:2018	Design calculation and section properties according to BS EN 1993	S450GD+Z275	S450GD

Technical Information

Length (mm)	Webb (mm)	Flange (mm)	Gauge (mm)	Weight (kg/lm)	Material Number
cut to order	74	40	1.2	1.43	675619
cut to order	74	70	1.8	2.91	675620
cut to order	74	70	2.0	3.23	675621
cut to order	94	40	1.2	1.62	675622
cut to order	94	70	1.8	3.26	675623
cut to order	94	70	2.0	3.61	675624
cut to order	104	40	1.2	1.69	675625
3000	104	40	1.2	1.69	840995
cut to order	104	70	1.8	3.35	675626
cut to order	104	70	2.0	3.71	675627
cut to order	124	40	1.2	1.90	675628
cut to order	124	70	1.8	3.69	675629
cut to order	124	70	2.0	4.08	675630
cut to order	154	40	1.2	2.16	675631
3000	154	40	1.2	2.16	840997
cut to order	154	70	1.8	4.04	675632
cut to order	154	70	2.0	4.49	675633
cut to order	204	40	1.2	2.63	675634
cut to order	204	70	1.8	4.75	675635
cut to order	204	70	2.0	5.28	675636
cut to order	254	40	1.2	3.09	675637
cut to order	254	70	1.8	5.45	675638
cut to order	254	70	2.0	6.06	675639
cut to order	304	40	1.2	3.60	675640
cut to order	304	70	1.8	6.23	675641
cut to order	304	70	2.0	6.91	675642

Additional Information

Sustainability

Total Recycled Content

18.41%

Recyclability

Fully recyclable

Storage and Handling

When using hand tools eye protection should be worn. Formed edges and cut ends may be sharp. Gloves should be worn when handling the material to avoid risk of lacerations. Head protection should be worn when overhead hazards exist. Avoid prolonged contact with skin and wear protective clothing when handling metal sections.

Packaging

Supplied bundled in small packs and strapped together in large packs for fork-lift truck off-loading, which should be stacked in a safe and stable manner. The bands or straps should not be used for lifting. Metal sections may spring apart when banding is released.

Disposal/Repair

Recycle or can be disposed of at an authorised landfill site in accordance with local or national controls.

Health & Safety

Please refer to our Safety Data Sheet for guidance on Personal Protection Equipment required for the handling and installation of this product.

Application / Installation

Knauf SFS U Track can be fixed to the substrate using Knauf SFS Screws.

Additional Documentation

[Declaration of Performance UKCA](#)

[Declaration of Performance CE](#)

[Safety Data Sheet](#)

Certification

[Environmental Product Declaration](#)

Product Accreditations:



Knauf UK GmbH Company Accreditations:



The information given in this publication is believed to be current and accurate as at the date of publication, but no warranty, express or implied is given. Updates will not be automatically issued © Copyright Knauf 2024

Customer Service

UK Tel: 0800 521 050

Eire Tel: 01 4620739

Email: cservice@knauf.com

Technical Service

Tel: 0800 521050 (option 2)

Email: technical-uk@knauf.com
(excluding public holidays)

UK Address

Knauf
Kemsley Fields Business Park
Sittingbourne
Kent ME9 8SR

Ireland Address

Knauf
87 Broomhill Road
Tallaght
Dublin 24
D24 WR85

Creation Date: 08/06/2023

Revision Reference: 002

Revision Date: 26/02/2025