



## DECLARATION OF PERFORMANCE

No: KAGE\_001

1. Unique identification code of the product-type: **AQUAPANEL® Cement Board Indoor**  
ID\_12,5\_901, ID\_12,5\_903
2. Intended use/es: **AQUAPANEL® Cement Board Indoor is used for construction of indoor walls and ceilings especially in wet and humid areas.**
3. Manufacturer: **Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D - 58638 Iserlohn**  
**Tel.: +49 2374 5036-0, Fax: +49 2374 5036-300, E-Mail: [aquapanel.info@knauf.com](mailto:aquapanel.info@knauf.com)**
4. Authorised representative: not applicable
5. System/s of AVCP: System 3 (reaction to fire), System 4 (all other product characteristics)
6. a) Harmonised standard: not applicable  
Notified body/ies: not applicable
6. b) European Assessment Document: EAD 15-21-0024-05.04  
European Technical Assessment: **ETA-07/0856**, dated 11.10.2017  
Technical Assessment Body: Deutsches Institut für Bautechnik DIBt  
Notified body/ies: MPA Nordrhein-Westfalen (0432) determined the reaction to fire classification
7. Declared performance/s:

Essential Characteristics	Performance
<b>Safety in case of fire (BWR 2)</b>	
Reaction to fire	Class A1 according to EN 13501-1:2010-01
<b>Hygiene, health and environment (BWR 3) / Content, emission and/or release</b>	
Vapour Permeability	$\mu$ = No performance assessed
Substance(s) classified as EU-cat. Carc. 1A/1B	The product does not contain these dangerous substances.
Substance(s) classified as EU-cat. Muta. 1A/1B	
Substance(s) classified as EU-cat. Acute Tox. 1, 2 and/or 3; substance(s) classified as EU-cat. Repr. 1A/1B; substance(s) classified as EU-cat. STOT SE 1 and/or STOT RE 1	
SVOC and VOC	No performance assessed
<b>Safety and accessibility in use (BWR 4)</b>	
Thickness	$e = 12,5 \text{ mm} \pm 1,25 \text{ mm}$
Dimensions (length and width)	Annex C
Straightness of edges	0,1 % = Level I according to EN 12467
Squareness of edges	2 mm/m = Level I according to EN 12467

**AQUAPANEL®**



Essential Characteristics	Performance	
<b>Safety and accessibility in use (BWR 4)</b>		
Density	$\rho_{\text{mean}} = 1100 \pm 100 \text{ kg/m}^3$	
Moisture content	$H = 8,0 \text{ \% by mass}$	
Water permeability	Passed	
Dimensional stability – length	$\delta_{65,85} = 0,3 \text{ mm/m}$ , $\delta_{65,30} = -0,3 \text{ mm/m}$	
Dimensional stability – thickness	$\delta_{65,85} = 0,09 \text{ \%}$ , $\delta_{65,30} = -0,06 \text{ \%}$	
Bending strength	$f_{m,0,k} = 6,0 \text{ N/mm}^2$ , $f_{m,90,k} = 6,3 \text{ N/mm}^2$ (smooth side under tension) $f_{m,90,k} = 5,9 \text{ N/mm}^2$ (smooth side under compression)	
Bending modulus of elasticity	$E_{m,0,\text{mean}}$ , $E_{m,90,\text{mean}}$ : No performance assessed	
Pull through resistance AQUAPANEL Maxi Screw	Type SN (Annex A1)	$f_{\text{head},k} = 280 \text{ N}$
	Type SB (Annex A2)	$f_{\text{head},k} = 390 \text{ N}$
Impact resistance	$IR_{\text{mean}} = 9,8 \text{ mm/m}$	
Water adsorption	$w_a = 29,3 \text{ \% by mass}$	
Warm water resistance for category C	$R_{L,ww} = 0,75$	
Soak-dry resistance for category C	$R_{L,SD} = 0,98$	
Durability of metal parts	Annex B1	
<b>Energy economy and heat retention (BWR 6)</b>		
Thermal conductivity	$\lambda_{10,1r}$ = No performance assessed	
Air permeability	The "AQUAPANEL Cement Board Indoor" is not permeable to air.	

8. Appropriate Technical Documentation and/or Specific Technical Documentation: not applicable

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Dr. Thomas Koslowski  
General Manager

Iserlohn, 09.11.2018




28.5.2014 L 159/43 Official Journal of the European Union EN

**AQUAPANEL®**