



## DECLARATION OF PERFORMANCE

### No. 0022\_Allround\_Sanitetssilikone\_2020-07-23

1. Unique identification code of the product-type: **EN 15651-1 - F-EXT-INT-CC**
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4): **Knauf Bauprodukte Allround Sanitetssilikone**
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Non-load-bearing sealants for interior and exterior applications**
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5): **Knauf Bauprodukte GmbH & Co. KG, Am Bahnhof 7, D-97346 Iphofen, Tel. +499323 31-0, Fax +499323 31-277, E-Mail [info@knauf-bauprodukte.de](mailto:info@knauf-bauprodukte.de)**

System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V: **System 3**

In the case of a declaration of performance covering a construction product covered by a harmonised standard SKZ-**TeConA GmbH (NB 1213)** has **determined the product type by means of type testing** according to system 3 and issued the following: **Test Certificate No. 106141/13-1: Test Institute Hoch (NB 1508)** has **carried out the fire behaviour test** according to System 3 and issued the following: **Classification report No. KB Hoch-131113. Factory production control by the manufacturer.**

9. Declared performance

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1	EN 15651-1:2012-09
Dangerous substances	NPD	EN 15651-1:2012-09
Water tightness and air tightness a) Resistance to flow b) Loss of volume c) Tensile properties at maintained extension after immersion in water d) Tensile properties for non-load-bearing joint sealants used in joints in areas with cold climate (-30 °C) e) Tensile properties for non-load-bearing joint sealants used in joints in areas with cold climate (-30 °C)	$\leq 2 \text{ mm}^2$ $\leq 10 \%$ pass $\leq 0,9 \text{ MPa}$ pass	EN 15651-1:2012-09
Durability	pass	EN 15651-1:2012-09

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: **Not relevant**

8. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4:

Signed for and on behalf of the manufacturer by:  
ppa. Ulrich Köhler  
(General Manager)

Iphofen, 2020-07-23  
(place and date of issue)