

AQUAPANEL® Exterior Primer (Basecoat)

Technical Data Sheet 12/2023



Aquapanel® Exterior Primer (Basecoat)

Primer - Synthetic Dispersion with high alkali resistance

Product Description

Water-based primer used on Aquapanel® outdoor as a bonding layer for plastering.

Storage

- Buckets should be kept unopened in a dry environment at 5-35 °C and should not be exposed to direct sunlight
- Storage life is only valid for unopened buckets.
- Unused buckets should be kept unopened
- Buckets should be kept in frost-free conditions.

Standards referred to

-

Fields of Application

- Plastered Aquapanel® surfaces before paint or mineral finishing render.
- Plastered surfaces before paint or mineral finishing render.

Properties

- High resistance to alkalis
- Dries to white

Aquapanel® Exterior Primer (Basecoat)

Primer - Synthetic Dispersion with high alkali resistance



General Data

Description	Weight (kg/m)	Packaging (pcs)	Shelf Life	Material Number
Aquapanel® Exterior Primer	15	1	18 month	49299

Technical Data

Description	
Working duration (min / m ²)	1
Consumption (g / m ²)	100-150
Climate conditions	> 5°C
Completely Drying Time	24 hour

System Performance Values

Performance values as sound insulation, fire resistance etc. may differ acc. to the drywall system to be applied. Please check the performance values of the drywall systems;

[Knauf Technical Website](#)
[Document Center](#)

Application

Application should be done acc. to the applicable standards (TS 1475) and acc. to the Knauf Technical Brochures of the respective drywall system.