

Aquapanel® Basecoat Plaster

Technical Data Sheet 12/2023



Aquapanel® Basecoat Plaster

Basecoat Plaster

Product Description

Aquapanel® Basecoat used in outdoor and indoor Aquapanel® systems as joint filler and basecoat plaster.

Storage

Bags should be kept in a dry environment on pallets and contact with water should be avoided. It is proposed to keep the bags horizontally on a flat surface during transportation and stocking. Pallets should not be exposed to direct sunlight

Standards referred to

TS EN 998 - 1

Fields of Application

- Aquapanel® indoor and outdoor board joint filler basecoat plaster.

Properties

- Flexible
- Synthetic resin enhanced
- Weather resistant
- Water repellent
- High adhesion

General Data

Description	Weight (kg/m)	Packaging (pcs)	Shelf Life	Material Number
Aquapanel® Basecoat Plaster	25	1	12 month	49157

Technical Data

Description	Grey
Water mixing quantity (L)	4,5-5
Reaction to fire	A1
Water absorption	W2
Water vapour diffusion resistance (μ)	5/20
Bonding (dry, wet)	7,8
Adhesion (N/m ²)	$\geq 0,08$
Thermal conductivity λ_{10} dry (EN 1745)	$\leq 0,47$ W / (m·K), P=50% $\leq 0,54$ W / (m·K), P=90%
Working time	45 min
Working temperature	$\geq +5$ °C

System Performance Values

Performance values as sound insulation, fire resistance etc. may differ acc. to the drywall system to be applied. Please check the performance values of the drywall systems;

[Knauf Technical Website](#)
[Document Center](#)

Application

Application should be done acc. to the applicable standards (TS 1475) and acc. to the Knauf Technical Brochures of the respective drywall system.

▶ 444 YAPI - 9274

▶ www.knauf.com.tr / www.teknik.knauf.com.tr

▶ teknik@knauf.com

Center: Knauf Moment Beştepe Office, Beştepe Mah. 32.Cadde No:1/212-218 06560 Beştepe-Yenimahalle
/ ANKARA Tel: 0312 297 0100 Faks: 0312 266 4506