
































## AMF TOPIQ® Prime



- AMF TOPIQ® Prime vrlo je lagana ploča od kamene vune s modernom, glatkom površinom.
- Odlična apsorpcija zvuka (0.95(H)  $\alpha_w$ )
- Odlična refleksija svjetlosti (88 %)
- ISO 5
- Idealno rješenje za urede, učionice, znanstvene inkubatore i podzemne garaže



<b>Detalji rubova</b> Ostali detalji rubova na upit		Board 	Tegular 24/90 	Tegular 15/90 														
<b>Debljina (mm)</b>		15	15	15														
<b>Dimenzije (mm)</b> Ostali formati na upit		600 x 600 625 x 625 1200 x 600 1250 x 625	600 x 600 625 x 625 1200 x 600	600 x 600 625 x 625 1200 x 600														
<b>Sustav</b>		Vidljiva konstrukcija, demontažni - sustav C																
<b>Težina</b>		2,4 kg / m <sup>2</sup>																
<b>Boja</b>		Bijela																
<b>Aposrpcija zvuka</b>		EN ISO 354 $\alpha_w = 0.95$ prema EN ISO 11654 - <b>Class A</b> <table border="1"> <thead> <tr> <th>Frekvencija f (Hz)</th> <th>125</th> <th>250</th> <th>500</th> <th>1000</th> <th>2000</th> <th>4000</th> </tr> </thead> <tbody> <tr> <td><math>\alpha_p</math></td> <td>0.50</td> <td>0.85</td> <td>0.95</td> <td>0.90</td> <td>1.00</td> <td>1.00</td> </tr> </tbody> </table> NRC = <b>0.90</b> prema ASTM C 423			Frekvencija f (Hz)	125	250	500	1000	2000	4000	$\alpha_p$	0.50	0.85	0.95	0.90	1.00	1.00
Frekvencija f (Hz)	125	250	500	1000	2000	4000												
$\alpha_p$	0.50	0.85	0.95	0.90	1.00	1.00												
<b>Uzdužna zvučna izolacija</b>		EN ISO 10848-2 $D_{n,f,w} = 24$ dB prema EN ISO 717-1																
<b>Zvučna izolacija</b>		EN ISO 10140-2 $R_w = 13$ dB prema EN ISO 717-1																
<b>Reakcija na požar</b>		Euroclass <b>A1</b> prema EN 13501-1																
<b>Refleksija svjetlosti</b>		<b>88%</b>																
<b>Otpornost na vlagu</b>		<b>100% RH</b>																
<b>Razred čistoće prostora</b>		<b>ISO 5</b> prema EN ISO 14644-1																
<b>Kvaliteta zraka</b>		 A	 E1	 IAC														
<b>Čišćenje</b>																		
<b>Održavanje</b>		 28.4%																
			 <a href="http://www.blauer-engel.de/uz132">www.blauer-engel.de/uz132</a>															

Proizvodi se mogu razlikovati između prodajnih područja. Molimo kontaktirajte svog lokalnog prodajnog predstavnika. Za dodatne i pravne informacije posjetite našu web stranicu.