







ADAGIO HD⁺ 19 mm Mineralni plafoni



- ADAGIO HD⁺ 19 mm nudi glatku, ujednačenu i izdržljivu površinu s neuporedivom otpornošću na ogrebotine i najsvetlijim belim izgledom bez premca. Zahvaljujući odličnoj propusnosti vazduha (bez efekta filtera), površina ostaje belja i svetlija duže vreme. Ploča takođe pruža ravnotežu apsorpcije i prigušenja zvuka, kao i visoku refleksiju svetlosti.
- Izvrsna apsorpcija zvuka (0,90 α_w) sa dobrom zvučnom izolacijom (34 dB).
- Dodatne akustičke opcije potražite u ADAGIO HD⁺ 30 mm i ADAGIO HD⁺ 35 mm.
- Izvrsna vrednost refleksije svetlosti: 88%.
- ISO 4, Zlatni sertifikat za kvalitet vazduha u zatvorenom prostoru i bronzani sertifikat Cradle to Cradle®.
- Idealno za individualne / privatne kancelarije i hodnike.

Build on us.



Karakteristike		Detaljne informacije							
Detalji ivica		Board 	Tegular 24/90 	Tegular 15/90 	SL2 	Finesse 			
Debljina (mm)		19	19	19	19	19			
Dimenzije (mm)		600 x 600 625 x 625 675 x 675 1200 x 300 1200 x 600 1250 x 625 1500 x 600 1800 x 600	600 x 600 625 x 625 675 x 675 1200 x 300 1200 x 600 1250 x 625 1500 x 600 1800 x 600	600 x 600 625 x 625 675 x 675 1200 x 300 1200 x 600 1250 x 625 1350 x 300 1350 x 600 1500 x 600 1800 x 600	1350 x 300 1350 x 600 1500 x 300 1800 x 300 2000 x 300	600 x 600 625 x 625 1200 x 600 1250 x 625			
Sistem		Vidljiva konstrukcija, demontažne ploče - sistem C		Vidljiva konstrukcija, demontažne ploče - sistem C Vidljiva konstrukcija - paralelni Bandraster profili, demontažne ploče - sisitem I.3 Vidljiva konstrukcija - Koridor elementi, demontažne ploče - sistem F.3		Poluskrivena konstrukcija, demontažne lamelne ploče - sistem I.3 Poluskrivena konstrukcija, demontažne lamelne ploče na Bandraster paralelnim profilima - sistem I.2 Poluskrivena konstrukcija, demontažne lamelne ploče za koridore - sistem F.2			
Težina		5.2 kg / m ²							
Boja		 Bela							
Apsorpcija zvuka		EN ISO 354							
		Frekvencija f (Hz)		125	250	500	1000	2000	4000
		α_p		0.45	0.75	0.85	0.85	1.00	1.00
		NRC = 0.90 prema ASTM C 423							
Uzdužna zvučna izolacija		EN ISO 10848-2 $D_{n,f,w}$ = 34 dB prema EN ISO 717-1							
		CAC = 35 dB prema ASTM E 413-10							
Zvučna izolacija		EN ISO 10140-2 R_w = 17 dB prema EN ISO 717-1							
Reakcija na požar		Euroclass A2-s1, d0 prema EN 13501-1							
Refleksija svetlosti		88%							
Toplotna provodljivost		λ = 0.060 W/mk prema EN 12667							
Propusnost vazduha		PM2 (≤ 50 m ³ /hm ²) prema DIN 18177							
Otpornost na vlagu		95% RH							
Klasa čistoće prostora		ISO 4 prema EN ISO 14644-1							
Kvalitet vazduha		 A+	 E1	 IACG					
Čišćenje									
Održavanje		 EN ISO 14021 49.1% (2024)	 BIOSOLUBLE WOOL EC 1272/2008 Annex G	 M1	 cradle to cradle BRONZE	 www.blauer-engel.de/uz132			