

AQUAPANEL® Maxi Screw SU

Technical Data Sheet 12/2023



Aquapanel® Maxi Screw SU

Screw

Product Description

Aquapanel® self tapping screws with countersunk cross-heads for fixing Aquapanel® indoor and outdoor to metal substructure with thickness of 0,6 mm up to 0.7 mm.

Standards referred to

DIN 18182 - 2

Fields of Application

- Aquapanel® Partition Wall Systems
- Aquapanel® Suspended Ceiling Systems
- Aquapanel® Drywall Lining Systems

Properties

- Cleand and easy installation
- 720 hours salt and corrosion resistance

Technical Data

Description	Diameter (mm)	Length (mm)	Weight (kg/box)	Packaging (pcs./box)	Material Number
Aquapanel® Maxi Screw SU	4,2	25	1,85	1000	87319
		39	1,40	500	53500

System Performance Values

Performance values as sound insulation, fire resistance etc. may differ acc. to the drywall system to be applied. Please check the performance values of the drywall systems;

[Knauf Technical Website](#)
[Document Center](#)

Application

Application should be done acc. to the applicable standards (TS 1475) and acc. to the Knauf Technical Brochures of the respective drywall system.

▶ 444 YAPI - 9274

▶ www.knauf.com.tr / www.teknik.knauf.com.tr

▶ teknik@knauf.com

Center: Knauf Moment Beştepe Office, Beştepe Mah. 32.Cadde No:1/212-218 06560 Beştepe-Yenimahalle
/ ANKARA Tel: 0312 297 0100 Faks: 0312 266 4506