

# ENVIRONMENTAL PRODUCT DECLARATION

In accordance with ISO 14025, ISO 21930 and EN 15804+A2 for:

## Rocksilk® Flat Roof Slab Extra

From

**KNAUF**INSULATION

|                          |                                                                                             |
|--------------------------|---------------------------------------------------------------------------------------------|
| Program:                 | The International EPD® System<br><a href="http://www.environdec.com">www.environdec.com</a> |
| Programme operator:      | EPD International AB                                                                        |
| EPD registration number: | S-P-04015                                                                                   |
| Publication date:        | 2021-06-11                                                                                  |
| Validity date:           | 2026-06-11                                                                                  |
| Version:                 | 2                                                                                           |
| Date of update:          | 2024-03-07                                                                                  |

## Programme-related information and verification

The EPD owner has the sole ownership, liability, and responsibility for the EPD.

EPDs within the same product category but from different programmes may not be comparable. EPDs of construction products may not be comparable if they do not comply with EN 15804+A2:2019. For further information about comparability, see EN 15804+A2:2019 and ISO 14025.

|                                        |                                                                                                                                                                                                                                    |
|----------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Programme:</b>                      | The International EPD® System<br>EPD International AB<br>Box 210 60<br>SE-100 31 Stockholm<br>Sweden<br><a href="http://www.environdec.com">www.environdec.com</a><br><a href="mailto:info@environdec.com">info@environdec.com</a> |
| <b>EPD registration number:</b>        | S-P-04015                                                                                                                                                                                                                          |
| <b>Published:</b>                      | 2021-06-11                                                                                                                                                                                                                         |
| <b>Valid until:</b>                    | 2026-06-11                                                                                                                                                                                                                         |
| <b>EPD owner</b>                       | Knauf Insulation Sprl<br>Rue de Maestricht 95<br>4600 Visé<br>Belgium                                                                                                                                                              |
| <b>Product Category Rules:</b>         | PCR 2019:14. Construction products (EN 15804:A2)<br>Version 1.1<br>c-PCR005 Thermal insulation products (EN 16783: 2017)                                                                                                           |
| <b>Product group classification:</b>   | UN CPC 37                                                                                                                                                                                                                          |
| <b>Reference year for plant data:</b>  | 2019                                                                                                                                                                                                                               |
| <b>Geographical application scope:</b> | Europe                                                                                                                                                                                                                             |

|                                                                                                                                                          |
|----------------------------------------------------------------------------------------------------------------------------------------------------------|
| CEN standard EN 15804+A2 serves as the Core Product Category Rules (PCR)                                                                                 |
| Product category rules (PCR): PCR 2019:14. Construction products (EN 15804+A2:2019) Version 1.1<br>c-PCR005 Thermal insulation products (EN 16783: 2017) |
| PCR review was conducted by: The Technical Committee of the International EPD® System                                                                    |
| Independent third-party verification of the declaration and data, according to ISO 14025:2006.                                                           |
| <input checked="" type="checkbox"/> EPD process certification <input type="checkbox"/> EPD verification                                                  |
| Certified by: Bureau Veritas certification Sverige AB SE006629-3                                                                                         |
| Procedure for follow-up of data during EPD validity involves third party verifier:                                                                       |
| <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No                                                                                      |

*An EPD should provide current information and may be updated if conditions change. The stated validity is therefore subject to the continued registration and publication at [www.environdec.com](http://www.environdec.com).*

## General information

### Information about the company

#### Description of the organisation:

Knauf Insulation has more than 40 years of experience in the insulation industry and is one of the most respected names in insulation worldwide. Knauf Insulation is manufacturing products and solutions mainly in glass and Rock Mineral Wool, as well as wood wool. We operate more than 37 manufacturing sites globally in 15 countries and employ more than 5,000 people.

The Headquarters are located in Visé, in Belgium.



#### Product-related or management system-related certifications:

All Knauf Insulation sites, including the related site for this EPD, are ISO 9001, ISO 14001, ISO 50001 and ISO 45001 certified under the scope "Design, Development and Production of Insulation Materials and Systems".

Knauf Insulation supports the Ten Principles of the United Nations Global Compact on human rights, labor, environment and anti-corruption. UK- Queensferry Plant holds BES 6001 Responsible Sourcing of Construction Products Certificate.

#### Name and location of production site:

The application in construction of the concerned product is Europe. The data utilized for the production stage life cycle assessment are related to production plants located in Queensferry.

2 Chemistry Ln, Queensferry, Deeside CH5 2DA, United Kingdom

### Information about Rock Mineral Wool production

The Rock Mineral Wool Products for Building Construction are available in the form of slabs, boards, lamellas and rolls. RMW slabs are used as a thermal, acoustical and fire insulation product.

In general, the density for Rock Mineral Wool products ranges from 20 to 200 kg/m<sup>3</sup>. In terms of composition, the inorganic part (92-98%) is composed of volcanic rocks, typically basalt, and some dolomite and with an increasing proportion of recycled material in the form of briquettes, a mix of stone wool scrap, other secondary materials and cement.

The remaining fraction is the thermo set resin binder.



## Product information

**Product name:** Rocksilk® Flat Roof Slab Extra

**Product identification:** The declared insulation Rocksilk® Flat Roof Slab Extra is a compact Rock Mineral Wool, uncoated, unfaced of 1m<sup>2</sup> (considered for this EPD).

For the placing on the market in the EU/EFTA (with exception of Switzerland), the regulation (EU) N°305/2011 of the Construction Product Regulation (CPR) applies.

For the UK market (England, Wales and Scotland), the UK Regulation SI 2019 No. 4651 applies. Besides, the SI 2020 No. 1359 amendment allows the usage of EU CPR in Northern Ireland. The concerned products have Declarations of Performance (DoP) R4208HPCPR, RU4208HPCPR.

**Product description:** The main application for Rocksilk® Flat Roof Slab Extra is thermal insulation of flat roofs.

**UN CPC code:**

37990: Non-metallic mineral products (including mineral wool, expanded mineral materials,

worked mica, articles of mica, non-electrical articles of graphite or other carbon and articles of peat).

**Geographical scope:** The product is manufactured in Queensferry with United Kingdom (UK) energy mix for electricity. Regarding the market area, the product is mainly marketed in Europe.

**Energy:**

Electricity mix and gas inputs are taken from UK (United Kingdom) with reference year 2016 (the latest available in GaBi database). 0.339 kg of CO<sub>2</sub> is released for 1 kwh of Electricity consumption from UK.

**Technical Characteristics:**

| Parameter                                   | Value                          |
|---------------------------------------------|--------------------------------|
| Thermal conductivity/ EN 12667              | 0.040 W/(mK) at 10°C           |
| Water vapor diffusion resistance (EN 12086) | 1                              |
| Thermal Resistance (ISO 8301)               | 2.69 m <sup>2</sup> K/W        |
| Reaction to fire (EN 13501-1)               | A1                             |
| Declared density range/ EN 1602             | 180 kg/m <sup>3</sup> (+/-10%) |
| Melting point of fibers DIN 4102-17         | ≥ 1000°C                       |

## LCA information

### Functional unit / declared unit

The declared unit is 1m<sup>2</sup> of unfaced, uncoated Rock Mineral Wool Rocksilk® Flat Roof Slab Extra with a thickness of 105 mm. The declared lambda is 0.040 W/mK. The density used for the calculation of this specific LCA is 180 kg/m<sup>3</sup>.

**Reference service life:** The RSL or durability of Rocksilk® Flat Roof Slab Extra is as long as the lifetime of the building equipment in which it is used (at least 50 years).

### Time representativeness & Information on Specific Data:


Plant production data for the complete year 2019. The reference product groups considered in this EPD are produced in one single manufacturing plant; therefore, variations issue for sites is not relevant.

The data which is used to carry out the LCA calculations contains >90 % specific data and below 10 % generic data.

### Database(s) and LCA software used:

The LCA model, the data aggregation and environmental impacts are calculated with the software GaBi 10.0 and its Service Pack 40 databases. The impact models used are those indicated in EN 15804:2012+A2:2019.

### System diagram:



### Description of system boundaries:

The system boundary of the EPD follows the modularity approach defined by the EN 15804:2012+A2:2019.

**The type of EPD is cradle-to-grave.**

List and explanation of the modules declared in the EPD.

**The product stage (A1-A3) includes:**

- A1 - raw material extraction and processing, processing of secondary material input (e.g. recycling processes),
- A2 - transport to the manufacturer and
- A3 - manufacturing.

This includes provision of all materials, products and energy, packaging processing and its transport, as well as waste processing up to the end-of-waste state or disposal of final residues during the product stage.

The LCA results are given in an aggregated form for the product stage, meaning that the modules A1, A2 and A3 are considered as a unique module A1-A3.

| Product Parameters       | Value                          |
|--------------------------|--------------------------------|
| Declared density         | 180 kg/m <sup>3</sup> (+/-10%) |
| Rock mineral wool weight | 18.90 kg                       |
| Surface                  | 1m <sup>2</sup>                |
| Thickness                | 105 mm                         |
| Volume                   | 0.11 m <sup>3</sup>            |
| Packaging Plastic sheet  | 0.03 kg                        |
| Packaging Wooden pallet  | 1.15 kg                        |

**The construction process stage includes:**

- A4 - transport to the construction site and
- A5 - installation into the building.

The transport to the building site (A4) and installation (A5) included in this LCA use the following parameters:

| Parameter                                                                   | Value                                                      |
|-----------------------------------------------------------------------------|------------------------------------------------------------|
| Average transport distance                                                  | 600 km                                                     |
| Type of fuel and vehicle consumption or type of vehicle used for transport. | Truck Euro 6 (28 – 32 t / 22 t payload). 140 L for 100 km. |
| Truck capacity utilization (including 30% of empty returns)                 | 68 % of the weight capacity                                |
| Loss of materials in construction site                                      | 2%                                                         |
| Packaging Wooden pallet                                                     | 40% recycled, 60% incinerated                              |
| Packaging Plastic sheet                                                     | 40% recycled, 60% incinerated                              |

The treatment of the packaging waste after the installation of the product (A5) has been considered.

**The Use stage (B1-B7) includes:**

- B1: Use
- B2: Maintenance
- B3: Repair
- B4: Replacement
- B5: Refurbishment
- B6: Operational Energy Use
- B7: Operational Water Use

Once installation is complete, no actions or technical operations are required during the use stages until the end of life. Therefore, the mineral wool has no impact (excluding potential energy savings) on this stage.

**The end-of-life stage includes:**

- C1 - de-construction, demolition,
- C2 - transport to waste processing,
- C3 - waste processing for reuse, recovery and/or recycling and
- C4 - disposal.

This includes provision of all transports, materials, products and related energy and water use. The common manual dismantling impact of insulation is considered as very small and can be neglected in C1.

Although Rock Mineral Wool products from Knauf Insulation are partly recycled at their end-of-life, an established collection system does not yet exist. Therefore, the assumption chosen in this study, 100% landfill (C4) after the use phase, is the most conservative approach.

| Parameter                                                                   | Value                                                                                                         |
|-----------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------|
| Disposal type (mineral wool)                                                | 100% landfill                                                                                                 |
| Average transport distance waste (C2)                                       | 50 km                                                                                                         |
| Type of fuel and vehicle consumption or type of vehicle used for transport. | Truck-trailer, Euro 3, 34 - 40t gross weight / 27t payload capacity/ 40 L for 100 km. (if 100 % utilization). |
| Truck capacity utilization                                                  | 50 % of the weight capacity                                                                                   |

**Module D** includes reuse, recovery and/or recycling potentials. According to EN 15804:2012+A2:2019 any declared benefits and loads from net flows leaving the product system not allocated as co-products and having passed the end-of waste state shall be included in module D. Benefits considered in module D originate from packaging recycling or incineration.

## Recycled material

For year 2019, the external recycled waste as raw material is 31.6 % originating (mainly) from slags.

## Additional information:

All raw materials for the manufacturing of the declared product, the required energy, water consumption and the resulting emissions are considered into the LCA. Consecutively, the recipe components with a share even less than 1% are included. All neglected processes contribute less than 5% to the total mass or less than 5% to the total energy consumption. For information, the impact of the Rock Mineral Wool plant construction or machines, are not taken into account in the life cycle assessment. No allocation is carried out for this specific product.

Knauf Insulation adopts a “worst case” approach into its EPDs.

Conversion factor for this EPD is 0.05 for 1 kg. In principal, an insulation product should always be characterized with its thickness and an R value, only taking into account the product's weight could lead to wrong interpretation.

## Differences versus previous versions:

Due to a minor recent adjustment related to the fibers, in accordance with local UK regulations, the lambda value has changed from 0.039 to 0.040 W/mK. This change does not impact the environmental footprint of the product but is significant as it defines the functional unit of the product.

## More information:

[www.knaufinsulation.com](http://www.knaufinsulation.com)

## Name and contact information of LCA practitioner:

Yaprak Nayir

Knauf Insulation Sprl

Rue de Maestricht 95

4600 Visé

Belgium

Contact: [sustainability@knaufinsulation.com](mailto:sustainability@knaufinsulation.com)

## Content Declaration

The product does not contain substances on the "Candidate List of Substances of Very High Concern for Authorisation" under the REACH regulation (if above 0.1% of the mass).

| Product compotents            | Weight %             | Pre-consumer material, weight - % | Renewable material, weight- % |
|-------------------------------|----------------------|-----------------------------------|-------------------------------|
| Basalt                        | 55 - 60              | 0                                 | 0                             |
| Dolomite - Limestone          | 15 - 20              | 0                                 | 0                             |
| Recovered metallurgical slags | 15 -35               | 100                               | 0                             |
| Thermo set resin binder       | 2 - 5                | 0                                 | 0                             |
| Additives                     | < 1                  | 0                                 | 0                             |
| Packaging Materials           | Weight, kg/ DU or FU | Weight -% (versus the product)    |                               |
| Wooden Pallet                 | 1.15                 | 6.06                              |                               |
| Polyethylene film             | 0.03                 | 0.18                              |                               |
| TOTAL                         | 1.18                 | 6.25                              |                               |

## Declared Modules

Life cycle stages as defined in the European standard EN 15978 :2011 and the description of the system boundaries for the reference product LCA (X = included in the LCA, MND = module is not declared)

| Product stage |           |               | Construction process stage |                           | Use stage |             |        |             |               |                        |                       | End of life stage          |           |                  |          | Resource recovery stage                |
|---------------|-----------|---------------|----------------------------|---------------------------|-----------|-------------|--------|-------------|---------------|------------------------|-----------------------|----------------------------|-----------|------------------|----------|----------------------------------------|
| Raw materials | Transport | Manufacturing | Transport                  | Construction Installation | Use       | Maintenance | Repair | Replacement | Refurbishment | Operational energy use | Operational water use | De-construction demolition | Transport | Waste processing | Disposal | Reuse- Recovery- Recycling - potential |
| A1            | A2        | A3            | A4                         | A5                        | B1        | B2          | B3     | B4          | B5            | B6                     | B7                    | C1                         | C2        | C3               | C4       | D                                      |
| X             | X         | X             | X                          | X                         | X         | X           | X      | X           | X             | X                      | X                     | X                          | X         | X                | X        | X                                      |

## Environmental performance

**Potential environmental impacts:** 1m<sup>2</sup> of Rock Mineral Wool Rocksilk® Flat Roof Slab Extra with a thickness of 105 mm with R value of 2.60 m<sup>2</sup>K/W.

| ENVIRONMENTAL IMPACTS |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |           |           |          |          |          |           |          |           |           |
|-----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|-----------|----------|----------|----------|-----------|----------|-----------|-----------|
| Parameter             | Unit                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | A1-3      | A4        | A5       | B1-B7    | C1       | C2        | C3       | C4        | D**       |
| GWP-fossil            | kg CO <sub>2</sub> eq.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 2.85E+01  | 7.79E-01  | 6.53E-01 | 0.00E+00 | 0.00E+00 | 6.72E-02  | 0.00E+00 | 2.87E-01  | -5.05E-01 |
| GWP-biogenic          | kg CO <sub>2</sub> eq.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | -1.57E+00 | -1.30E-03 | 1.23E+00 | 0.00E+00 | 0.00E+00 | -1.14E-04 | 0.00E+00 | -2.27E-02 | -1.15E-03 |
| GWP-luluc             | kg CO <sub>2</sub> eq.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 2.26E-02  | 6.27E-03  | 4.52E-04 | 0.00E+00 | 0.00E+00 | 5.49E-04  | 0.00E+00 | 8.25E-04  | -3.07E-04 |
| GWP-total             | kg CO <sub>2</sub> eq.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 2.69E+01  | 7.84E-01  | 1.88E+00 | 0.00E+00 | 0.00E+00 | 6.77E-02  | 0.00E+00 | 2.65E-01  | -5.06E-01 |
| ODP                   | kg CFC 11 eq.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | 9.65E-14  | 1.42E-16  | 4.43E-11 | 0.00E+00 | 0.00E+00 | 1.25E-17  | 0.00E+00 | 1.06E-15  | -6.91E-13 |
| AP                    | mol H <sup>+</sup> eq.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 1.86E-01  | 1.91E-03  | 3.92E-03 | 0.00E+00 | 0.00E+00 | 4.13E-04  | 0.00E+00 | 2.06E-03  | -8.26E-04 |
| EP-freshwater         | kg PO <sub>4</sub> <sup>3-</sup> eq.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | 3.89E-05  | 2.36E-06  | 7.99E-07 | 0.00E+00 | 0.00E+00 | 2.07E-07  | 0.00E+00 | 4.92E-07  | -2.81E-06 |
| EP-freshwater [1]     | kg P eq.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 1.19E-04  | 7.23E-06  | 2.45E-06 | 0.00E+00 | 0.00E+00 | 6.34E-07  | 0.00E+00 | 1.51E-06  | -8.61E-06 |
| EP-marine             | kg N eq.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 1.59E-02  | 8.08E-04  | 3.72E-04 | 0.00E+00 | 0.00E+00 | 2.00E-04  | 0.00E+00 | 5.29E-04  | -2.41E-04 |
| EP-terrestrial        | mol N eq.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 5.77E-01  | 9.10E-03  | 1.24E-02 | 0.00E+00 | 0.00E+00 | 2.21E-03  | 0.00E+00 | 5.82E-03  | -2.60E-03 |
| POCP                  | kg NMVOC eq.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 4.15E-02  | 2.26E-03  | 9.83E-04 | 0.00E+00 | 0.00E+00 | 5.48E-04  | 0.00E+00 | 1.60E-03  | -6.96E-04 |
| ADP-minerals&metals*  | kg Sb eq.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 2.29E-06  | 6.26E-08  | 4.54E-08 | 0.00E+00 | 0.00E+00 | 5.49E-09  | 0.00E+00 | 2.57E-08  | -7.44E-08 |
| ADP-fossil*           | MJ                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | 3.63E+02  | 1.03E+01  | 7.40E+00 | 0.00E+00 | 0.00E+00 | 9.05E-01  | 0.00E+00 | 3.76E+00  | -8.68E+00 |
| WDP                   | m <sup>3</sup>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | 1.66E+00  | 7.55E-03  | 1.67E-01 | 0.00E+00 | 0.00E+00 | 6.62E-04  | 0.00E+00 | 3.00E-02  | -4.47E-02 |
| Acronyms              | GWP-fossil = Global Warming Potential fossil fuels; GWP-biogenic = Global Warming Potential biogenic; GWP-luluc = Global Warming Potential land use and land use change; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential, Accumulated Exceedance; EP-freshwater = Eutrophication potential, fraction of nutrients reaching freshwater end compartment; EP-marine = Eutrophication potential, fraction of nutrients reaching marine end compartment; EP-terrestrial = Eutrophication potential, Accumulated Exceedance; POCP = Formation potential of tropospheric ozone; ADP-minerals&metals = Abiotic depletion potential for non-fossil resources; ADP-fossil = Abiotic depletion for fossil resources potential; WDP = Water (user) deprivation potential, deprivation-weighted water consumption |           |           |          |          |          |           |          |           |           |

**\*\*:** [Life Cycle D stage covers benefits and loads beyond the system boundary stage (reuse, recovery and recycling potential) therefore, when summing up results, this stage should be considered separately].

**\* Disclaimer:** The results of this environmental impact indicator shall be used with care as the uncertainties of these results are high or as there is limited experience with the indicator.

[1] EN 15804:2012+A2:2019 specifies that the unit for the indicator for Eutrophication aquatic freshwater shall be kg PO<sub>4</sub> eq, although the reference given ("EUTREND model, Struijs et al., 2009b, as implemented in ReCiPe") uses the unit kg P eq, until this has been corrected, results shall be given in both kg PO<sub>4</sub> eq and kg P eq. in the EPD.

## Potential environmental impact – additional mandatory and voluntary indicators

| Indicator  | Unit                   | Tot.A1-A3 | A4       | A5       | B1-B7    | C1       | C2       | C3       | C4       | D         |
|------------|------------------------|-----------|----------|----------|----------|----------|----------|----------|----------|-----------|
| GWP-GHG[2] | kg CO <sub>2</sub> eq. | 2.83E+01  | 7.71E-01 | 6.48E-01 | 0.00E+00 | 0.00E+00 | 6.66E-02 | 0.00E+00 | 2.83E-01 | -4.99E-01 |

[2] The indicator includes all greenhouse gases included in GWP-total but excludes biogenic carbon dioxide uptake and emissions and biogenic carbon stored in the product. This indicator is thus equal to the GWP indicator originally defined in EN 15804:2012+A1:2013.

Additional environmental impact indicators like PM [Disease incidences], IR [kBq U235 eq.], ETF-fw [CTUe], HTP-c [CTUh], HTP-nc [CTUh] and SQP [Pt] are not declared (ND) but were calculated and can be provided on request.

**Use of resources:** 1m<sup>2</sup> of Rock Mineral Wool Rocksilk® Flat Roof Slab Extra with a thickness of 105 mm with R value of 2.69 m<sup>2</sup>K/W.

| RESOURCES USE |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |          |          |          |          |          |          |          |          |           |
|---------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|----------|----------|----------|----------|----------|----------|----------|-----------|
| Parameter     | Unit                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | A1-3     | A4       | A5       | B1-B7    | C1       | C2       | C3       | C4       | D*        |
| PERE [MJ]     | MJ                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | 3.70E+01 | 5.97E-01 | 6.55E-01 | 0.00E+00 | 0.00E+00 | 5.23E-02 | 0.00E+00 | 4.92E-01 | -5.79E+00 |
| PERM [MJ]     | MJ                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | 1.72E+01 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00  |
| PERT [MJ]     | MJ                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | 5.42E+01 | 5.97E-01 | 6.55E-01 | 0.00E+00 | 0.00E+00 | 5.23E-02 | 0.00E+00 | 4.92E-01 | -5.79E+00 |
| PENRE [MJ]    | MJ                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | 3.48E+02 | 1.04E+01 | 7.14E+00 | 0.00E+00 | 0.00E+00 | 9.09E-01 | 0.00E+00 | 3.76E+00 | -8.68E+00 |
| PENRM [MJ]    | MJ                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | 1.45E+01 | 0.00E+00 | 2.61E-01 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00  |
| PENRT [MJ]    | MJ                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | 3.63E+02 | 1.04E+01 | 7.40E+00 | 0.00E+00 | 0.00E+00 | 9.09E-01 | 0.00E+00 | 3.76E+00 | -8.68E+00 |
| SM            | kg                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | 5.85E+00 | 0.00E+00 | 1.17E-01 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00  |
| RSF           | MJ                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00  |
| NRSF          | MJ                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00  |
| FW            | m <sup>3</sup>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 8.31E-02 | 6.96E-04 | 4.78E-03 | 0.00E+00 | 0.00E+00 | 6.10E-05 | 0.00E+00 | 9.48E-04 | -1.89E-03 |
| Acronyms      | PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRT = Total use of non-renewable primary energy re-sources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Use of net fresh water |          |          |          |          |          |          |          |          |           |

\*: [Life Cycle D stage covers benefits and loads beyond the system boundary stage (reuse, recovery and recycling potential) therefore, when summing up results, this stage should be considered separately].

**Waste production and output flows:** 1m<sup>2</sup> of Rock Mineral Wool Rocksilk® Flat Roof Slab Extra with a thickness of 105 mm with R value of 2.69 m<sup>2</sup>K/W.

| OUTPUT FLOWS AND WASTE CATEGORIES |      |          |          |          |          |          |          |          |          |           |
|-----------------------------------|------|----------|----------|----------|----------|----------|----------|----------|----------|-----------|
| Parameter                         | Unit | A1-3     | A4       | A5       | B1-B7    | C1       | C2       | C3       | C4       | D*        |
| Hazardous waste disposed          | kg   | 7.04E-07 | 4.80E-07 | 1.41E-08 | 0.00E+00 | 0.00E+00 | 4.20E-08 | 0.00E+00 | 5.74E-08 | -3.31E-09 |
| Non-hazardous waste disposed      | kg   | 2.38E+00 | 1.64E-03 | 4.35E-01 | 0.00E+00 | 0.00E+00 | 1.44E-04 | 0.00E+00 | 1.89E+01 | -3.54E-03 |
| Radioactive waste disposed        | kg   | 9.12E-03 | 1.91E-05 | 1.79E-04 | 0.00E+00 | 0.00E+00 | 1.68E-06 | 0.00E+00 | 4.27E-05 | -5.35E-04 |
| Components for re-use             | kg   | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00  |
| Material for recycling            | kg   | 0.00E+00 | 0.00E+00 | 4.72E-01 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00  |
| Materials for energy recovery     | kg   | 0.00E+00 | 0.00E+00 | 7.08E-01 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00  |
| Exported energy, electricity      | MJ   | 0.00E+00 | 0.00E+00 | 1.91E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00  |
| Exported energy, thermal          | MJ   | 0.00E+00 | 0.00E+00 | 3.59E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00  |

\*: [Life Cycle D stage covers benefits and loads beyond the system boundary stage (reuse, recovery and recycling potential) therefore, when summing up results, this stage should be considered separately].

#### [Information on biogenic carbon content](#)

| Results per functional or declared unit |      |          |
|-----------------------------------------|------|----------|
| BIOGENIC CARBON CONTENT                 | Unit | QUANTITY |
| Biogenic carbon content in product      | kg C | 0.00E+00 |
| Biogenic carbon content in packaging    | kg C | 5.73E-01 |

Note: 1 kg biogenic carbon is equivalent to 44/12 kg CO<sub>2</sub>.

## LCA interpretation

### ENVIRONMENTAL IMPACTS

All impact categories, except the Abiotic Depletion Potential Element and the Ozone Depletion Potential, are dominated by the manufacturing processes. This can be explained by the huge impact of the energy use (electricity, natural gas and coke) for Rock Mineral Wool production.

**The Global Warming Potential (GWP)** is dominated by the manufacturing in the cupola, mostly due to CO<sub>2</sub> emissions from raw materials and energy consumption (50%). The production of the binder represents about 15% of the impact.

**The Ozone layer Depletion Potential (ODP)** results are under the high influence of the selected scenario for plastic sheets packaging incineration.


**The Acidification Potential (AP)** is also dominated by the manufacturing due to the emissions related to the processes and the energy consumption.

**The Eutrophication Potential (EP)** is significantly influenced by the manufacturing due to emissions from cupola furnace, curing oven and other unit processes.

**The Photochemical Ozone Creation Potential (POCP)** is particularly dominated by the manufacturing (emissions in the cupola furnace and other unit processes).

**The Abiotic Depletion Potential Element (ADPe)** impact mainly comes from the manufacturing of the product.

**The Abiotic Depletion Potential Fossil (ADPf)** is dominated by the use of coke as energy carrier. Next to the coke, we have also the impact of natural gas and upstream the electricity energy mix.



## RESOURCES USE

**Total Use of Non-Renewable Primary Energy Resources (PENRT)** is dominated by the manufacturing of Rock Mineral Wool products (especially due to the energy carrier, coke) and the binder.

**Total Use of Renewable Primary Energy Resources (PERT)** is dominated by the manufacturing, mostly due to electricity consumption and packaging.

**For the Use of Secondary Material (SM)**, it consists of slags.

## References

### International EPD® System

General Programme Instructions of the International EPD® System. Version 3.01.

Product category rules (PCR): PCR 2019:14. Construction products (EN 15804+A2:2019) Version 1.1.  
c-PCR-005 Thermal insulation products (EN 16783: 2017)

#### ISO 14025

DIN EN ISO 14025:2011-10: Environmental labels and declarations — Type III environmental declarations — Principles and procedures

#### EN 15804

EN 15804:2012+A2:2019: Sustainability of construction works — Environmental Product Declarations — Core rules for the product category of construction products

#### EN 16783:2017

Thermal insulation products - Product category rules (PCR) for factory made and in-situ formed products for preparing environmental product declarations

#### GaBi 10.0

GaBi 10.0: Software and database for life cycle engineering. LBP, University of Stuttgart and PE INTERNATIONAL AG, 2019.

#### EN 1602:

EN1602: 2013 Thermal insulation products for building applications – Determination of the apparent density

#### EN 12667

EN 12667: 2001 Thermal performance of building materials and products - Determination of thermal resistance by means of guarded hot plate and heat flow meter methods - Products of high and medium thermal resistance

#### EN 13162

EN 13162:2012 Thermal insulation products for buildings - Factory made mineral wool (MW) products - Specification

#### EN 13501-1

EN 13501-1: 2009 Fire classification of construction products and building elements - Part 1: Classification using test data from reaction to fire tests.

#### DIN 4102 / T17

DIN 4102 / T17: 1990 Fire behaviour of building materials and elements; determination of melting point of mineral fibre insulating materials; concepts, requirements and testing.

#### EN 12086

EN 12086: 2013 Thermal insulating products for building applications –determination of water vapour transmission properties.

**EN 15978: 2011**

EN 15978: 2011 Sustainability of construction works - Assessment of environmental performance of buildings - Calculation method.

**ISO 8301:1991**

Thermal insulation — Determination of steady-state thermal resistance and related properties — Heat flow meter apparatus.

**ISO 21930:2017**

Sustainability in buildings and civil engineering works — Core rules for environmental product declarations of construction products and services

**DoP R4208HPCPR, RU4208HPCPR**

Declaration of Performance

**DIN 4102-17**

Fire behaviour of building materials and building components - Part 17: Melting point of mineral wool insulating materials - Terms and definitions, requirements and test

## Contact information:

|                            |                                                                                                                                                                                                                                                                                                                                                                                                                            |
|----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <p>EPD owner:</p>          | <br>Knauf Insulation<br>Rue de Maestricht 95<br>4600 Visé<br>Belgium<br><a href="http://www.knaufinsulation.com">www.knaufinsulation.com</a><br>Contact: <a href="mailto:sustainability@knaufinsulation.com">sustainability@knaufinsulation.com</a>                                                                                       |
| <p>LCA support:</p>        | <br>Université de Liège – Laboratory of Chemical Engineering<br>PEPs - Products, Environment and Processes<br>Allée du 6 août 15, Bat B6<br>4000 Liège<br>Belgium<br><br><br>Sphera<br>Hauptstraße 111-113<br>70771 Leinfelden-Echterdingen<br>Germany |
| <p>Programme operator:</p> | <br>EPD International AB<br><a href="mailto:info@environdec.com">info@environdec.com</a>                                                                                                                                                                                                                                                |