

KNAUF INSULATION



Made with a plant-based binder, that's better for you and the environment.



DriTherm® Technology enhances durability and moisture resistance.

Declare.



Knauf Insulation glasswool contains no harmful ingredients which pose serious health risks.



New brand Same superior qualities


The new Knauf Insulation range of products **has all the same features and benefits** as the **ecoinsulation** glasswool range you are familiar with.



Made using up to 80% recycled glass



Non-combustible, it will not catch fire



Compression packed, meaning more product per pack



Will help reduce energy bills



Designed to meet H1 energy efficient standards in NZ



CEILING



R-Value (m²K/W)	Code	Thickness (mm)	Width (mm)	Length (mm)	Pieces per pack	Area per pack (m²)
R3.4*	INKISR860146	110	580	1160	7	4.7
R3.6	INKICE860144	170	430	1160	18	9.0
R4.2	INKICE860138	210	430	1160	14	7.0
R5.2	INKICE860132	230	430	1160	11	5.5
R7.0	INKICE860128	330	460	1160	8	4.3

*Designed for use at the perimeter of ceilings where space is limited.



SKILLION ROOF



R-Value (m²K/W)	Code	Thickness (mm)	Rafter depth (mm)	Width (mm)	Length (mm)	Pieces per pack	Area per pack (m²)
R1.3	INKIWA860164	45	*	450	1160	24	12.5
R3.4	INKISR860146	110	140	580	1160	7	4.7
R5.0	INKISR860134	165	190	430	1160	6	3.0
R6.0	INKISR860130	215	240	430	1160	6	3.0
R7.4	INKISR860126	265	290	430	1160	6	3.0

*Designed for use as a secondary insulating layer installed between battens beneath rafters.



EXTERNAL WALL



R-Value (m²K/W)	Code	Thickness (mm)	Width (mm)	Length (mm)	Pieces per pack	Area per pack (m²)
R1.3*	INKIWA860164	45	450	1160	24	12.5
R2.2	INKIWA860162	90	580	1160	29	19.5
R2.4	INKIWA860160	90	580	1160	20	13.5
R2.6	INKIWA860158	90	430	1160	12	6.0
R2.6	INKIWA860156	90	580	1160	12	8.1
R2.8	INKIWA860152	90	430	1160	10	5.0
R2.8	INKIWA860150	90	580	1160	10	6.7
R3.2	INKIWA860148	140	580	1160	22	14.8
R4.1	INKIWA860140	140	580	1160	9	6.1
R4.4	INKIWA860136	140	580	1160	6	4.0

*Designed for use as a secondary insulating layer installed between battens to the inside of studwork.



CodeMark
CMNZ30095

CARTERS Your Building Partner

KINZ10241494BR^(10.9)

find out more at
www.knauf.com

