

Aquapanel® Joint Filler - Grey

Technical Data Sheet 12/2023



Aquapanel® Joint Filler - Grey

Cement-bound joint filler

Product Description

AQUAPANEL® Joint Filler – grey is a cement-bound filling material for full surface skim coating of joints by hand.

Storage

Bags should be kept in a dry environment on pallets and contact with water should be avoided. It is proposed to keep the bags horizontally on a flat surface during transportation and stocking. Pallets should not be exposed to direct sunlight.

Standards referred to

-

Fields of Application

- Joint Filler for use with AQUAPANEL® Cement Board Indoor (ceiling) and AQUAPANEL® Cement Board Outdoor (wall and ceiling).

General Data

Description	Weight (kg/m)	Packaging (pcs)	Shelf Life	Material Number
Aquapanel® Joint Filler - Grey	20	1	12 month	131094

Technical Data

Description	
Reaction to fire	A1
Water absorption	W2
Water vapour diffusion coefficient (μ) (EN 1745)	5 (wet cup) 20 (dry cup)
Thermal conductivity λ10 dry,mat (EN 1745)	≤ 0.45 W/(mK), P=50% ≤ 0.49 W/(mK), P=90%
Working time	45 min.
Working temperature	≥ +5°C
Water mixing ratio	6,8 l/bag (0,34 l water/kg Aquapanel® Joint Filler- Grey)

Material Consumption

Product	Unit	Consumption kg/m ²
Aquapanel® Joint Filler - Grey (for joints)	kg	0,7

System Performance Values

Performance values as sound insulation, fire resistance etc. may differ acc. to the drywall system to be applied. Please check the performance values of the drywall systems;

[Knauf Technical Website](#)
[Document Center](#)

Application

Application should be done acc. to the applicable standards (TS 1475) and acc. to the Knauf Technical Brochures of the respective drywall system.

▶ 444 YAPI - 9274

▶ www.knauf.com.tr / www.teknik.knauf.com.tr

▶ teknik@knauf.com

Center: Knauf Moment Beştepe Office, Beştepe Mah. 32.Cadde No:1/212-218 06560 Beştepe-Yenimahalle
/ ANKARA Tel: 0312 297 0100 Faks: 0312 266 4506