

KSK runner



KSK reinforcement runners for partitions with KR studs

Page: 1/1

03/2017

PRODUCT DATA			
CHARACTERISTIC		VALUE	UNIT
Fire	Reaction to fire	A1	Incombustible
Strength	Yield point	250	N/mm ²
Surface	Zinc	275	g/m ²
Corrosion class		C2	
Measurements	Widths ± 0,5	45/70/95/120/145	mm
	Thickness	1,0	mm
	Length	± + 0 / - 3	
	Other - see drawing	± 1	mm

Areas of use

Runner for KR studs for partitions.

For telescopic solutions for very high walls or for walls where a high degree of stability is required.

Profiles produced according to EN 14195.

Variants/sizes:

Studs KSK 45/70/95/120/145 mm

PROFILE DATA						
	t	h	A	iy	ly	Wy
Profile	mm	mm	mm ²	mm	mm ⁴	mm ³
KSK 45	1,0	45	121,9	20,3	5,01 x 10 ⁴	1,55 x 10 ³
KSK 70	1,0	70	129,5	28,2	10,30 x 10 ⁴	2,32 x 10 ³
KSK 95	1,0	95	166,0	37,7	23,61 x 10 ⁴	4,37 x 10 ³
KSK120	1,0	120	189,0	46,0	39,97 x 10 ⁴	5,95 x 10 ³
KSK145	1,0	145	212,7	54,1	62,35 x 10 ⁴	7,78 x 10 ³

Steel quality: S250GD+Z275

