



USGKnauf EasyPlus™ JOINTING COMPOUND

USGKnauf EasyPlus™ is a high performance air-drying compound used for treating Gypsum board joints and fixing points.

EasyPlus™ provides excellent tape bonding strength, is exceptionally smooth to work with and the easy mixing saves time. EasyPlus™ is relatively easy to sand, giving a high level of finish.

Product Usage Data:

Air drying compound	
Mixing Ratio	2 parts of compound to 1 part of water (in kg.)
Storage	The product must be kept in dry conditions, away from moisture. The bag should be stored at an elevated position. Part open bags should be sealed, as moisture can accelerate the setting time.

Mixing Procedure:




1. Always use clean water, tools and containers. Using dirty containers / tools may affect setting time.



2. Slowly add powder to water.


Tapered Edge Joints (3 easy steps):

1st Coat




Apply EasyPlus™ of 150 mm width for joint reinforcement.

2nd Coat




Apply an even coat of EasyPlus™ of 200 mm width.

3rd Finishing Coat




Apply an even coat of EasyPlus™ of 300 mm width for finishing.


Square Edge Joints (3 easy steps):



Apply EasyPlus™ of 300 mm width for joint reinforcement.



Apply an even coat of EasyPlus™ of 400 mm width.



Apply an even coat of EasyPlus™ of 500-600 mm width for finishing.

Note: All Gypsum board joints require light sanding before painting.

*Available in 25kg bag

Knauf India Private Limited

Head Office: 9th Floor, Plaza Tower, DLF Phase -1, Gurugram - 122002, Haryana, India

Customer Care No: +91 - 9015147147

Email: info.india@knauf.com

www.usgknauf.com