



## **Knauf** Trenn-Fix

For crack-free connection joints

# Knauf Trenn-Fix

For crack-free connection joints

**KNAUF**  
Drywall Systems

## Product description

- Knauf Trenn-Fix is a special coated adhesive.
- 50m per roll.
- Store in a dry area and keep it away from direct heat.

## Fields of Application

- For crack free separation of drywall partitions and ceilings as well as solid wall or slabs.

## Properties

- Ready made
- Easy to install
- Stiff
- Crack free joints

## Application

- Apply Knauf Trenn-Fix's self-adhesive side at the back of the Knauf CW+, CW, UW or UD profiles with the excess part of the Trenn-Fix facing the board cladding side.
- Apply Knauf Acoustical Sealant or Knauf Insulation strip if high acoustic performance is needed.
- Leave 5mm jointing gap when installing Knauf Gypsum Boards.
- Apply 2 layers of Knauf Joint Compound at the joint. Alternatively apply skim coating and wait for the surface to dry.
- Trim the excess Knauf Trenn-Fix once the joint compound has dried off.



Apply the Knauf Trenn-Fix on the CW+, CW, UW or UD Profile.



Apply Knauf Acoustical Sealant or Knauf Insulation strip. (optional)



Alternatively, apply the Knauf Trenn-Fix on solid components or on drywalls after fixing the perimeter frame.



Leave 5mm jointing gap to install Knauf Gypsum Boards.



Fill the joints



Trim the excess material once the joint filler dries off

Knauf LLC  
P.O. Box 112871  
Dubai  
United Arab Emirates  
Tel +971 4 - 337 7170  
Fax +971 4 - 334 9659  
E-mail [info@knauf.ae](mailto:info@knauf.ae)  
Internet <http://www.knauf.ae>