

Note on English translation / Hinweise zur englischen Fassung

This is a translation of the product data sheet valid in Germany.

All stated details and properties are in compliance with the regulations of the German standards and building regulations. They are only applicable for the specified products, system components, application rules, and construction details in connection with the specifications of the respective certificates and approvals.

Knauf Gips KG denies any liability for applications outside of Germany as this requires changes acc. to the respective national standards and building regulations.




Drywall Systems

K533.de

Product Data Sheet

2020-05



Cleaneo Caps

Fastening for Cleaneo linear

Product description

Cleaneo Caps consist of coated, corrosion-protected mounting sleeves made of metal or plastic and the enclosed metal screws with a black or white screw head.

Storage

Store in a dry place.

Quality

In compliance with EN 13964, the product is subject to initial type testing and continuous factory production control and bears the CE marking.

Properties and added value

- Optically matched to the perforation design
- Concealed installation
- Filling the screws heads is no longer required
- Ball impact safe
- Same screw spacings as with normal screw fastening

Field of application

Cleaneo Caps are a quick and uncomplicated solution for fastening of Cleaneo linear or Cleaneo Complete boards to the grid.

The Cleaneo Caps are optimally adapted to the corresponding perforation diameters and for 12.5 mm thick Cleaneo linear boards or Cleaneo Complete boards with black acoustical fleece (black screw) or white acoustical fleece (white screw) on the rear and available for standard circular perforation 8/18 R, 10/23 R and 12/25 R and the square perforation 12/25 Q perforations.

Thus, they are perfectly integrated into the visual appearance of the board perforations and eliminate the need to fill the screw heads with filler. The screws are almost undetectable on the ceiling.

Application

For perforated boards with black acoustical fleece on the rear, use the enclosed metal screw with a black screw head.

For perforated boards with white acoustical fleece on the rear, use the enclosed metal screw with a white screw head.

Notes	For use at normal room climates, where the relative air humidity of the room may only briefly exceed a level of 65 %. Observe Code of Practice no. 1 "Baustellenbedingungen - Site conditions" of the BVG (IGG) for installation. The relative humidity should be at least 40 %.
	Cleaneo Caps can be used for ball impact safe ceiling systems, but are not rated for dynamic loads, e.g. alternating loads due to wind.

Installation

Installation using Cleaneo Caps is simple, fast and absolutely safe. The number of anchoring points remains identical to conventional installation with at least 23 points per m².

Only use profiles from Knauf or the Knauf Group for the installation of Cleaneo boards.

Detailed information for installation can be found in the Installation Instructions [Cleaneo linear K761L-A01.de](#).

Product range

Description	Application	Packaging unit	Material number	EAN
Cleaneo-Caps R	8 R ¹⁾ with black screw	500 pieces / pack	00248099	4003982243034
	10 R with black screw	180 packages / pallet	00248102	4003982243041
	12 R with black screw		00248103	4003982243058
	8 R ¹⁾ with white screw	00582030	4003982416148	
	10 R with white screw	00582031	4003982416155	
	12 R with white screw	00582032	4003982416162	
Cleaneo-Caps Q	12 Q ¹⁾ with black screw	500 pieces / pack	00525502	4003982342713
	12 Q ¹⁾ with white screw	200 packages / pallet	00582033	4003982416179

1) Apply Cleaneo-Caps on the front edges with double CD 60/27 (see Installation Instructions [Cleaneo linear K761L-A01.de](#)).



Observe safety data sheet!

For safety data sheet see

pd.knauf.de



Videos for Knauf systems and products can be found under the following link:

[youtube.com/knauf](https://www.youtube.com/knauf)



The iPad App Knauf Infothek now provides all the current information and documents from Knauf Gips KG at any time and in every location in a clear and comfortable way.

knauf.de/infothek

Knauf Direct

Technical Advisory Service:

▶ knauf-direkt@knauf.de

▶ www.knauf.de

Knauf Gips KG Am Bahnhof 7, 97346 Iphofen, Germany

All technical changes reserved. Only the current printed instructions are valid. The stated information represents current state-of-the-art Knauf technology. The entire state of approved engineering rules, appropriate standards, guidelines, and rules of craftsmanship are not included herewith. These and all application instructions have to be adhered to separately by the installer. Our warranty is expressly limited to our products in flawless condition. All application quantities and delivery amounts are based on empirical data that are not easily transferable to other deviating areas.

All rights reserved. All amendments, reprints and photocopies, including those of excerpts, require our expressed permission.