

# KNAUF

## Knauf Self Tapping Drywall Screws

Knauf Self Tapping Drywall Screws are fine thread self tapping plasterboard screws, made from carbon steel with black phosphate coating.

*Product-Data-Sheet*

**Build on us.**



### Areas of Application

Fixing plasterboard to metal frames up to a gauge of 1.2mm.

### Compliance Standards

EN 14566: 2009 & A1 2009

### Key Benefits

- Black phosphate coated
- Thread insures clean, smooth, low torque instillation
- PH2 head
- Carbon steel
- Bugle head for flush counter sink application

Creation Date: 08/06/2023  
Revision Reference: 002  
Revision Date: 15/07/2024

## Product Information

### Performance Data

Reaction to Fire (R2F)	Steel Thickness (mm)	Nominal Diameter (mm)	Ultimate Pull Out Values (kN)	Ultimate Tensile Strength (kN)	Ultimate Shear Strength (kN)	Recommended drill speed (RPM)
A1	0.6	3.5	0.7	5.6	4.3	4000 - 6000
A1	0.6	3.9	0.8	7.8	6.2	4000 - 6000
A1	0.6	4.2	0.8	8.4	7.0	4000 - 6000

### Technical Information

Length (mm)	Nominal Diameter (mm)	Type	Coating Type	Material Grade	Material Grade	Material Number
25	3.5	Loose	Black Phosphate	ASIS C1022 carbon steel	ASIS C1022 carbon steel	258309
32	3.5	Loose	Black Phosphate	ASIS C1022 carbon steel	ASIS C1022 carbon steel	258310
38	3.5	Loose	Black Phosphate	ASIS C1022 carbon steel	ASIS C1022 carbon steel	258311
42	3.5	Loose	Black Phosphate	ASIS C1022 carbon steel	ASIS C1022 carbon steel	258312
50	3.9	Loose	Black Phosphate	ASIS C1022 carbon steel	ASIS C1022 carbon steel	358313
60	4.2	Loose	Black Phosphate	ASIS C1022 carbon steel	ASIS C1022 carbon steel	258314
75	4.2	Loose	Black Phosphate	ASIS C1022 carbon steel	ASIS C1022 carbon steel	258315
25	3.5	Collated	Black Phosphate	ASIS C1022 carbon steel	ASIS C1022 carbon steel	158103
35	3.5	Collated	Black Phosphate	ASIS C1022 carbon steel	ASIS C1022 carbon steel	158106
45	3.5	Collated	Black Phosphate	ASIS C1022 carbon steel	ASIS C1022 carbon steel	322296

## Additional Information

### Sustainability

#### Recyclability

The screws are fully recyclable, and the collated screw carrier can be recycled

### Storage and Handling

Store in dry conditions.

### Packaging

Cardboard box in outer cardboard carton.

### Disposal/Repair

Disposal should be in accordance with local authority requirements.

### Application / Installation

Designed for fixing plasterboard to metal substrates in Knauf partition systems.

Do not use impact guns, over torquing will break or damage screw, heads and threads.

### Additional Documentation

Declaration of Performance UKCA

Declaration of Performance CE

Product Accreditations:



Knauf UK GmbH Company Accreditations:



The information given in this publication is believed to be current and accurate as at the date of publication, but no warranty, express or implied is given. Updates will not be automatically issued © Copyright Knauf 2024

#### Customer Service

UK Tel: 0800 521 050  
Eire Tel: 01 4620739  
Email: [cservice@knauf.com](mailto:cservice@knauf.com)

#### Technical Service

Tel: 0800 521050 (option 2)  
Email: [technical-uk@knauf.com](mailto:technical-uk@knauf.com)  
(excluding public holidays)

#### UK Address

Knauf  
Kemsley Fields Business Park  
Sittingbourne  
Kent ME9 8SR

#### Ireland Address

Knauf  
87 Broomhill Road  
Tallaght  
Dublin 24  
D24 WR85

Creation Date: 08/06/2023  
Revision Reference: 002  
Revision Date: 15/07/2024