





ADAGIO Alpha⁺ Mineralni plafoni



Build on us.

- ADAGIO Alpha⁺ nudi glatku, ujednačenu i izdržljivu površinu s prvoklasnom otpornošću na ogrebotine i najsvjetlijim belim izgledom bez premca. Ploče takođe pružaju ravnotežu apsorpcije i prigušenja zvuka, kao i visoku refleksiju svetlosti.
- Izvrsna apsorpcija zvuka: 1,00 α_w .
- Izvrsna vrednost refleksije svetlosti: 88%.
- ISO 4, Zlatni sertifikat za kvalitet vazduha u zatvorenom prostoru i bronzani sertifikat Cradle to Cradle®.
- Idealno za otvorene prostore (pozivni centri, biblioteke, kancelarije otvorenog prostora, kafeterije, itd.)



Karakteristike		Detaljne informacije							
Detalji ivica		Board 	Tegular 24/90 			Tegular 15/90 			
Debljina (mm)		20	20			20			
Dimenzije (mm)		600 x 600 625 x 625 675 x 675 1200 x 300 1200 x 600 1250 x 625 1500 x 600 1800 x 600	600 x 600 625 x 625 675 x 675 1200 x 300 1200 x 600 1250 x 625 1500 x 600 1800 x 600			600 x 600 625 x 625 675 x 675 1200 x 300 1200 x 600 1250 x 625 1500 x 600 1800 x 600			
Sistem		Vidljiva konstrukcija, demontažne ploče - sistem C					Vidljiva konstrukcija, demontažne ploče - sistem C Vidljiva konstrukcija - paralelni Bandraster profili, demontažne ploče - sistem I.3 Vidljiva konstrukcija - Koridor elementi, demontažne ploče - sistem F.3		
Težina		3.4 kg / m²							
Boja		 Bela							
Apsorpcija zvuka		EN ISO 354 α_w = 1.00 prema EN ISO 11654 - Klasa A							
		Frekvencija f (Hz)	125	250	500	1000	2000	4000	
		α _p	0.55	0.80	1.00	0.95	1.00	1.00	
		NRC = 0.95 prema ASTM C 423							
Uzdužna zvučna izolacija		EN ISO 10848-2 D _{n,f,w} = 25 dB prema EN ISO 717-1 CAC = 26 dB prema ASTM E 413-10							
Zvučna izolacija		EN ISO 10140-2 R _w = 12 dB prema EN ISO 717-1							
Reakcija na požar		Euroclass A2-s1, d0 prema EN 13501-1							
Refleksija svetlosti		88%							
Toplotna provodljivost		λ = 0.040 W/mk prema EN 12667							
Propusnost vazduha		PM3 (≤ 100 m³/hm²) prema DIN 18177							
Otpornost na vlagu		95% RH							
Klasa čistoće prostora		ISO 4 prema EN ISO 14644-1							
Kvalitet vazduha		 A+	 E1	 IACG					
Čišćenje									
Održavanje		 59.6% (2024)	 EC 1272/2008 Annex Q	 M1	 cradle to cradle BRONZE		www.blauer-engel.de/uz132		