



## Knauf FR Sealant



Knauf FR Sealant is a grey-colored, acrylic based sealant which improves fire insulation and acoustical performance when applied in fire-resistant drywall partitions as per Knauf's recommendation. It can be used as a general purpose sealant for compatible joints involving gypsum board, metal, concrete, cement, wood and plastics.

The most common application is for sealing the surface under Knauf UW tracks, and the gap between edges of boards and structural elements in perimeters of all types of fire-resistant drywall partitions.

\* Fire Resistant only as a part of tested Knauf FR Drywall Systems

# Knauf FR Sealant

## Product Description

Knauf FR Sealant is a grey-colored, acrylic based sealant which improves fire insulation and acoustical performance when applied in fire-resistant drywall partitions as per Knauf's recommendation. It can be used as a general purpose sealant for compatible joints involving gypsum board, metal, concrete, cement, wood and plastics.

The most common application is for sealing the surface under Knauf UW tracks, and the gap between edges of boards and structural elements in perimeters of all types of fire-resistant drywall partitions."

## Precautions

Uncured sealant may irritate eyes and skin. In case of such contact, rinse immediately using plenty of water and seek medical advice.

Use only in a well ventilated place. Do not ingest.

Keep out of the reach of children.

## Application Instructions

Application surfaces should be clean, dry and free from all contaminants like dust, rust, grease etc. Cut the nozzle at angle and apply the sealant with a hand or air operated cartridge gun tool immediately to spread the sealant over the surface and give a smooth finish. Please refer to the data sheet for further details.

### SHELF LIFE

12 months from manufacturing date when stored in temperature range of 5°C to 25°C.

**Approx. 280 ml**

**Material code : 624402**

Please contact our sales department for inquiries about storage and packing.

### Note:

-----  
-----  
-----  
-----

### Knauf Head Office

- ▶ Phone: +971 4 337 7170
- ▶ Fax: +971 4 334 9659
- ▶ P.O.Box: 112871, Dubai
- ▶ info.uae@knauf.com

### Knauf Manufacturing Plant

P.O.Box 50006  
Ras Al Khaimah, U.A.E.  
Tel: +971 7 268 9837  
Fax: +971 7 221 5301



#### Disclaimer:

The information provided in this leaflet is only intended to give guidance in selecting and using Knauf products. While we make every effort to ensure its accuracy, neither Knauf LLC and its branches nor any of its employees or affiliates warrant or assume any legal liability or responsibility for the completeness or usefulness of any failure in installation or constructing any structure installation or building or caused by using this leaflet. Readers are advised to independently verify this information prior to rely on it. In particular, readers must obtain appropriate independent advice on the use in specific structures, installations or buildings to ensure compliance with all regulations, including health and safety regulations. Knauf reserves the right to amend technical specification.

The constructional and structural properties, and characteristic building physics Knauf system can solely be ensured with the exclusive use Knauf system components, or other product expressly recommended by Knauf.