

Screw-Self Tapping SU

Technical Data Sheet 12/2023



Screw-Self Tapping SU

Screw

Product Description

Self tapping screws with countersunk cross-heads for fixing plasterboard to metal substructure up to 0.7 mm thick.

Storage

- Direct contact with water should be avoided.
- Packages should be stored in flat, dry and clean areas.

Standards referred to

EN 14566

Fields of Application

- Gypsum Board Partition Wall Systems
- Gypsum Board Suspended Ceiling Systems
- Gypsum Board Wall Cladding Systems

Properties

- Clean and easy installation.

Technical Data

Description	Diameter (mm)	Length (mm)	Weight (kg/box)	Packaging Unit (pcs./box)	Material Number
Screw-Self Tapping SU	3,5	25	1,35 / 22	1000 / 16000	141254 / 51290
		35	1,8 / 16	1000 / 9000	141255 / 51291
		45	2,1	1000	51292
		55	2,65		5397

System Performance Values

Performance values as sound insulation, fire resistance etc. may differ acc. to the drywall system to be applied. Please check the performance values of the drywall systems;

[Knauf Technical Website](#)
[Document Center](#)

Application

Application should be done acc. to the applicable standards (TS 1475) and acc. to the Knauf Technical Brochures of the respective drywall system.

▶ 444 YAPI - 9274

▶ www.knauf.com.tr / www.teknik.knauf.com.tr

▶ teknik@knauf.com

Center: Knauf Moment Beştepe Office, Beştepe Mah. 32.Cadde No:1/212-218 06560 Beştepe-Yenimahalle / ANKARA Tel: 0312 297 0100 Faks: 0312 266 4506