



DECLARATION OF PERFORMANCE

No. KAQ_0411

1. Unique identification code of the product-type: **AQUAPANEL® Joint Filler & Skim Coating - white**
JFSCW_131095_012
2. Intended use/es: **Skim coating on AQUAPANEL® Cement Board for indoor and outdoor application**
3. Manufacturer: **Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D - 58638 Iserlohn**
Tel.: +49 2374 5036-0, Fax: +49 2374 5036-300, E-Mail: aquapanel.info@knauf.com
4. Authorised representative: not applicable
5. System/s of AVCP: **System 4**
6. a) Harmonised standard: **EN 998-1:2016**
Notified body/ies: not applicable
6. b) European Assessment Document / European Technical Assessment / Technical Assessment Body /
Notified body/ies: not applicable
7. Declared performance/s: **General purpose mortar (GP) for interior and exterior use (CS IV)**

Essential characteristics	Performance	Harmonised tech. specification
Reaction to fire	A1	EN 13501-1:2010
Water absorption	W _c 2	EN 998-1:2016
Water vapour diffusion coefficient	$\mu = 5$ (wet cup); $\mu = 20$ (dry cup) table value EN 1745	
Adhesion	$\geq 0,08$ N/mm ² , FP: B	
Thermal conductivity ($\lambda_{10, dry}$)	$\leq 0,45$ W/mK for P = 50%; $\leq 0,49$ W/mK for P = 90% (Table value EN 1745, dry density ≤ 1400 kg/m ³)	
Durability	NPD / No requirements	
Dangerous Substances	NPD / No requirements	

8. Appropriate Technical Documentation and/or Specific Technical Documentation: not applicable

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Dr. Thomas Koslowski, General Manager

Iserlohn, 10.12.2018