



## AQUAPANEL® Basecoat Primer

Synthetic dispersion with high alkali resistance

**Be certain,  
choose AQUAPANEL®**

**AQUAPANEL®**



## Description

AQUAPANEL® Basecoat Primer is used as a primer on AQUAPANEL® Exterior Basecoat and AQUAPANEL® Exterior Basecoat - white where AQUAPANEL® render finishes, e.g. AQUAPANEL® Exterior Silicon Synthetic Resin Plaster – white, AQUAPANEL® Exterior Dispersion Plaster – white or AQUAPANEL® Exterior Mineral Finish white are used on AQUAPANEL® Cement Board Outdoor. It reduces suction variations.

## Properties

- High resistance to alkalis
- Dries to white

## Preparation of the substrate

The background must be rigid, dry, clean and free of loose parts and peeling residues. The background and air temperature must not be below +5°C during use.

## Processing

AQUAPANEL® Basecoat Primer is applied undiluted across the entire surface with a lamb's wool roller or brush. Stir bucket contents occasionally. Leave at least 24 hours between priming and finishing plaster. The primer must be completely dry.

Clean tools and equipment with water immediately after use.

## Material coverage

Approx. 100 –150 g/m<sup>2</sup>

## Working time

Approx. 1 minute/m<sup>2</sup>

## Working temperature/climate

The background and air temperature must not be below +5° during use.

## Method of delivery/storage

- 15 kg/pail
- Can be stored for approx. 18 months in a frost-free area

Item code: 49299

**AQUAPANEL®**

▶ [www.AQUAPANEL.com](http://www.AQUAPANEL.com)

@ [aquapanel.info@knauf.com](mailto:aquapanel.info@knauf.com)

AQUAPANEL® is a technologically advanced building system. Because it's a system, it involves clear step-by-step process from design idea to project completion. AQUAPANEL® cement board panels, accessories and services work in unison – you can be certain that your project will all come together as planned.

AQUAPANEL® is a registered trademark.

Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, 58638 Iserlohn, Germany