



# SELECT XL32

## 15mm Exposed Tee System

### BENEFITS

- Hot dipped galvanized coating inhibits red rusting better than electrogalvanized, painted or plated systems.
- XL2 clip staked-on cross tee provides double lock with 4 times stronger than integral end detail to secure locked connection; easy to remove, reuse and relocate.
- Mitered cut at 45 degree, uniformed joints with consolidated groove on face, vivid three dimensional effect, novelty and fashion design.
- Choice of black and white reveal.

### Material

Hot dipped galvanized steel

### Surface Finish

Baked polyester paint

### Cross Tee/Main Beam Interface

Mitered

### End Detail

Main beam: Coupling

Cross Tee: Staked-on XL2 clip

### Profile

Exposed tee system

### Classification

Light duty LD

# SELECT XL32

## 15mm Exposed Tee System

Select XL32							
	Item Number	Description	Dimensions				
			Reveal Colour	Rout Spacing	Length	Height	Width
	BP6942102BI*	3000mm Main Beam	Black	600mm	3000mm	32mm	15mm
	BP6942102*	3000mm Main Beam	White	600mm	3000mm	32mm	15mm
	BP6930102BI	1200mm Cross Tee	Black	600mm	1200mm	32mm	15mm
	BP6930102	1200mm Cross Tee	White	600mm	1200mm	32mm	15mm
	BP6920102BI	600mm Cross Tee	Black	-	600mm	32mm	15mm
	BP6920102	600mm Cross Tee	White	-	600mm	32mm	15mm
Angle Molding							
	BPT1945H	3000mm Angle Molding	-	-	3000mm	19mm	19mm
	BPT2222H	3000mm Angle Molding	-	-	3000mm	22mm	22mm
	BP784203	3000mm Shadow Molding	-	-	3000mm	19 x 7 x 7 x 14mm	
	<b>Sustainability</b>		25%				

**Note:** Hanger Spacing 1200mm, \*load: 7.88kg/m LD

### Contact

For further details, please contact your local representative or email [asia.support@knaufarmstrong.com](mailto:asia.support@knaufarmstrong.com)