

## EARTHWOOL® METAL ROOFING ROLL (UNFACED)

January 2026

### Applications



Earthwool Metal Roofing Rolls are designed for quick and efficient installation in both single-skin and double-skin profiled metal roof systems, including standing seam and bracketed rail constructions. Each roll is manufactured at 1,200 mm width to suit common purlin spans and support systems. The insulation is typically laid over or between purlins, and supported by roof sheeting, metal mesh, or spacer systems depending on the roof design.



### Description

Earthwool is soft, low-dust composition—enabled by ECOSE Technology—makes it lightweight and easy to handle, improving installer comfort and productivity. TwinTech Technology delivers a smooth finish and improved handling during placement and alignment.

Once installed, Earthwool insulation contributes to excellent thermal and acoustic performance, while its non-combustible and moisture-resistant properties support long-term durability, safety, and energy efficiency under metal cladding systems.



### Knauf Insulation GMW Unfaced Performance

|  |  |                                     |      |                        |      |      |                    |      |
|--|--|-------------------------------------|------|------------------------|------|------|--------------------|------|
| Thermal (ASTM C518-21)   | MS 1020:2022                                     |                                     |      |                        |      |      |                    |      |
| Fire Hazard Properties (ASTM E84)*   | Spread of Flame: 0<br>Smoke Developed: 0-5       |                                     |      |                        |      |      |                    |      |
| <b>MATERIAL PROPERTY</b>   | <b>RESULT</b>                                    | <b>REQUIREMENT PER ASTM C665-17</b> |      |                        |      |      | <b>PASS / FAIL</b> |      |
| Water Vapor Sorption (Mass %) (ASTM C1104)*                                | 3  | ≤5                                  |      |                        |      |      | Pass               |      |
| Corrosiveness - Aluminium (rating scale 15-40) (ASTM C665)*                | 40   | >21                                 |      |                        |      |      | Pass               |      |
| Corrosiveness - Copper (rating scale 15-40) (ASTM C665)*                   | 40   | >21                                 |      |                        |      |      | Pass               |      |
| Corrosiveness - Steel (ASTM C1617)*  | ≤5 ppm   | ≤5 ppm                              |      |                        |      |      | Pass               |      |
| Fungi Resistance (ASTM C1338)*   | No growth  | Growth ≤ Comparative                |      |                        |      |      | Pass               |      |
| Non-combustibility (BS 476)  | Part 4   |                                     |      |                        |      |      | Pass               |      |
| Fire propagation (BS 476)  | Part 6   |                                     |      |                        |      |      | Pass               |      |
| Surface spread of flame (BS 476)   | Part 7   |                                     |      |                        |      |      | Pass               |      |
| Short-term water absorption by partial immersion, average (ISO 29767:2019) | 16 kg/m <sup>3</sup>                             |                                     |      | 32 kg/m <sup>3</sup>   |      |      | Pass               |      |
|  | 0.20 kg/m <sup>2</sup>                           |                                     |      | 0.15 kg/m <sup>2</sup> |      |      |                    |      |
| Noise Reduction Coefficient (NRC)  | Frequency (Hz)                                   |                                     |      |                        |      |      | NRC                |      |
|  | 125  | 250                                 | 500  | 1000                   | 2000 | 4000 |                    |      |
|  | for 16kg/m <sup>3</sup> density (50mm thickness) |                                     |      |                        |      |      |                    |      |
|  | 0.24   | 0.65                                | 0.92 | 0.94                   | 0.96 | 0.97 |                    | 0.85 |
| for 20kg/m <sup>3</sup> density (50mm thickness)                           |  |                                     |      |                        |      |      |                    |      |
| 0.24   | 0.66   | 0.94                                | 0.97 | 0.98                   | 0.97 | 0.90 |                    |      |
| for 24kg/m <sup>3</sup> density (50mm thickness)                           |  |                                     |      |                        |      |      |                    |      |
| 0.24   | 0.67   | 0.97                                | 1.00 | 0.99                   | 0.97 | 0.90 |                    |      |

\*product testing based on product density of 32kg/m<sup>3</sup>

### Certifications



Declare.



**KNAUFINSULATION**



Please scan the QR Code to view the complete list of certifications on our website.

## EARTHWOOL® METAL ROOFING ROLL (UNFACED)

January 2026

### Benefits

- ✓ High level of sound reduction
  - Effectively minimizes noise from rain and other unwanted sounds
- ✓ High thermal performance
  - Equivalent to or better than rock mineral wool with half the weight, lowering embodied carbon, environmental impact, and costs
- ✓ Material Health
  - No added formaldehyde or phenol
  - Red List Free certified, free from harmful chemicals
- ✓ TwinTech® - smooth finish on both sides
- ✓ DriTherm® Technology, silicone treated
  - Water ingress resistance
  - Humidity and water vapour protection
- ✓ Saves energy - lower energy bills
- ✓ Non-combustible
- ✓ Odourless
- ✓ Naturally brown - no artificial colours added
- ✓ Superior handling
  - Consistent quality materials, cut easily and installs fast
  - Highly resilient insulation recovers quickly to full thickness
- ✓ Compression packed - more product per pack, less storage needed, reduce carbon footprint

### Specifications

#### Knauf Insulation GMW Unfaced

| Product Code | Density (kg/m <sup>3</sup> ) | Thickness (mm) | Thermal Conductivity* <sup>①</sup> (W/mK) | R-Value <sup>①</sup> (m <sup>2</sup> K/W) | Width (mm) | Length (mm) | Area per pack (m <sup>2</sup> ) | Pieces per pack |
|--------------|------------------------------|----------------|---|---|------------|-------------|---------------------------------|-----------------|
| 868897       | 16                           | 50             | 0.0366                                    | 1.36                                      | 1,200      | 15,000      | 18.0                            | 1               |
| 868899       | 20                           | 50             | 0.0352                                    | 1.42                                      | 1,200      | 11,500      | 13.8                            | 1               |
| 868902       | 24                           | 50             | 0.0339                                    | 1.47                                      | 1,200      | 10,000      | 12.0                            | 1               |

<sup>①</sup> In accordance with Clause 4.2.1 (b) of Malaysian standard MS1020 (Thermal insulation products for buildings - factory made mineral wool products), thermal resistance and thermal conductivity values shall be expressed with three significant figures.

\* Thermal conductivity 20°C λ Value (W/mK)

## EARTHWOOL® METAL ROOFING ROLL (UNFACED)

January 2026

### Additional Information

#### Specification Guide

The insulation shall be Earthwool Metal Roofing Roll (Unfaced) \* \_\_\_\_\_ kg/m<sup>3</sup>, \* \_\_\_\_\_ mm thick, MS 1020:2022 compliant product. The product will be non-combustible, Red List Free as labelled by Declare, Global GreenTag GreenRate Level A certified, contain no ozone-depleting substances or greenhouse gases, glasswool insulation with high post-consumer recycled glass content and with ECOSE® Technology. It will be manufactured under Quality Assurance Standards ISO 9001, ISO14001, ISO45001 and ISO50001 by Knauf Insulation Sdn. Bhd. and shall be installed in accordance with the instructions issued by them.

\*architect to insert details of products used.

#### Fire Safety

Tested in accordance with BOMBA Class '0'; B.S. 476: Part 4 Non-combustibility, B.S. 476: Part 6 Fire propagation, and B.S. 476: Part 7 Surface spread of flame.

#### Bio-solubility

The formulation used for Knauf Insulation glasswool has been independently assessed and certified by EUCEB to demonstrate bio-solubility. All products manufactured by Knauf Insulation are made of non-classified fibres (fibres that are less bio-persistent than every day dust) and are certified by EUCEB. EUCEB is a voluntary initiative which provides independent certification that guarantees that products are made of fibres which comply with the exoneration criteria for carcinogenicity (Note Q) of the Regulation (EC) 1272/2008. To help user's identify the safety of our Glasswool fibres the EUCEB logo is displayed on our product packaging and/or labels.

#### Material Health

Knauf Insulation glasswool is free of hazardous ingredients and certified as Red List Free. The Living Building Challenge (LBC) Red List represents the "worst in class" materials, chemicals, and elements known to pose risks to human health. To earn the Red List Free designation, a product must fully disclose its ingredients, ensuring that none of them contain Red List chemicals. Products bearing the Red List Free label demonstrate adherence to the LBC's objectives of promoting ingredient transparency and the removal of Red List chemicals throughout the industry.

#### Environmental

Earthwool Metal Roofing Roll (Unfaced) represents no known threat to the environment and comes with GreenTag GreenRate Level A certification,

Declare label and a certified Environmental Product Declaration. Earthwool Metal Roofing Roll (Unfaced) has low VOCs and benefits from ECOSE® Technology. Eurofins Indoor Air Comfort (Gold) certification provides assurance that a product fulfills low product emissions requirements. Gold level certified products are those with the **best-in-class** low emissions, and therefore good for indoor air quality.

#### Proven Performance

- Earthwool Metal Roofing Roll (Unfaced) is preferred by professional installers concerned with quality, appearance and productivity.
- Earthwool Metal Roofing Roll (Unfaced) has excellent acoustical properties reduce sound transmission in the building when properly installed.

#### Durability

Earthwool Metal Roofing Roll (Unfaced) is odourless, rot proof, non-hygroscopic, does not sustain vermin and will not encourage the growth of fungi, mould or bacteria.

#### Superior Handling

- Highly resilient insulation recovers quickly to full thickness for a snug fit and superior finished aesthetics.
- Consistent quality materials, feel smooth, easy to cut and install.
- Low dust for easier handling and increased productivity.

#### Convenient Packaging, Easier Handling

- Earthwool Metal Roofing Roll (Unfaced) is packaged in a strong, white poly bag that offers excellent protection from abuse, dust and moisture.
- Earthwool Metal Roofing Roll (Unfaced) packages feature easy to follow installation instructions.
- MasterBag insulation units (containing multiple packs) ensure reduced handling costs with improved compression – more square metres per bag, more square metres per truck load, fewer trips to the job site and less warehouse space for storage.

#### Superior Service and Support

- Knauf Insulation is totally focused on providing first class customer service, producing high quality product and 'on time in full' deliveries.
- Knauf Insulation supports a professional network of distributors and re-sellers in order to service a growing insulation market.
- Knauf Insulation is committed to providing a comprehensive range of relevant sales and marketing literature and web-based technical information to support specifiers and customers.



Earthwool® products made with ECOSE® Technology benefit from a no added formaldehyde binder, which is less energy intensive than traditional binders and is based on rapidly renewable, plant-based materials instead of petro-based chemicals. The technology has been developed for Knauf Insulation's glass and rock mineral wool products, enhancing their environmental credentials without affecting the thermal, acoustic or fire performance. Earthwool® products made with ECOSE® Technology contain no added dyes or artificial colours.

#### Knauf Insulation Pte Ltd

Registration no: 201510286R

1 Yishun Industrial Street 1, #05-34, A'Posh Bizhub, Singapore, 768160

Technical Advisory: info.sg@knaufinsulation.com

**KNAUF**INSULATION

All rights reserved, including those of photomechanical reproduction and storage in electronic media. Extreme caution was observed when putting together and processing the information, texts and illustrations in this document. Nevertheless, errors cannot quite be ruled out. The publisher and editors cannot assume legal responsibility or any liability whatever for incorrect information and the consequences thereof. The publisher and editors will be grateful for improvement suggestions and details of possible errors pointed out.