


KNAUF

Armstrong ANF RH95






















Armstrong ANF RH95 offers a non-directional pin hole visual and excellent Light Reflectance.

- Non-directional pin hole visual saves installation time & wastage
- Superior humidity resistance: RH95
- Ideal for offices, retail, education, healthcare

Build on us.

Armstrong ANF RH95

Characteristic	Detailed information							
Edge details		Board 	Tegular 24 	Tegular 15 BE 				
Thickness (mm)		15	15	15				
Dimensions (mm)		600 x 600	600 x 600	600 x 600				
System		Exposed Grid System, Demountable Ceiling (Prelude 24 mm)			Exposed Grid System, Demountable Ceiling (Suprafine 15 mm / Silhouette)			
Weight		≅ 3.0 kg/m²						
Colour		 White						
Sound attenuation		CAC = 30 dB						
Sound absorption		Frequency f (HZ)	125	250	500	1000	2000	4000
		a_p	0.31	0.33	0.57	0.70	0.46	0.35
		NRC = 0.50						
Fire Reaction		Class 0 / Class 1 as per BS 476 Pt - 6 & 7 Class A as per ASTM E-84						
Light reflectance		Up to 85%						
Thermal conductivity		$\lambda = 0.052 - 0.057 \text{ W/mK}$						
Humidity resistance		Up to 95% RH						
Recycled content		Up to 30%						
Cleanability								
Sustainability	