

Safety data sheet in accordance with Regulation (EC) No 1907/2006

Revision date: 01.06.2015
Replacement of version 0017 of 20.06.2014

Version: 0018

Knauf Aquapanel GmbH & Co. KG

1. Identification of the substance/mixture and of the company/undertaking

1.1 *Product identifier*

Trade name **AQUAPANEL® Exterior Dispersion Plaster - white**
Product number **KAQ_0400**
Item code **87268**

1.2 *Relevant identified uses of the substance or mixture and uses advised against*

Appropriate use:
The product is used as a facade plaster/structural plaster.

Recommended restrictions on use:

Preclude from exposure and handling this product those persons suffering from an allergy and those persons susceptible to respiratory disease.

1.3 *Company/undertaking identification*

Knauf Aquapanel GmbH & Co. KG
Zur Helle 11
D-58638 Iserlohn

Telephone: +49-2374-50360
e-mail: aquapanel.info@knauf.com

Fax: +49-2374-5036300

Technical contact:

Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn
Telephone: +49-2374-50360 Fax: +49-2374-5036300

1.4 *Emergency telephone number*

Giftnotruf Berlin, Advice in German and English
Telephone: +49-30-30686 790

Safety data sheet in accordance with Regulation (EC) No 1907/2006

Trade name:	AQUAPANEL® Exterior Dispersion Plaster - white	Product number:	KAQ_0400
Company/Undertaking:	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn	Date issued:	
Telephone:	+49-(0)2374-50360	Revision date:	01.06.2015

2. Hazards identification

2.1 Classification of the substance or mixture in accordance with Regulation (EC) No 1272/2008

Aquatic Chronic 3; H412

2.2 Label elements in accordance with Regulation (EC) No 1272/2008

Hazard pictogram(s): No pictogram is used

Signal word(s): No signal word is used

Product identifier: AQUAPANEL® Exterior Dispersion Plaster - white

Hazard statements: H412 Harmful to aquatic life with long lasting effects.

Precautationary statements: P102 Keep out of reach of children.
P273 Avoid release to the environment.
P501 Dispose of contents/container to an authorized waste disposal site.

Supplemental label for certain mixtures:

EUH208 Contains 2-methyl-2H-isothiazol-3-one, 1,2-benzisothiazolin-3-one, reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no 220-239-6] (3:1) and 2-octyl-2H-isothiazol-3-one. May produce an allergic reaction.

Special labelling in accordance with Article 58 (3)

of Regulation (EU) No 528/2012: Contains terbutryn, 2-methyl-2H-isothiazol-3-one, 1,2-benzisothiazolin-3-one, reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no 220-239-6] (3:1), 2-octyl-2H-isothiazol-3-one and pyriithione zinc as biocidal active substances.

Remark:

- The precautionary statements P102 and P501 must only appear on the label of packaging supplied to the general public.
- According to Article 35 paragraph 2 of Regulation (EC) No 1272/2008 packaging supplied to the general public should not have either a shape or form to mislead consumers.
- The use of the EUH208 sentence is based on the CEPE Guidance on labelling decorative paint with skin sensitizing biocides⁵.

2.3 Other hazards

Persistent or repeated contact with the skin may cause irritations.

Risk of skin defatting and skin desiccation in case of persistent or repeated contact with the skin.

Preclude from exposure and handling this product those persons suffering from an allergy and those persons susceptible to respiratory disease.

Ingestion of the product can cause disorders of the intestinal flora.

The product is classified as low hazardous to water.

The mixture does not contain any substances classified as PBT/vPvB.

Safety data sheet in accordance with Regulation (EC) No 1907/2006

Trade name:	AQUAPANEL® Exterior Dispersion Plaster - white	Product number:	KAQ_0400
Company/Undertaking:	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn	Date issued:	
Telephone:	+49-(0)2374-50360	Revision date:	01.06.2015

3. Composition/information on ingredients

3.2 Mixtures

REACH registration number:

The ingredients do not require registration according to Regulation (EC) No 1207/2006 [REACH] or the registration is scheduled at a later date.

3.2.1 Characterisation

This product is a mixture of calcium carbonate, titanium dioxide, silicious fillers, plastics dispersion, water and additives.

3.2.2 Substances presenting a health/environmental hazard within the meaning of Regulation (EC) No 1272/2008

CAS No	EC No	Identification	% by weight	Classification
2682-20-4	220-239-6	2-methyl-2H-isothiazol-3-one	≥ 0.01 - < 0.1	Acute Tox. 3; H301 Acute Tox. 3; H311 Skin Corr. 1B; H314 Skin Sens. 1; H317 Eye Dam. 1; H318 STOT SE 3; H335 Aquatic Acute 1; H400
2634-33-5	220-120-9	1,2-benzisothiazolin-3-one	≥ 0.005 - < 0.05	Acute Tox. 4; H302 Skin Irrit. 2; H315 Skin Sens. 1; H317 Eye Dam. 1; H318 Aquatic Acute 1; H400
26530-20-1	247-761-7	2-octyl-2H-isothiazol-3-one	≥ 0.005 - < 0.05	Acute Tox. 4; H302 Acute Tox. 3; H311 Skin Corr. 1; H314 Skin Sens. 1; H317 Acute Tox. 3; H331 Aquatic Acute 1; H400 Aquatic Chronic 1; H410
55965-84-9	not available	Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no 220-239-6] (3:1)	≥ 0.00015 – < 0.0015	Acute Tox. 3; H301 Acute Tox. 3; H311 Skin Corr. 1B; H314 Skin Sens. 1; H317 Eye Dam. 1; H318 Acute Tox. 3; H331 Aquatic Acute 1; H400 Aquatic Chronic 1; H410
886-50-0	212-950-5	terbutryn	≥ 0.0025 - < 0.01	Acute Tox. 4; H302 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410
13463-41-7	236-671-3	pyrithione zinc	< 0.01	Acute Tox. 3; H301 Eye Dam. 1; H318 Acute Tox. 3; H331 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-factor (chronic) = 10 M-factor (acute) = 100

See subsection 2.2 for further details. Full text of the hazard statements see subsection 16.2.

3.2.3 Substances which are assigned Community workplace exposure limits and which are not already included under point 3.2.2 (see also Section 8.)

No substances.

3.3 Additional information

None.

Trade name:	AQUAPANEL® Exterior Dispersion Plaster - white	Product number:	KAQ_0400
Company/Undertaking:	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn	Date issued:	
Telephone:	+49-(0)2374-50360	Revision date:	01.06.2015

4. First aid measures

4.1 Description of first aid measures

4.1.1 General information

Take off contaminated clothing immediately and wash before reuse.
Emergency eyewash should be provided in the immediate working surroundings.

4.1.2 In case of inhalation

Take affected person to fresh air.
By continuous complaints seek medical advice.

4.1.3 In case of contact with skin

In case of contact with skin wash off immediately with soap and water.
Do not wash with solvents or diluting agent.
By continuous complaints seek medical advice.

4.1.4 In case of contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.
Remove contact lenses, if present and easy to do.

4.1.5 In case of ingestion

If swallowed, rinse mouth with water (only if the person is conscious).
Do not induce vomiting.
Put victim at rest. Summon a doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

Risk of skin defatting and skin desiccation in case of persistent or repeated contact with the skin.
Possible allergic reaction in case of skin contact.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically. No information available.

5. Firefighting measures

5.1 Extinguishing media

5.1.1 Suitable extinguishing media

Alcohol-resistant foam, carbon dioxide, dry powder, water spray jet..

5.1.2 Unsuitable extinguishing media

Full water jet.

5.2 Special hazards arising from the substance or mixture

In the event of fire the following can be released: toxic pyrolysis products (e.g. carbon dioxide, carbon monoxide).

5.3 Advice for firefighters

Wear self-contained breathing apparatus.
Do not inhale explosion and/or combustion gases. Cool endangered containers with water spray jet.
Collect contaminated firefighting water separately, must not be discharged into the drains.
Aqueous product is not combustible as long as the water fraction is present.

Trade name:	AQUAPANEL® Exterior Dispersion Plaster - white	Product number:	KAQ_0400
Company/Undertaking:	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn	Date issued:	
Telephone:	+49-(0)2374-50360	Revision date:	01.06.2015

6. Accidental release measures

6.1 *Personal precautions, protective equipment and emergency procedures*

6.1.1 *For non-emergency personnel*

Ensure adequate ventilation. Use personal protective clothing.
Keep away from unprotected people.

6.1.2 *For emergency responders*

For suitable fabric for personal protective clothing see Section 8.

6.2 *Environmental precautions*

Do not discharge into the drains, the aquatic environment and soil.

6.3 *Methods and material for containment and cleaning up*

Absorb with liquid-binding material (e.g. sand, kieselguhr, acid binder, universal binder, sawdust).
Send in suitable containers for recovery or disposal.
Clean contaminated floors and objects thoroughly with detergents, do not use solvents.

6.4 *Reference to other sections*

For personal protective equipment see also Section 8.
For disposal considerations see also Section 13.

7. Handling and storage

7.1 *Precautions for safe handling*

7.1.1 *Advice on safe handling*

Provide good ventilation of working area (local exhaust ventilation if necessary).
Comply with the minimum standards in accordance with TRGS 500.¹
Moreover, comply with the protective measures in accordance with TRGS 401.¹
In designing the work process the model solutions of the protection guideline 120¹ must be taken into consideration in case of small-area skin contact (e.g. splashes) regardless on the duration of skin contact.
In designing the work process the model solutions of the protection guideline 120¹ must be taken into consideration in case of large-area skin contact (wetting of the skin) and short-term effect (duration of skin contact less than 15 minutes per shift).
In designing the work process the model solutions of the protection guidelines 120¹ and 250¹ must be taken into consideration in case of large-area skin contact (wetting of the skin) and long-term effect (duration of skin contact more than 15 minutes per shift).

7.1.2 *Advice on general occupational hygiene*

Avoid contact with eyes and skin.
Take off contaminated clothing immediately and wash before reuse.
At work do not eat, drink, smoke or take drugs.
Clean skin thoroughly after work and before breaks; apply skin cream. Use barrier skin cream.
Set out skin protection guidelines.
Emergency eyewash should be provided in the immediate working surroundings.

7.2 *Conditions for safe storage, including any incompatibilities*

7.2.1 *Advice on protection against fire and explosion*

No special measures necessary. Aqueous product is not combustible as long as the water fraction is present.

7.2.2 *Requirements for storage rooms and vessels*

Keep container tightly closed. Keep only in the original container in a dry, well ventilated place.

7.2.3 *Advice on storage compatibility*

Do not store together with strong acidic and alkaline materials and oxidising agents.
The information about joint storage given in Table 2 of TRGS 510¹ must be observed.

7.2.4 *Further information on storage conditions*

Protect from heat and direct sunlight. Protect from frost.
Recommended storage temperature: + 5 up to + 25°C.
Storage life: 24 months in the original container.

7.2.5 *Storage class (for Germany only)*

LGK 12 (non-combustible liquids) in accordance with TRGS 510¹.

Safety data sheet in accordance with Regulation (EC) No 1907/2006

Trade name:	AQUAPANEL® Exterior Dispersion Plaster - white	Product number:	KAQ_0400
Company/Undertaking:	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn	Date issued:	
Telephone:	+49-(0)2374-50360	Revision date:	01.06.2015

7.3 *Specific end use(s)*

The product is only intended for the uses mentioned under subsection 1.2.

For outdoor use. Observe technical data sheet.

In accordance with GISBAU (Information system of the the German professional associations for building and construction industry): GISCODE⁴: M-DF02 (water-based paints)

8. Exposure controls/personal protection

8.1 *Control parameters*

The product does not contain substances above cut-off values for which there are exposure limit values.

8.2 *Exposure controls*

8.2.1 *Appropriate engineering controls*

Technical measures and appropriate working operations should be given priority over the use of personal protective equipment.

See also subsection 7.1.

8.2.2 *Individual protection measures, such as personal protective equipment*

Personal protective equipment needs to be selected specifically for the workplace, depending on concentrations and quantities of the hazardous substances handled. In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer/supplier of the personal protective equipment.

8.2.2.1 *Eye/face protection*

Tightly fitting safety glasses in accordance with EN 166.

In case of spraying: goggles.

8.2.2.2 *Skin protection*

Hand protection:

Protective gloves made of natural rubber latex, neoprene, nitrile, PVC, fluorinated rubber, butyl rubber.

A list of models of suitable protective gloves for handling this product can be find under GISCODE M-DF02⁴ (water-based paints) in accordance with GISBAU (Information system of the the German professional associations for building and construction industry). Wear cotton undermitten if possible.

The protective gloves to be used must be comply with the specifications of the standard EN 374.

Body protection:

Closed work clothing. In case of spraying: single-use suit.

8.2.2.3 *Respiratory protection*

In case of spraying, higher concentrations and if ventilation insufficient, use a respiratory protection apparatus with respiration filter (particle filter P2).

The limitations in wearing time according to the DGUV Regel 112-190² (rule of the German employers' liability insurance association) for the use of respirators have to observed.

8.2.2.4 *Thermal hazards*

Not relevant.

8.2.3 *Environmental exposure controls*

See Section 6.

Safety data sheet in accordance with Regulation (EC) No 1907/2006

Trade name:	AQUAPANEL® Exterior Dispersion Plaster - white	Product number:	KAQ_0400
Company/Undertaking:	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn	Date issued:	
Telephone:	+49-(0)2374-50360	Revision date:	01.06.2015

9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	pasty
Colour:	white
Odour:	characteristic
Odour threshold:	no data available
pH (as supplied) (20°C):	9
pH (of an aqueous solution) (20°C):	not determined
Melting point/freezing point (°C):	not determined
Boiling point and boiling range (°C):	not determined
Flash point (°C), closed cup:	not relevant
Evaporation rate:	not determined
Flammability (solid, gas):	not relevant
Upper flammability or explosive limit:	not relevant
Lower flammability or explosive limit:	not relevant
Vapour pressure (20°C) (hPa):	23
Vapour density (20°C):	not determined
Density (g/cm ³) (20°C):	1.80 (DIN 53217)
Solubility in water:	completely miscible
Soluble in:	not determined
Partition coefficient: n-octanol/water:	no data available
Auto-ignition temperature (°C):	not relevant
Decomposition temperature (°C):	not determined
Dynamic viscosity (mPa · s) (20°C):	no data available
Explosive properties:	not explosive
Oxidising properties:	not relevant

9.2 *Other information* None.

10. Stability and reactivity

10.1 Reactivity

No data available for the product.

10.2 Chemical stability

The product is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

Possible reaction in case of contact with strong acids, strong alkalies and oxidising agents.

10.4 Conditions to avoid

When used as intended, no particular conditions known.

10.5 Materials to avoid

Avoid contact with strong acids, strong alkalies and oxidising agents.

10.6 Hazardous decomposition products

No hazardous decomposition products known. For hazardous combustion products see subsection 5.2.

Trade name:	AQUAPANEL® Exterior Dispersion Plaster - white	Product number:	KAQ_0400
Company/Undertaking:	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn	Date issued:	
Telephone:	+49-(0)2374-50360	Revision date:	01.06.2015

11. Toxicological information

11.1 Information on toxicological effects

11.1.1 Toxicokinetics, metabolism and distribution

No data are available for the product.

11.1.2 Acute effects (acute toxicity, irritation and corrosivity)

LD50 rat, oral	(mg/kg)	No data available.
LD50 rat, dermal	(mg/kg)	No data available.
LC50 rat, inhalation	(mg/l/4h)	No data available.
Irritant effect on skin		No data available.
Irritant effect on eyes		No data available.

11.1.3 Sensitisation

The product has not been tested.

The product contains 2-methyl-2*H*-isothiazol-3-one, 1,2-benzisothiazolin-3-one, reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no 247-500-7] and 2-methyl-2*H*-isothiazol-3-one [EC no 220-239-6] (3:1) and 2-octyl-2*H*-isothiazol-3-one. These substances are classified as sensitising.

11.1.4 Repeated dose toxicity

No data available.

11.1.5 CMR effects (carcinogenicity, mutagenicity, toxicity for the reproduction)

Carcinogenicity	No data available.
Mutagenicity	No data available.
Toxicity for the reproduction	No data available.

11.1.6 Comprehensive evaluation of the CMR properties of substances subject to registration

No data available.

11.1.7 Information on likely routes of exposure

Persistent or repeated contact with the skin may cause irritations.

Risk of skin defatting and skin desiccation in case of persistent or repeated contact with the skin.

Possible allergic reaction in case of skin contact.

Ingestion of the product can cause disorders of the intestinal flora

11.1.8 Symptoms related to the physical, chemical and toxicological characteristics

Persistent or repeated contact with the skin may cause irritations.

Risk of skin defatting and skin desiccation in case of persistent or repeated contact with the skin.

Possible allergic reaction in case of skin contact.

Ingestion of the product can cause disorders of the intestinal flora

11.1.9 Delayed and immediate effects as well as chronic effects from short and long-term exposure

Persistent or repeated contact with the skin may cause irritations.

Risk of skin defatting and skin desiccation in case of persistent or repeated contact with the skin.

Persons suffering from an allergy may be sensitive to very low concentrations of allergenic substances and should consequently have no further contact with this product (possibility of an allergic reaction).

Ingestion of the product can cause disorders of the intestinal flora.

11.1.10 Interactive effects

No information on interactive effects available for the product.

11.1.11 General remarks

The product has not been tested.

Safety data sheet in accordance with Regulation (EC) No 1907/2006

Trade name:	AQUAPANEL® Exterior Dispersion Plaster - white	Product number:	KAQ_0400
Company/Undertaking:	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn	Date issued:	
Telephone:	+49-(0)2374-50360	Revision date:	01.06.2015

12. Ecological information

12.1 Toxicity

Aquatic toxicity:

96 h LC50	(fish)	No data available.
48 h EC50	(daphnia)	No data available.
72 h IC50	(algae)	10 - 100 mg/l (Pseudokirchneriella subcapitata) (information of the manufacturer)

Behaviour in sewage works:

The behaviour of the product in sewage treatment plants has not been tested. Do not discharge into the drains.

12.2 Persistence and degradability

The product has not been tested.

12.3 Bioaccumulative potential

The product has not been tested.

12.4 Mobility in soil

The product has not been tested.

12.5 Results of PBT and vPvB assessment

The mixture does not contain any substances classified as PBT/vPvB.

12.6 Other adverse effects

Ozone depletion potential	No data available.
Photochemical ozone creation potential	No data available.
Global warming potential	No data available.
AOX-hint	Not to apply.

12.7 Further information

Chemical oxygen demand (COD)	No data available.
Biochemical oxygen demand (BOD5)	No data available.

The product is classified as low hazardous to water.

Contains according to the formulation following compounds of directives 2006/11/EC and 80/68/EEC:

List II: biocides and their derivatives not appearing in List I.

Safety data sheet in accordance with Regulation (EC) No 1907/2006

Trade name:	AQUAPANEL® Exterior Dispersion Plaster - white	Product number:	KAQ_0400
Company/Undertaking:	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn	Date issued:	
Telephone:	+49-(0)2374-50360	Revision date:	01.06.2015

13. Disposal considerations

13.1 Waste treatment methods

Waste disposal according to official state regulations.
Consult the local waste disposal expert about waste disposal.
Sewage disposal must be avoided.

Disposal operations/recovery operations according to Directive 2008/98/EC

Disposal operations: D 9 Physico-chemical treatment
Recovery operations: R 5 Recycling/reclamation of other inorganic materials

Properties of waste which render it hazardous in accordance with Annex III of Directive 2008/98/EC

H 14: Ecotoxic

13.1.1 Product / unused product

Waste disposal corresponding to European Waste Catalogue. Wastes must be classified with respect to their origin and depending on different processing steps. The waste codes mentioned as follows are only constituted as our recommendations. Referring to the particular case they should be completed or revised.

Dried-out product remainders:

EC waste code: 08 01 12
Waste notation: Waste paint and varnish other than those mentioned in 08 01 11

Liquid product residues:

EC waste code: 08 01 20
Waste notation: Aqueous suspensions containing paint or varnish other than those mentioned in 08 01 19

Alternative:

EC waste code: 17 09 04
Waste notation: Mixed construction and demolition wastes other than those mentioned in 17 09 01, 17 09 02 and 17 09 03

13.1.2 Contaminated packaging

Recommendation: Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Recommended cleansing agent: Water.

Packaging that cannot be cleaned:
EC waste code: 15 01 02
Waste notation: Plastic packaging

14. Transport information

14.1 UN number

No dangerous good in accordance with the UN Model Regulations (ADR/RID/ADN/IMDG/ICAO/IATA).

14.2 UN proper shipping name

Not relevant.

14.3 Transport hazard class(es)

Not relevant.

14.4 Packing group

Not relevant.

14.5 Environmental hazards

Not relevant.

14.6 Special precautions for user

Not relevant.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not relevant.

Safety data sheet in accordance with Regulation (EC) No 1907/2006

Trade name:	AQUAPANEL® Exterior Dispersion Plaster - white	Product number:	KAQ_0400
Company/Undertaking:	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn	Date issued:	
Telephone:	+49-(0)2374-50360	Revision date:	01.06.2015

15. Regulatory information

15.1 *Safety, health and environmental regulations/legislation specific for the substance or mixture*

15.1.1 *Information regarding relevant Community provisions*

Directive 2004/42/EC: The product is not subject to Directive 2004/42/EC.

15.1.2 *Information regarding national laws/national measures that may be relevant (for Germany only)*

Indications on restriction of occupation: Not relevant
Major-accident Regulation: Not relevant
Fire and explosion hazards: Not relevant
Regulation on clean air (TA Luft): Not relevant
Water hazard class: WGK 1 – low hazardous to water
(self-classification of the manufacturer according to annex 4, No 3 VwVwS)³
The Federal State Enactment for Facilities to Handle Water Endangering Substances (German VAWS–Anlagen-Verordnung) has to be observed.

German Ordinance on Hazardous Substances
(in accordance with EC-Directive 98/24/EC): Articles 6, 7, 8 and 14 must be observed.
Technical Rules for Hazardous Substances¹: TRGS 400, 401, 500, 510, 555
Rules of the employers' liability insurance association²: DGUV Regel 112-189, 112-190, 112-192, 112-195
DGUV Regel 100-500, chapter 2.29
(processing of coating material)

Classification in accordance with the easy-to-use workplace control scheme for hazardous substances of the Federal Institute for Occupational Safety and Health, version 2.2, 2012⁶: skin contact: hazard group HA

In accordance with Article 16e of the German Chemicals Act there is an obligation to notify the product at the Federal Institute of Risk Assessment (BfR).

15.2 *Chemical Safety Assessment*

No Chemical Safety Assessment has been carried out for a substance in the product..

Safety data sheet in accordance with Regulation (EC) No 1907/2006

Trade name:	AQUAPANEL® Exterior Dispersion Plaster - white	Product number:	KAQ_0400
Company/Undertaking:	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn	Date issued:	
Telephone:	+49-(0)2374-50360	Revision date:	01.06.2015

16. Other information

16.1 Keeping (restrictions)

Article 8 paragraphs 5 and 6 of the German Ordinance on Hazardous Substances has to be observed. (only for Germany)
to industry consumer, for the general public

Supply

16.2 Full text of the hazard statements referred to under subsection 2.1 and point 3.2.2 of the Safety Data Sheet

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

16.3 Key to abbreviations and acronyms used in the safety data sheet

ADN:	Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
ADR:	Accord européen relatif au transport international des marchandises dangereuses par route
AOX:	adsorbable organically bound halogens
CEPE:	Conseil Européen de l'Industrie des Peintures, des Encres d'Imprimerie et des Couleurs d'Arts (European Council of Paint, Printing Ink and Artist's Colours Industry)
ICAO/IATA:	International Civil Aviation Organisation/International Air Transport Association-Dangerous Goods Regulations
IMDG-Code:	International Maritime Dangerous Goods-Code
LGK:	Lagerklasse (storage class)
PBT:	persistent, bioaccumulative and toxic
RID:	Règlement international concernant le transport des marchandises dangereuses par chemin de fer
TRGS:	Technische Regeln für Gefahrstoffe (Technical Rules for Hazardous Substances)
VCI:	Verband der chemischen Industrie (German Association of Chemical Industry)
vPvB:	very persistent and very bioaccumulative
VwVwS:	Verwaltungsvorschrift wassergefährdende Stoffe (Administrative Regulation of Water-polluting Substances)

16.4 Literature references and sources for data

- <http://www.baua.de>
- <http://www.arbeitssicherheit.de>
- <http://www.umweltbundesamt.de>
- <http://www.wingis-online.de>
- <http://www.cepe.org/efede/public.htm#!HTML/3008>
- <http://www.baua.de/emkg>

16.5 Method used for the classification of the mixture

The classification was undertaken in accordance with the classification criteria of Annex I of Regulation (EC) No 1272/2008.

16.6 Changes which have been made to the previous version of the safety data sheet

Revised sections: 1.2, 2.1.1 (now 2.1), 2.1.2 (deleted), 2.2, 2.3, 3.2.2, 3.2.3 (deleted), 3.2.4 (now 3.2.3), 4.1.1, 4.2, 7.1.1, 7.1.2, 8.1, 8.2.2.3, 9.1, 11.1.3, 11.1.7, 11.1.8, 11.1.9, 11.11, 12.1, 13.1.1, 13.1.2, 15.1.1, 15.1.2, 16.2, 16.3 (deleted), 16.4 (deleted), 16.5 (now 16.3), 16.6 (now 16.4), 16.7 (now 16.5), 16.8 (now 16.6)

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.