

## Note on English translation / Hinweise zur englischen Fassung

This is a translation of the product data sheet valid in Germany.

All stated details and properties are in compliance with the regulations of the German standards and building regulations. They are only applicable for the specified products, system components, application rules, and construction details in connection with the specifications of the respective certificates and approvals.

Knauf Gips KG denies any liability for applications outside of Germany as this requires changes acc. to the respective national standards and building regulations.

# KNAUF



Floor Systems

## F431.de

Product Data Sheet

2020-05



# Estrichgrund screed primer

Primer for absorbent flooring substrates

## Product description

Estrichgrund screed primer is a concentrated primer on a synthetic resin emulsion basis, is pink in colour and alkaline resistant.

## Storage

It can be stored for at least 18 months in the original unopened container in a cool and frost-free (+5 °C to +25 °C) environment. Close opened buckets airtight. Do not expose to direct sunlight or heat.

## Quality

The product is subject to continuous factory production control.

## Properties and added value

- For interior and exterior application
- Very low emission, EMICODE EC 1<sup>PLUS</sup>  
For details see [www.emicode.com/en](http://www.emicode.com/en)

- Solvent-free concentrate
- Regulates absorption
- Pigmented green
- Manual application

## Field of application

For interior application on basic floors intended for the application of bonded screed as well as pre-fab floor screed (e.g. Knauf Brio), calcium sulphate screed (e.g. FE 50 Largo, FE 80 Allegro), and other common mineral-based floor substrates.

For regulating the absorptivity, improving bonding properties and moisture protection as a preliminary coat before the application of:

- Floor filling compounds
- Floor coverings (e.g. tiles)



### Application

#### Substrate and pretreatment

Preliminary tests are necessary with critical substrates, if necessary, crosscut or scratch tests may need to be performed.

The substrate must be

- Stable, dry, firm and sufficiently dimensionally stable as well as
- Dust-free, free of loose components, oil, grease, concrete release agents and treatment agents, sinter layers, impurities and harmful efflorescence.

#### Preparation

<b>Note</b>	Do not mix Estrichgrund screed primer with other materials because properties can possibly change significantly.
-------------	------------------------------------------------------------------------------------------------------------------

Protect easily-soiled building components, particularly glass surfaces, wood, metal, natural stone and floor covering.

#### Application

Stir the contents of the bucket thoroughly before application. Dilute Estrichgrund screed primer in accordance with the substrate (see table) and apply a uniform cross coat with a floor coater, painter's brush, primer brush or roller. Remove excess material so that no glossy spots or pools occur. Clean tools directly after use with water. Remove contaminations of Estrichgrund screed primer (splashes or similar) on the contaminated surfaces preferably in the fresh state with warm water. Dried material can be removed after softening, using a damp wiping cloth or similar.

#### Drying

Wait with subsequent work until the Estrichgrund screed primer is no longer adhesive and has fully dried (min. 12 hours at 20 °C and 65% rel. humidity). Correspondingly longer drying times result from cool and damp site conditions.

Highly absorbent surfaces and/or good ventilation shorten the drying times. The time after drying of Estrichgrund primer and commencement of the subsequent work should be kept as short as possible to avoid dust depositing on the surfaces.

#### Application temperature / climate

The material, substrate and air temperatures during application and until the primer is fully dry should not fall below +5 °C.

Substrate	Subsequent coating	Recommended dilution values Estrichgrund : Water
<b>Basic concrete, cementitious screed</b>	Bonded calcium sulphate screed e.g. FE 80 Allegro, FE 50 Largo, FE 25 A tempo	1 : 1 <sup>1)</sup>
	Thin-screed compound, e.g. N 340	1 : 1 <sup>1)</sup>
	Equalization compound, e.g. N 320 Sprint	1 : 1 <sup>1)</sup>
<b>Calcium sulphate screed<sup>2)</sup></b> Knauf flowing screed (e.g. FE 80 Allegro, FE 50 Largo, FE 25 A tempo, N 440)	Equalization compound, e.g. N 320 Sprint	1 : 1 <sup>1)</sup>
	N 410	1 : 1
	Tile adhesive mortar, floor covering adhesive, carpet fixing	1 : 1
<b>Pre-fab floor screed</b> Brio	Filler compounds, flooring adhesive, tiling adhesive	1 : 1
	Tile adhesive mortar, floor covering adhesive, carpet fixing	1 : 1

1) If required apply 2x primer with highly absorbent substrate, on non-absorbing substrates suitable special primers, e.g. Spezialhaftgrund bonding primer should be used.

2) For N 440 (F422.de) on calcium sulphate screed use FE-Imprägnierung (F451.de) as a primer

### Technical data

Density	Viscosity	pH value
1.0 kg/l	liquid	approx. 7.5

### Material requirement and efficiency

Substrate	Consumption approx. in g/m <sup>2</sup> per application
Basic floor	150
Calcium sulphate screed	100
Pre-fab floor screed	50

*All specifications are approximate values and can deviate depending on the substrate. The exact consumption can only be determined on the individual object.*

### Product range

Description	Application	Packaging unit	Material number	EAN
Estrichgrund	5 kg	60 buckets/pallet	00005700	4003982020123
	10 kg	36 buckets/pallet	00005355	4003982020116



**Observe safety data sheets!**

For safety data sheets and CE marking see  
[pd.knauf.de](http://pd.knauf.de)



Videos for Knauf systems and products can be found under the following link:

[www.youtube.com/knauf](http://www.youtube.com/knauf)



The iPad App Knauf Infothek now provides all the current information and documents from Knauf Gips KG at any time and in every location in a clear and comfortable way.

[Knauf Infothek](#)

**Knauf Direct**

Technical Advisory Service:

▶ [knauf-direkt@knauf.de](mailto:knauf-direkt@knauf.de)

▶ [www.knauf.de](http://www.knauf.de)

**Knauf Gips KG** Am Bahnhof 7, 97346 Iphofen, Germany

All technical changes reserved. Only the current printed instructions are valid. The stated information represents current state-of-the-art Knauf technology. The entire state of approved engineering rules, appropriate standards, guidelines, and rules of craftsmanship are not included herewith. These and all application instructions have to be adhered to separately by the installer. Our warranty is expressly limited to our products in flawless condition. All application quantities and delivery amounts are based on empirical data that are not easily transferable to other deviating areas.

All rights reserved. All amendments, reprints and photocopies, including those of excerpts, require our expressed permission.