

Knauf GW-TX

Fire Resistant Gypsum Board



Product-Data-Sheet

06/2024

Product Description

Knauf GW-TX is a type X Fire Resistant Gypsum Board and offers an improved fire protection when used as part of a complete fire rated Knauf System.

Knauf GW-TX Board is made from an aerated gypsum core with glass fiber additives to maintain the integrity of board for longer time when exposed to fire, and has premium paper liners on each side of the board. The board is ideally suited to receive Knauf jointing finishes before decoration.

Key Benefits

- Strong and versatile.
- Enhanced fire resistance performance.
- Good sound insulation performance.
- Fully recyclable.
- Quick and easy to install.
- Multiple layers can be used for added performance.


Areas of Application

Knauf GW-TX Board is suitable for drywall partitions, wall linings, ceilings, and shaftwall applications where superior fire protection is required.

Compliance Standard

- **ASTM C1396-17: Standard Specification for Gypsum Board**
 - Type X: Gypsum panel specifically designed for superior fire resistance.
 - Section 5: Gypsum wallboard, predecorated gypsum board, and laminated gypsum board.
 - Section 12: Gypsum ceiling board
- **ASTM E84: Standard Test Method for Surface Burning Characteristics of Building Materials**
 - Class A

Appearance



Performance Table

Thickness (mm)	Surface Burning Characteristics (ASTM E84)		Thermal Conductivity (w/mk)	Board Density (kg/m ³)
	FSI*	SDI*		
12.7	10	20	0.25	827
15.9	10	15	0.25	824

*FSI: Flame Spread Index

*SDI: Smoke Developed Index

Technical Information

Dimension, Weight and Physical Properties

Thickness (mm)	Width (mm)	Length (mm)	Weight (kg/m ²)	Nail Pull Resistance Method B (N)	Flexural Strength Method B	
					Parallel (N)	Perpendicular (N)
12.7	1200	2400*	10.50	> 343	> 476	> 160
	1200	3000*	10.50	> 343	> 476	> 160
15.9	1200	2400*	13.10	> 387	> 654	> 205
	1200	3000*	13.10	> 387	> 654	> 205

*Special sizes are available upon request.

Sustainability

Recyclability -The product can be recycled, make sure it has no or minimal contamination from non-gypsum based materials as this will affect its recyclability.

Substances of very high concern (SVHC) This product do not contain any substance of high concern

Volatile Organic Compound Content (VOC) This product contains < 0.05 mg/kg VOC content.

Asbestos Content: This product does not contain any asbestos content.

Storage and Handling

Product must be stored flat and on a surface strong enough to support them. Keep boards dry at all times.

Refer to the HSE Manual Handling Operations Regulation for best practice guidance.

Packaging

Product is stacked on non-recycled chipboard bearers and is not recyclable but it can be returned to Knauf.

Shelf Life/Service Life

Service life of this product is 60 years and/or the lifetime of the building.

Disposal

Disposal should be in accordance with local authority requirements. Keep gypsum based products in their own recycling area to minimise contamination from non-gypsum based products.

Health & Safety

Please refer to our Safety Data Sheet for guidance on personal protection equipment required for the handling and installation of this product.

Application /Installation

Typically installed as a part of a partition system, wall lining and ceiling system with Knauf fixings, jointing, taping and finishing products.

Use Knauf plasterboard screws at a distance of 300mm on horizontal joints and 10mm from bound edge and 13mm from cut edges in from the edge of the board. Knauf Readygips with Knauf Joint Tape can be used to finish the joints.

Should an alternative Gypsum or surface finish be required, seek guidance from the supplier on application. The type and number of layers of board used will influence the structural, fire, acoustic and thermal performance of the system. All products must be installed in accordance with Knauf's recommendations.

Additional Documentation

Material Safety Datasheet
EPD / HPD

Customer Service

UAE Tel: +971 4 33771700

8:00 - 17:30 (UAE Time)

Email:GCCcustomer.care@knauf.com

Email: GCCtechnical.care@knauf.com

HQ Address

Knauf LLC
Units B9 & B10 - LIU 6
Dubai Silicon Oasis
Dubai, UAE

Plant Address

P.O.Box 50006
Ras Al Khaimah, U.A.E.
Tel: +971 7 268 9837
Fax: +971 7 221 5301

Plant Address

Plot no - RY-PH02-M3-008
Raysut - WGS-84-Zone 39
Salalah Free Zone
Salalah, Dhofar, Oman



Observe safety data sheet!
For safety data sheets and CE labelling see
www.Knauf.com



Tender texts for all Knauf systems and products with export functions for Word and PDF.



Videos for Knauf systems and products can be found under the following link:
youtube.com/knauf



All information and documents from Knauf GCC are now always up-to-date,

Knauf GCC

Dubai, United arab Emirates

Subject to technical changes. The current edition applies. The information contained herein corresponds to our current state of the art. The generally recognised rules of construction technology, relevant standards, guidelines and trade regulations must be observed by the contractor in addition to the processing instructions. Our warranty relates only to the flawless quality of our material. Consumption, quantity and execution data are empirical values that cannot be transferred without further ado in the event of deviating conditions. All rights reserved. Changes, reprinting and photomechanical and electronic reproduction, even in extracts, require our express authorisation.

Hotline

800 - KNAUF(56283)

The structural, static and physical properties of Knauf systems can only be guaranteed if only Knauf system components or products recommended by Knauf are used.

www.knauf.com

