





ADAGIO dB⁺ Mineralni plafoni



- ADAGIO dB⁺ nudi glatku, ujednačenu i izdržljivu površinu s prvoklasnom otpornošću na ogrebotine i najsvetlijim belim izgledom bez premca. Zahvaljujući odličnoj propusnosti vazduha (bez efekta filtera), površina ostaje belja i svetlija duže vreme. Ploča takođe pruža ravnotežu apsorpcije i prigušenja zvuka, kao i visoku refleksiju svetlosti.
- Izvrsna zvučna izolacija: 41 dB (24mm) / 43 dB (30mm).
- Izvrsna vrednost refleksije svetlosti: (88%).
- ISO 4, Zlatni sertifikat za kvalitet vazduha u zatvorenom prostoru i bronzani sertifikat Cradle to Cradle®.
- Idelano za individualne/privatne kancelarije.

Build on us.



Karakteristike		Detaljne informacije						
Detalji ivica		Board 	Tegular 24/90 			Tegular 15/90 		
Debljina (mm)		24, 30	24			24		
Dimenzije (mm)		600 x 600 625 x 625 1200 x 600 1250 x 625	600 x 600 625 x 625 1200 x 600 1250 x 625			600 x 600 625 x 625 1200 x 600 1250 x 625		
Sistem		Vidljiva konstrukcija, demontažne ploče - sistem C					Vidljiva konstrukcija, demontažne ploče - sistem C Vidljiva konstrukcija - paralelni Bandraster profili, demontažne ploče - sistem I.3 Vidljiva konstrukcija - Koridor elementi, demontažne ploče - sistem F.3	
Težina		8.6 kg/m² (24mm) 10.6 kg/m² (30mm)						
Boja		 Bela						
Apsorpcija zvuka		EN ISO 354		$\alpha_w = 0.65$ (H) prema EN ISO 11654 - Klasa C				
		Frekvencija f (Hz)	125	250	500	1000	2000	4000
		α_p 24 mm	0.40	0.45	0.60	0.80	0.85	0.85
		α_p 30mm	0.35	0.40	0.65	0.85	0.90	0.95
		NRC = 0.70 prema ASTM C 423						
Uzdužna zvučna izolacija		EN ISO 10848-2 D _{n,f,w} = 41 dB (24mm) prema EN ISO 717-1 D _{n,f,w} = 43 dB (30mm) prema EN ISO 717-1		CAC = 43 dB (24mm) prema ASTM E 413-10 CAC = 44 dB (30mm) prema ASTM E 413-10				
Zvučna izolacija		EN ISO 10140-2 R _w = 24 dB (24mm) prema EN ISO 717-1		R _w = 25 dB (30mm) prema EN ISO 717-1				
Reakcija na požar		Euroclass A2-s1, d0 prema EN 13501-1						
Refleksija svetlosti		88%						
Toplotna provodljivost		$\lambda = 0.075$ W/mk prema EN 12667						
Propusnost vazduha		PM1 (≤ 30 m³/hm²) prema DIN 18177						
Otpornost na vlagu		95% RH						
Klasa čistoće prostora		ISO 4 prema EN ISO 14644-1						
Kvalitet vazduha		 A+	 E1	 IACG				
Čišćenje								
Održavanje		 36.8-37.4% (2024)	 EC 1272/2008 Annex G	 MATERIALS EMISSION CLASS FOR BUILDING	 BRONZE		www.blauer-engel.de/uz132	