



## DECLARATION OF PERFORMANCE

No 0022\_Fliseklæber Extra\_2020-07-23

1. Unique identification code of the product-type: **C 2 TE S1 - Knauf Fliseklæber Extra**
2. Intended use/es: **Ceramic tile adhesives for internal and/or external wall, floor and ceiling finishes**
3. Manufacturer: **Knauf Bauprodukte GmbH & Co. KG, Am Bahnhof 7, D-97346 Iphofen, Tel. +499323 31-0, Fax +499323 31-277, E-Mail [info@knauf-bauprodukte.de](mailto:info@knauf-bauprodukte.de)**
4. Authorised representative: **Not relevant**
5. System/s of AVCP: **System 3**
6. a) Harmonised standard: **EN 12004:2007+A1 :2012-06**  
Notified body/ies: **TÜV Rheinland LGA Bautechnik GmbH (NB 0780)**
6. b) European Assessment Document: **Not relevant** / European Technical Assessment: **Not relevant**  
Technical Assessment Body: **Not relevant** / Notified body/ies: **Not relevant**
7. Declared performance/s:

Essential characteristics	Performance
Reaction to fire	E
Release of dangerous substances	See safety data sheet
High initial tensile adhesion strength	$\geq 1,0 \text{ N/mm}^2$
Slip	$\leq 0,5 \text{ mm}$
Extended open time: tensile adhesion strength	$\geq 0,5 \text{ N/mm}^2$ after not less than 30 min
Deformable adhesive: transverse deformation	$\geq 2,5 \text{ mm}$ and $< 5 \text{ mm}$
High tensile adhesion strength after heat ageing	$\geq 1,0 \text{ N/mm}^2$
High tensile adhesion strength after water immersion	$\geq 1,0 \text{ N/mm}^2$
High tensile adhesion strength after freeze/thaw cycles	$\geq 1,0 \text{ N/mm}^2$

8. Appropriate Technical Documentation and/or Specific Technical Documentation: **Not relevant**

The performance of the product identified above is in conformity with the set of declared performance/s.  
This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:  
ppa. Ulrich Köhler  
(General Manager)

Iphofen, 2020-07-23  
(place and date of issue)