

# KNAUFINSULATION

## Ultracoustic

**Build on us.**



with **ECOSE**<sup>®</sup>  
TECHNOLOGY

### Product description

**High performance sound insulation rolls of Mineral Wool with ECOSE<sup>®</sup> Technology.**

Ultracoustic is a mineral wool roll offering high sound absorption in special drywall and suspended ceiling applications.

### Applications



# Ultracoustic

## Technical characteristics

Declared coefficient of thermal conductivity $\lambda_D$	0.037 W/mK
Reaction to fire	A1 - non-combustible material
Thickness tolerance	T2
Air flow resistance AFR	>5 kPa·s/m <sup>2</sup>
Declaration of Performance - DoP	<a href="http://www.dopki.com/G4297JPCPR">www.dopki.com/G4297JPCPR</a>
<b>DESIGNATION CODE: MW - EN 13162 - T2 - AFR5</b>	

## Benefits

- High noise absorption capacity
- Excellent reaction to fire - Euroclass A1
- Special thicknesses to fit different dry wall designs
- Simple and easy handling
- Benefits resulting from ECOSE® Technology: softer feel, less dusty, odourless, easy to cut
- Excellent sustainability credentials
- Ideal for LEED, WELL, BREEAM, DGNB projects

## Dimensions and packaging

Thickness (mm)	Width (mm)	Length (mm)	pcs / roll	m2 / roll	Rolls / pallet	m2 / pallet	R Thermal resistance (m2K/W)
45	600	16000	2	19,20	24	460,80	1,20

## Certification, accreditations and industry standards



Declare.



## Application

The product is optimized for applications with high sound absorption requirements. Its typical purpose is sound insulation for partition walls and suspended ceilings. Ultracoustic provides also insulation for systems with given fire resistance requirements as it is a non-combustible material, classified A1 as per EN 13501-1. It can be installed in a single layer and is simple and fast in application.

## Packaging

The product Ultracoustic is delivered in PE heat-shrinking foil. The products must be stored in a dry place, indoors or under roof. In exceptional situations, the packages stored outdoors should be protected by watertight foil. The packages must not be placed directly on the ground

## Quality

Ultracoustic is certified to comply with standard EN 13162 as well as with the EUCEB certificate which ensures that the product is biosoluble and not dangerous for health in accordance with European Directive 97\69\EC. Due to ECOSE Technology naturally based binder, it also possesses Eurofins Indoor Air Comfort Gold Certificate, regarding indoor Environmental Quality and Low-Emitting Materials. It is also officially certified by the DECLARE label, indicating that it is independently analyzed in forensic detail to ensure it does not contain any harmful or unhealthy chemical ingredients included on the International Living Future Institute's Red List.



Knauf Insulation mineral wool products made with ECOSE Technology® benefit from a no added formaldehyde binder, which is up to 70% less energy intensive than traditional binders and is made from rapidly renewable bio-based materials instead of petroleum-based chemicals. The technology has been developed for Knauf Insulation's mineral wool products, enhancing their environmental credentials without affecting the thermal, acoustic or fire performance. Insulation products made with ECOSE Technology® contain no dye or artificial colours.

All rights reserved, including those of photomechanical reproduction and storage in electronic media. Extreme caution was observed when putting together and processing the information, texts and illustrations in this document. Nevertheless, errors cannot quite be ruled out. The publisher and editors cannot assume legal responsibility or any liability whatever for incorrect information and the consequences thereof. The publisher and editors will be grateful for improvement suggestions and details of possible errors pointed out.

## Knauf Insulation S.A.

Evripidou 10, Kallithea 176 74, Greece, Tel: +30 211 710 7007, sales.gr@knaufinsulation.com