

GUARDEX[®] Screw SU

Technical Data Sheet 12/2023



GUARDEX[®] Screw SU

Hanger element

Product Description

Guardex[®] self tapping screws with countersunk cross-heads, having exposed to min. 240 hrs of salt test, are for fixing Guardex[®] to metal substructure with thickness up to 1 mm.

Storage

- Direct contact with water should be avoided.
- Packages should be stored in flat, dry and clean areas.

Referans Standart

EN14566

Fields of Application

- Guardex[®] Exterior Drywall System with ETICS
- Guardex[®] Exterior Drywall Lining System with ETICS
- Guardex[®] Ventilated Façade System

Properties

- Clean and easy installation

Technical Data

Description	Diameter (mm)	Length (mm)	Weight (kg/box)	Packaging Unit (pcs./pallet)	Material Number
GUARDEX® Screw SU	3,5	25	1,32	1000	449540

System Performance Values

Performance values as sound insulation, fire resistance etc. may differ acc. to the drywall system to be applied. Please check the performance values of the drywall systems;

[Knauf Technical Website](#)
[Document Center](#)

Application

Application should be done acc. to the applicable standards (TS 1475) and acc. to the Knauf Technical Brochures of the respective drywall system.

▶ 444 YAPI - 9274

▶ www.knauf.com.tr / www.teknik.knauf.com.tr

▶ teknik@knauf.com

Center: Knauf Moment Beştepe Office, Beştepe Mah. 32.Cadde No:1/212-218 06560 Beştepe-Yenimahalle / ANKARA Tel: 0312 297 0100 Faks: 0312 266 4506