

DECLARATION OF PERFORMANCE

No: SK 02:12/03/2014

1. Unique identification code of the prosuct – type: 3° XERI (TRITO CHERI)

2. Intended use/es: General purpose rendering / plastering mortar for external and internal application CSI

3. Manufacturer:

Knauf Cyprus Itd, Christou Zeipekki 1, 4504 Vasa Kellakiou

Tel. +357-25821040, Fax +357-25821043, E-Mail: knauf@knauf.com.cy

4. System/s

System 4

5. Harmonized standard:

CYS EN 998 - 1:2016

6. Declared performance/s:

Essential characteristics	Performance	Harmonized standard
Reaction to fire	A1	CYS EN 998-1:2016
Adhesion	0.2N/mm² FP:A	
Compressive strength	CS I	
Water absorption	^ W0	
Water vapour diffusion coeff	μ25	
Thermal conductivity	0,83 W/m·K for P = 50% 0,93 W/m·K for P = 90% (tab. mean value)	
Durability (against freeze / thaw)	Evaluation based on provisions valid in the intended place of use of the mortar	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No. 305/2011, with the sole responsibility of the manufacturer identified above.

Signed for and behalf of the manufacturer by:

Marina Christodoulou

(Plant manager)

Limasol / Cyphus, on 02.10.2019