

AQUAPANEL® Interior Primer

Technical Data Sheet 12/2023



Aquapanel® Interior Primer

Primer

Product Description

Ready-to-use primer for Aquapanel® indoor used as a layer to promote adhesion before surface applications.

Storage

- Buckets should be kept unopened in a dry environment at 5-35 °C and should not be exposed to direct sunlight
- Storage life is only valid for unopened buckets.
- Unused buckets should be kept unopened
- Buckets should be kept in frost-free conditions.

Standards referred to

-

Fields of Application

- Plastered Aquapanel® indoor or floor before ceramic adhesive application.
- Cement based plastered surfaces, bricks, briquettes, aerated concrete blocks and concrete blocks surfaces before rendering
- As a bonding primer for smooth or non-absorbent backgrounds (old tiles, mastic asphalt, etc.). Offers a high level of adhesion for tiles and plaster.
- As a highly effective moisture barrier for timber and wood product subsurfaces before applying screed compounds, tile adhesive, etc.
- As a primer for strongly-absorbent surfaces (brick, porous concrete etc.)
- For almost non-porous trowelled layers, minimises air bubbles coming through from the subsurfaces.
- For interior walls and floors, as well as interior and exterior ceiling applications.

General Data

Description	Weight (kg/m)	Packaging (pcs)	Shelf Life	Material Number
Aquapanel® Interior Primer	15	1	18 month	49279

Technical Data

Description	Dilution (Aquapanel® Board Primer/water)	Coverage/m ² (Concentrate per m ²)*	Drying time (at 23 °C and 50 % rel. humidity)
Aquapanel® floor	1:1	50 g	3 hour
Aquapanel® indoor	1:2	40 - 60 g	12 hour
Bricks, concretes etc.	1:4	50 - 100 g	12 hour
Wood and wood product substrates	1:1	60 - 80 g	approx. 6 hours
Old tiles, terrazzo	undiluted	70 - 100 g	approx. 3 hours

* Depending on the absorbency of the background

System Performance Values

Performance values as sound insulation, fire resistance etc. may differ acc. to the drywall system to be applied. Please check the performance values of the drywall systems;

[Knauf Technical Website](#)
[Document Center](#)

Application

Application should be done acc. to the applicable standards (TS 1475) and acc. to the Knauf Technical Brochures of the respective drywall system.

▶ 444 YAPI - 9274

▶ www.knauf.com.tr / www.teknik.knauf.com.tr

▶ teknik@knauf.com

Center: Knauf Moment Beştepe Office, Beştepe Mah. 32.Cadde No:1/212-218 06560 Beştepe-Yenimahalle
/ ANKARA Tel: 0312 297 0100 Faks: 0312 266 4506