



AMF TOPIQ® Efficient Pro



- AMF TOPIQ® Efficient Pro is a very light stone wool panel with a modern, smooth surface
- Excellent sound absorption (1.00 $\alpha_{\rm w}$
- Excellent light reflectance (88%)
- ISO 4
- Ideal for offices, classrooms, learning applications and underground garages





AMF TOPIQ® EFFICIENT PRO



Edge details Additional edge details on request	Board	Tegular 24/90		Tegular 15/90			
Thickness (mm)	20	20		20			
Dimensions (mm) Additional sizes on request	600 × 600 625 × 625 1200 × 600	600 x 600 625 x 625		600 x 600 625 x 625			
System	Exposed demountable - System C						
Weight	$2.8 \text{ kg}/\text{m}^2$						
Colour	White						
Sound absorption	EN ISO 354 α_{w} = 1.00 as per EN ISO 11654 - Frequency f (Hz) α_{p} NRC = 0.95 as per ASTM C 423		25 250 45 0.90		1000	2000	4000
Sound attenuation	EN ISO 10848-2 D _{n,f,w} = 25 dB as per EN ISO 717-1 CAC = 25 dB as per ASTM E 413-10						
Sound reduction	EN ISO 10140-2 R _w = 15 dB as per EN ISO 717-1						
Fire reaction	Euroclass A1 as per EN 13501-1	RUS KM2 (RUS KM2 (G1, V1, D1, T1) as per 123-FZ				
Light reflectance	88%						
Humidity resistance	100% RH						
Clean room	ISO 4 as per EN ISO 14644-1						
Indoor air quality	A E1 IAC						
Cleanability		760°					
Sustainability	8000LUBLE WOOL SO 140021 EC LIZZIZZOBO Arross Q EC LIZZIZZOBO Arross Q	M DHIGT.	r-engel.de/uz132				



