



CEIL NR | CHALK NR INDUSTRIAL PLASTER

Ceil NR and Chalk NR are fine and very white Beta plasters produced using high purity gypsum from Thailand. The fine particle size and low cost make them suitable for a variety of applications, from simple architectural castings to formulation and fillers.

TYPICAL PHYSICAL PROPERTIES

Product	CEIL NR	CHALK NR
Plaster to Water Ratio (%P/W)	135	100
Water to Plaster Ratio (%W/P)	74	100
Initial Setting Time by Knife Setting (minutes)	6 - 22	4 - 6.5
Final Setting Time by Shore A (minutes)	≤45	10 - 16
Fluidity by Schmidt Ring (mm)	140 - 220	130 - 250

INSTRUCTIONS

STORAGE AND USE

When properly used, Plaster is safe to handle and easy to work with. Keep indoors in a dry, stable environment. Do not stack more than two pallets high. Keep from drafts. Rotate stock Always follow handling and use directions and safety warnings on the package.

SHELF LIFE

Best before 6 months from manufacture.

For more Information
please e-mail: jp-knauf-th@knauf.com

Manufactured by
Knauf Gypsum Co., Ltd.
80 Moo 5, Nongplakradi Road,
Nongplamoh, Nongkhae, Saraburi 18140
Tel: +66(0) 36374526-8