

Note on English translation / Hinweise zur englischen Fassung

This is a translation of the product data sheet valid in Germany.

All stated details and properties are in compliance with the regulations of the German standards and building regulations. They are only applicable for the specified products, system components, application rules, and construction details in connection with the specifications of the respective certificates and approvals.

Knauf Gips KG denies any liability for applications outside of Germany as this requires changes acc. to the respective national standards and building regulations.



Drywall Systems

K713A.de

Product Data Sheet

2023-03



DIY Board GKF

Narrow gypsum board for drylining and basis systems in drywalling

Product description

DIY Boards GKF are 600 mm narrow gypsum boards. They are particularly suitable for use as dry lining thanks to their format. The gypsum boards have a fibre-reinforced gypsum core for enhanced stability and fire resistance quality.

- Board type
DIN 18180
EN 520
- Colour of board liner
- Rear side marking

GKF
DF
grey
red

Storage

Store boards on board pallets in a dry environment.

Quality

In compliance with EN 520, the product is subject to initial type testing and continuous factory production control and bears the CE marking.

Properties and added value

- Convenient format
- Simple and fast one man installation
- Non-combustible
- Good coherence of structure when exposed to fire
- Bendable
- Folding with mitring is possible

Narrow gypsum board for drylining and basis systems in drywalling

Field of application

DIY Boards GKF are used in all fields of interior works as dry lining or as cladding in drywall systems. The narrow format especially suitable for construction in existing structures.

Suitable for the following systems:

- Dry lining
- Ceiling linings and suspended ceilings
- Attic linings

Design

Application

Note

Application should be undertaken in accordance to the applicable standards and acc. to the relevant Knauf system data sheets for drywall systems.

Technical data

Description	Standard	Unit	DIY Board GKF 12.5
Board type Germany	DIN 18180	–	GKF
Board type European	EN 520	–	DF
Reaction to fire	EN 13501-1	Class	A2-s1, d0 (B)
Width dimensional tolerance	EN 520	mm	+0 / -4
Length dimensional tolerance	EN 520	mm	+0 / -5
Thickness dimensional tolerance	EN 520	mm	+0.5 / -0.5
Angularity dimensional tolerance	EN 520	mm per m board width	≤ 2.5
Thermal conductivity λ	EN ISO 10456	W/(m·K)	0.23
Shrinkage and expansion per 1 % change of relative air humidity	–	mm/m	0.005 – 0.008
Shrinkage and expansion per 1 Kelvin change of temperature	–	mm/m	0.013 – 0.02
Long term temperature exposure (max. limit)	–	°C	≤ 50
Density	–	kg/m ³	≥ 800
Flexural breaking load longitudinal direction	–	N	≥ 610
Flexural breaking load transverse direction	–	N	≥ 210
Board weight	–	kg/m ²	approx. 10
Water vapour resistance factor μ dry	EN ISO 10456	–	10
Water vapour resistance factor μ wet	EN ISO 10456	–	4
Bending radius dry	–	mm	≥ 2750
Bending radius wet	–	mm	≥ 1000
Characteristic compressive strength $f_{c,90,k}$ (for out of plane loads)	EN 1995-1-1/NA	N/mm ²	≥ 5.5
Characteristic bending tensile strength $f_{m,k}$ longitudinal direction (for out of plane loads)	EN 1995-1-1/NA	N/mm ²	≥ 6.5
Characteristic bending tensile strength $f_{m,k}$ transverse direction (for out of plane loads)	EN 1995-1-1/NA	N/mm ²	≥ 2
Mean E modulus E_{mean} longitudinal direction (for out of plane loads)	EN 1995-1-1/NA	N/mm ²	≥ 2800
Mean E modulus E_{mean} transverse direction (for out of plane loads)	EN 1995-1-1/NA	N/mm ²	≥ 2200

Order information

Description	Width	Length	Thick-ness	Edges	Delivery weight	Packaging unit	Material number	EAN
DIY Board GKF 12.5	600 mm	2600 mm	12.5 mm	SSK HRK	approx. 10.5 kg/m ²	60 pieces / pallet 93.6 m ² / pallet	00008266	4003982001771

SSK = Front cut square edge

HRK = Half-rounded edge

Sustainability and environment

Short description	Unit	Value
Requirements of the German AgBB-scheme	–	fulfilled
Complies with the requirements of the French emission class	–	A+
LEED requirements	–	fulfilled
BREEAM requirements	–	Exemplary Level
Eurofins Indoor Air Comfort Gold®	–	fulfilled
Recycling share post-consumer	%	4
Environmental product declaration	–	EPD-BVG-20210343-IBE1-DE



Observe the safety data sheet!

For safety data sheets and CE marking see
pd.knauf.de



Videos for Knauf systems and products can be found under the following link:

youtube.com/knauf



The Knauf Infothek App now provides all the current information and documents from Knauf Gips KG at any time and in every location in a clear and comfortable way.

knauf.de/infothek

Knauf Direct

Technical Advisory Service:

knauf-direkt@knauf.com

www.knauf.de

Knauf Gips KG Am Bahnhof 7, 97346 Iphofen, Germany

All technical changes reserved. Only the current printed instructions are valid. The stated information represents current state-of-the-art Knauf technology. The entire state of approved engineering rules, appropriate standards, guidelines, and rules of craftsmanship are not included herewith. These and all application instructions have to be adhered to separately by the installer. Our warranty is expressly limited to our products in flawless condition. All application quantities and delivery amounts are based on empirical data that are not easily transferable to other deviating areas.

All rights reserved. All amendments, reprints and photocopies, including those of excerpts, require our expressed permission.